

ISO 16293-2:2025-04 (E)

Glass in building - Basic soda lime silicate glass products - Part 2: Float glass

| Contents | | Page |
|---|--|-------------|
| Foreword | | iv |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Dimensional requirements | 3 |
| 4.1 | Thickness | 3 |
| 4.1.1 | General | 3 |
| 4.1.2 | Tolerances | 3 |
| 4.2 | Length, width and squareness | 4 |
| 4.2.1 | Stock sizes | 4 |
| 4.2.2 | Final cut sizes | 4 |
| 5 | Quality requirements | 4 |
| 5.1 | General | 4 |
| 5.2 | Methods of observation and measurement | 5 |
| 5.2.1 | Optical imperfection | 5 |
| 5.2.2 | Visual blemish | 6 |
| 5.2.3 | Edge imperfection for final cut sizes | 6 |
| 5.3 | Acceptance levels | 7 |
| 5.3.1 | Optical imperfections | 7 |
| 5.3.2 | Spot blemish | 8 |
| 5.3.3 | Linear/extended blemish | 8 |
| 5.3.4 | Edge imperfection for final cut sizes | 8 |
| 6 | Designation | 9 |
| Annex A (informative) Method for measuring the halo size of spot fault | | 10 |