

ISO 834-1:2025-05 (E)

Fire-resistance tests - Elements of building construction - Part 1: General requirements

| Contents | | Page |
|-----------------|--|-------------|
| Foreword | | v |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Symbols | 3 |
| 5 | Test equipment | 3 |
| 5.1 | General | 3 |
| 5.2 | Furnace | 4 |
| 5.3 | Loading equipment | 4 |
| 5.4 | Restraint and support frames | 4 |
| 5.5 | Instrumentation | 4 |
| 5.5.1 | Temperature | 4 |
| 5.5.2 | Pressure | 8 |
| 5.5.3 | Load | 10 |
| 5.5.4 | Deformation | 10 |
| 5.5.5 | Integrity | 10 |
| 5.6 | Accuracy of measuring equipment | 11 |
| 6 | Test conditions | 12 |
| 6.1 | Furnace temperature | 12 |
| 6.1.1 | Heating curves | 12 |
| 6.1.2 | Tolerances | 17 |
| 6.2 | Furnace pressure differential | 17 |
| 6.2.1 | General | 17 |
| 6.2.2 | Vertical elements | 17 |
| 6.2.3 | Horizontal elements | 18 |
| 6.3 | Loading | 18 |
| 6.4 | Restraint/boundary conditions | 18 |
| 6.5 | Ambient conditions | 18 |
| 6.6 | Deviation from specified test conditions | 18 |
| 6.7 | Calibration | 19 |
| 6.8 | Furnace atmosphere | 19 |
| 7 | Test specimen preparation | 19 |
| 7.1 | Construction | 19 |
| 7.2 | Size | 19 |
| 7.3 | Number of test specimens | 20 |
| 7.4 | Conditioning | 20 |
| 7.5 | Test specimen verification | 20 |
| 8 | Application of instrumentation | 21 |
| 8.1 | Temperature | 21 |
| 8.1.1 | Furnace thermocouples (plate thermometers) | 21 |
| 8.1.2 | Unexposed surface thermocouples | 21 |
| 8.1.3 | Roving thermocouple | 22 |
| 8.1.4 | Interior thermocouples | 22 |
| 8.2 | Pressure | 22 |
| 8.2.1 | Furnaces for vertical elements | 22 |

| | | |
|--|--|-----------|
| 8.2.2 | Furnaces for horizontal elements | 22 |
| 8.3 | Deformation | 22 |
| 8.4 | Integrity | 22 |
| 8.4.1 | Cotton wool pad | 22 |
| 8.4.2 | Gap gauges | 23 |
| 9 | Test procedure | 23 |
| 9.1 | Restraint application | 23 |
| 9.2 | Load application | 23 |
| 9.3 | Commencement of test | 24 |
| 9.4 | Measurements and observations | 24 |
| 9.4.1 | General | 24 |
| 9.4.2 | Temperature | 24 |
| 9.4.3 | Furnace pressure | 24 |
| 9.4.4 | Deformation | 24 |
| 9.4.5 | Integrity | 24 |
| 9.4.6 | Load and restraints | 25 |
| 9.4.7 | General behaviour | 25 |
| 9.5 | Termination of test | 25 |
| 10 | Performance criteria | 25 |
| 10.1 | General | 25 |
| 10.2 | Specific performance criteria | 25 |
| 10.2.1 | General | 25 |
| 10.2.2 | Loadbearing capacity | 26 |
| 10.2.3 | Integrity | 26 |
| 10.2.4 | Insulation | 27 |
| 11 | Validity of the test | 27 |
| 12 | Expression of test results | 27 |
| 12.1 | Fire resistance | 27 |
| 12.2 | Performance criteria | 27 |
| 12.2.1 | Insulation and integrity versus loadbearing capacity | 27 |
| 12.2.2 | Insulation versus integrity | 27 |
| 12.3 | Termination prior to failure | 27 |
| 12.4 | Expression of test result | 27 |
| 13 | Test report | 28 |
| Annex A (informative) Commentary on test method and guide to the application of the outputs from the fire resistance test | | 29 |
| Bibliography | | 47 |