

# ISO/TR 22099:2025-05 (E)

## Application examples for using reaction-to-fire test data for fire safety engineering

---

| <b>Contents</b>    |   | <b>Page</b> |
|--------------------|---|-------------|
| Foreword .....     |   | iv          |
| Introduction ..... |   | v           |
| <b>1</b>           | <b>Scope .....</b>  | <b>1</b>    |
| <b>2</b>           | <b>Normative references .....</b>   | <b>1</b>    |
| <b>3</b>           | <b>Terms, definitions and abbreviated terms .....</b>   | <b>1</b>    |
| <b>3.1</b>         | <b>Abbreviated terms .....</b>  | <b>1</b>    |
| <b>4</b>           | <b>Example 1: Using mass loss data for a single burning item as input for computational fluid dynamics (CFD) calculations .....</b>         | <b>1</b>    |
| <b>4.1</b>         | <b>Introduction .....</b>   | <b>1</b>    |
| <b>4.2</b>         | <b>Experimental investigations .....</b>  | <b>1</b>    |
| <b>4.3</b>         | <b>Numerical investigations .....</b>   | <b>4</b>    |
| <b>4.4</b>         | <b>Discussion of the results .....</b>  | <b>7</b>    |
| <b>4.5</b>         | <b>Conclusions .....</b>  | <b>8</b>    |
| <b>5</b>           | <b>Example 2: Using cone calorimeter and LIFT apparatus data as input for flame spread calculations .....</b>                               | <b>9</b>    |
| <b>5.1</b>         | <b>Reaction to fire tests for flame spread calculations .....</b>   | <b>9</b>    |
| <b>5.1.1</b>       | <b>Overview .....</b>   | <b>9</b>    |
| <b>5.1.2</b>       | <b>Cone calorimeter tests .....</b>   | <b>9</b>    |
| <b>5.1.3</b>       | <b>Lateral ignition and flame transport (LIFT) test .....</b>   | <b>10</b>   |
| <b>5.2</b>         | <b>Methods to derive material properties for flame spread .....</b>   | <b>11</b>   |
| <b>5.2.1</b>       | <b>Parameters calculated from cone calorimeter tests .....</b>  | <b>11</b>   |
| <b>5.2.2</b>       | <b>Parameters measured by LIFT tests .....</b>  | <b>17</b>   |
| <b>5.3</b>         | <b>An example of derivation of properties .....</b>   | <b>19</b>   |
| <b>5.3.1</b>       | <b>Specimen .....</b>   | <b>19</b>   |
| <b>5.3.2</b>       | <b>Properties derived from Cone calorimeter tests[19] .....</b>   | <b>19</b>   |
| <b>5.3.3</b>       | <b>Properties derived from LIFT tests .....</b>   | <b>22</b>   |
| <b>5.4</b>         | <b>Prediction of flame spread over lining materials .....</b>   | <b>25</b>   |
| <b>5.4.1</b>       | <b>Overview .....</b>   | <b>25</b>   |
| <b>5.4.2</b>       | <b>Schematics of model .....</b>  | <b>25</b>   |
| <b>5.4.3</b>       | <b>Ignition of wall surface .....</b>   | <b>26</b>   |
| <b>5.4.4</b>       | <b>Heat release rate .....</b>  | <b>27</b>   |
| <b>5.4.5</b>       | <b>Upward flame spread .....</b>  | <b>27</b>   |
| <b>5.4.6</b>       | <b>Lateral and downward flame spread .....</b>  | <b>28</b>   |
| <b>5.4.7</b>       | <b>Smoke layer temperature .....</b>  | <b>28</b>   |
| <b>5.4.8</b>       | <b>Calculation procedure .....</b>  | <b>28</b>   |
| <b>5.5</b>         | <b>Comparison with an experiment .....</b>  | <b>28</b>   |
| <b>5.5.1</b>       | <b>Experimental conditions and procedure .....</b>  | <b>28</b>   |
| <b>5.5.2</b>       | <b>Experimental results .....</b>   | <b>30</b>   |
| <b>5.5.3</b>       | <b>Calculation conditions .....</b>   | <b>32</b>   |
| <b>5.5.4</b>       | <b>Calculation results .....</b>  | <b>33</b>   |
| <b>5.6</b>         | <b>Summary of example 2 .....</b>   | <b>35</b>   |
| <b>6</b>           | <b>Example 3: Using mass loss data for a single burning item as input for zone model calculations including fuel response effects .....</b> | <b>35</b>   |
| <b>6.1</b>         | <b>General .....</b>  | <b>35</b>   |
| <b>6.2</b>         | <b>Experimental investigations .....</b>  | <b>36</b>   |
| <b>6.3</b>         | <b>Numerical investigations .....</b>   | <b>37</b>   |
| <b>6.4</b>         | <b>Discussion of the results .....</b>  | <b>37</b>   |
| Bibliography ..... |   | 41          |