DIN 18008-6:2026-02 (E)

Glass in building - Design and construction rules - Part 6: Additional requirements for walk-on glazing in case of maintenance procedures and for fall-through glazing

Contents

Page

Foreword 3

1 Scope 4

2 Normative references 4

3 Terms and definitions, symbols and units 4
3.1 Terms and definitions 4
3.2 Symbols and units 5

4 Construction products 5

5 Application conditions 5

6 Effects of actions and verification 8
6.1 General 8
6.2 Limit states for static actions 8
6.3 Limit states for impact actions and residual load-bearing capacity 8

Annex A (normative) Verification of impact resistance and residual load-bearing capacity by building component tests 9

A.1 Test equipment 9
A.2 Test set-up 9
A.3 Test conditions 10
A.4 Verification of impact resistance 12
A.5 Verification of residual load-bearing capacity 13
A.6 Test report 14

Annex B (normative) Verification of impact resistance and residual load-bearing capacity of glass structures by calculation 15

B.1 General 15
B.2 Action 15
B.3 Distinction between walk-on and fall-through glazing 15
B.4 Verification of insulating glazing units 16
B.5 Verification of laminated safety glass 17

Bibliography 18

Figures Figure 1 -- Distinction between walk-on and fall-through glazing 7

Figure A.1 -- Examples of a test apparatus with an impact body: pendulum (left) or impactor holding equipment (right) 9

Figure A.2 -- Principle of the test set-up 10

Figure A.3 -- Area of the impact points 11

Figure A.4 -- Impact points for damaging the pane facing the impact 13

Figure A.5 -- Residual load-bearing capacity test 13

Figure B.1 -- Basic energy in relation to the installation angle 16