

DIN 18008-6:2026-02 (E)

Glass in building - Design and construction rules - Part 6: Additional requirements for walk-on glazing in case of maintenance procedures and for fall-through glazing

Contents

Page

Foreword	3
1 Scope	4
2 Normative references	4
3 Terms and definitions, symbols and units	4
3.1 Terms and definitions	4
3.2 Symbols and units	5
4 Construction products	5
5 Application conditions	5
6 Effects of actions and verification	8
6.1 General	8
6.2 Limit states for static actions	8
6.3 Limit states for impact actions and residual load-bearing capacity	8
Annex A (normative) Verification of impact resistance and residual load-bearing capacity by building component tests	9
A.1 Test equipment	9
A.2 Test set-up	9
A.3 Test conditions	10
A.4 Verification of impact resistance	12
A.5 Verification of residual load-bearing capacity	13
A.6 Test report	14
Annex B (normative) Verification of impact resistance and residual load-bearing capacity of glass structures by calculation	15
B.1 General	15
B.2 Action	15
B.3 Distinction between walk-on and fall-through glazing	15
B.4 Verification of insulating glazing units	16
B.5 Verification of laminated safety glass	17
Bibliography	18
Figures Figure 1 -- Distinction between walk-on and fall-through glazing	7
Figure A.1 -- Examples of a test apparatus with an impact body: pendulum (left) or impactor holding equipment (right)	9
Figure A.2 -- Principle of the test set-up	10
Figure A.3 -- Area of the impact points	11
Figure A.4 -- Impact points for damaging the pane facing the impact	13
Figure A.5 -- Residual load-bearing capacity test	13
Figure B.1 -- Basic energy in relation to the installation angle	16