DIN EN 1793-5:2026-07 (E)

Road traffic noise reducing devices - Test method for determining the acoustic performance - Part 5: Intrinsic characteristics - Sound absorption under direct sound field conditions

Contents

Page

European foreword 4

Introduction 6

1 Scope 8

2 Normative references 8

3 Terms and definitions 8

4 Symbols and abbreviations 14

5 Sound reflection index measurements 16
5.1 General principle 16
5.2 Measured quantity 17
5.3 Test arrangement 20
5.3.1 General 20
5.3.2 Tests on purposely built full-size test specimens 20
5.3.3 Installed road traffic noise reducing devices 21
5.3.4 Inclined or curved road traffic noise reducing devices 23
5.4 Measuring equipment 26
5.4.1 Components of the measuring system 26
5.4.2 Sound source 27
5.4.3 Test signal 27
5.5 Data processing 28
5.5.1 Calibration 28
5.5.2 Sample rate and filtering 29
5.5.3 Background noise 30
5.5.4 Signal subtraction technique 31
5.5.5 Accurate alignment procedure 32
5.5.6 Adrienne temporal window 34
5.5.7 Placement of the Adrienne temporal window 36
5.5.8 Maximum sampled area 38
5.6 Positioning of the measuring equipment 39
5.6.1 General 39
5.6.2 Selection of the measurement positions 39
5.6.3 Consideration of relevant and parasitic reflections 47
5.6.4 Low-frequency limit 50
5.6.5 Reflecting objects 51
5.6.6 Safety considerations 51
5.7 Test specimen surface and meteorological conditions 51
5.7.1 Condition of the test specimen surface 51
5.7.2 Wind 51
5.7.3 Air temperature 51
5.8 Single-number rating of sound absorption under a direct sound field DLRI 51

6 Measurement uncertainty 52

7 Measuring procedure 52

8 Test report 53

Annex A (informative) Low-frequency limit and window width 55

Annex B (normative) Measurement uncertainty 60

Annex C (normative) Template of test report on sound reflection index of road traffic noise reducing devices 62

Annex D (normative) Indoor measurements for product qualification 71

Bibliography 72