

DIN EN 14309:2010-03 (E)

Thermal insulation products for building equipment and industrial installations - Factory made products of expanded polystyrene (EPS) - Specification

Contents		Page
Foreword		4
1	Scope	6
2	Normative references	6
3	Terms, definitions, symbols, units and abbreviated terms	8
4	Requirements	11
5	Test methods	20
6	Designation code	24
7	Evaluation of Conformity	25
8	Marking and labelling	26
Annex A (normative) Factory production control		27
Annex B (normative) Product classification		34
Annex C (normative) Determination of minimum service temperature		35
Annex D (informative) Additional properties		39
Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU Construction Products Directive		42
Bibliography		50
Figures	Figure A.1 -- Relationship between compressive stress at 10 % deformation and apparent density for indirect testing; 1 - = 90; n = 495	31
	Figure A.2 -- Relationship between declared thermal conductivity (at 50 mm reference thickness and 10 °C mean temperature) and apparent density for indirect testing; 1 - = 90; n = 3 873	32
	Figure ZA.1 -- Example of CE marking information	49
Tables	Table 1 -- Dimensional tolerances	12
	Table 2 -- Classes of dimensional stability under normal laboratory conditions	13
	Table 3 -- Levels of dimensional stability under specified temperature and humidity conditions	15
	Table 4 -- Levels for compressive stress at 10 % deformation	15
	Table 5 -- Levels for tensile strength perpendicular to faces	16
	Table 6 -- Levels of bending strength	16

Table 7 -- Levels for long time water absorption by total immersion	17
Table 8 -- Levels for long time water absorption by diffusion	18
Table 9 -- Levels for dynamic stiffness	19
Table 10 -- Classes for thickness tolerances	19
Table 11 -- Levels for compressibility	20
Table 12 -- Test methods, test specimens, conditions	22
Table A.1 -- Minimum product testing frequencies	27
Table A.2 -- Minimum product testing frequencies for the reaction to fire characteristics	29
Table A.3 -- Thickness effect parameter, L, for the determination of the declared thermal conductivity, D 33	
Table B.1 -- Classification of EPS products	34
Table B.2 -- Classification of load bearing EPS products with acoustical properties	34
Table D.1 -- Correlation between bending strength and shear strength	39
Table D.2 -- Tabulated values of water vapour diffusion resistance index and water vapour permeability	40
Table D.3 -- Test methods	41
Table ZA.1 -- Relevant clauses	43
Table ZA.2 -- System(s) of attestation of conformity	44
Table ZA.3 -- Assignment of evaluation of conformity tasks for products under system 1	45
Table ZA.4 -- Assignment of evaluation of conformity tasks for products under system 3 or system 3 combined with system 4 for reaction to fire	46