

DIN EN 14064-1:2010-06 (E)

Thermal insulation products for buildings - In-situ formed loose-fill mineral wool (MW) products - Part 1: Specification for the loose-fill products before installation

| Contents | | Page |
|----------------------------|--|-------------|
| Foreword | | 5 |
| 1 | Scope | 7 |
| 2 | Normative references | 7 |
| 3 | Terms, definitions, symbols and abbreviations | 8 |
| 3.1 | Terms and definitions | 8 |
| 3.2 | Symbols and abbreviations | 8 |
| 4 | Requirements | 9 |
| 4.1 | General | 9 |
| 4.2 | For all applications | 10 |
| 4.2.1 | Thermal conductivity - Thermal resistance | 10 |
| 4.2.2 | Weight of the sale unit | 10 |
| 4.2.3 | Settlement | 10 |
| 4.2.4 | Reaction to fire | 12 |
| 4.2.5 | Durability characteristics | 12 |
| 4.3 | For specific applications | 13 |
| 4.3.1 | General | 13 |
| 4.3.2 | Airflow resistivity | 13 |
| 4.3.3 | Water absorption | 13 |
| 4.3.4 | Water vapour diffusion resistance | 13 |
| 4.3.5 | Reaction to fire of product in standardized assemblies simulating end-use applications .. | 13 |
| 4.3.6 | Release of dangerous substances | 13 |
| 4.3.7 | Continuous glowing combustion | 14 |
| 5 | Test methods | 14 |
| 5.1 | Sampling | 14 |
| 5.2 | Conditioning | 14 |
| 5.3 | Testing | 14 |
| 5.3.1 | General | 14 |
| 5.3.2 | Thermal resistance and thermal conductivity | 15 |
| 5.3.3 | Reaction to fire | 16 |
| 6 | Designation code | 16 |
| 7 | Evaluation of conformity | 16 |
| 7.1 | General | 16 |
| 7.2 | Initial type testing | 17 |
| 7.3 | Factory production control | 17 |
| 8 | Marking and labelling | 17 |
| Annex A (normative) | Determination of the declared values of thermal resistance and thermal conductivity | 20 |
| A.1 | Introduction | 20 |
| A.2 | Input data | 20 |
| A.3 | Declared values | 20 |
| A.3.1 | General | 20 |

| | | |
|---|---|----|
| A.3.2 | Case where thermal resistance and thermal conductivity are declared | 21 |
| A.3.3 | Case where only thermal resistance is declared | 22 |
| Annex B (normative) Factory production control | | 23 |
| Annex C (normative) Specimen preparation method for thermal resistance and thermal conductivity test | | 25 |
| C.1 | Principle | 25 |
| C.2 | Procedure | 25 |
| C.2.1 | Specimen preparation method for ventilated roof spaces application | 25 |
| C.2.2 | Specimen preparation method for closed cavities application | 26 |
| Annex D (normative) Specimen preparation method for water absorption test | | 27 |
| D.1 | Principle | 27 |
| D.2 | Procedure | 27 |
| Annex E (normative) Specimen preparation method for airflow resistivity test | | 28 |
| E.1 | Principle | 28 |
| E.2 | Procedure | 28 |
| Annex F (normative) Testing for reaction to fire of products | | 29 |
| F.1 | Scope | 29 |
| F.2 | Product and installation parameters | 29 |
| F.3 | Standardized Mounting and fixing | 30 |
| F.3.1 | Test specimens for EN ISO 11925-2 (Ignitability) and EN 13823 (SBI) | 30 |
| F.3.2 | EN ISO 11925-2 (Ignitability) | 30 |
| F.3.3 | EN 13823 (SBI) | 30 |
| Annex G (normative) Testing for reaction to fire of products in standardised assemblies simulating end-use application(s) | | 31 |
| G.1 | Scope | 31 |
| G.2 | Product and installation parameters | 31 |
| G.3 | Standardized Mounting and fixing | 32 |
| G.3.1 | Test specimens for EN ISO 11925-2 (Ignitability) and EN 13823 (SBI) | 32 |
| G.3.2 | EN ISO 11925-2 (Ignitability) | 32 |
| G.3.3 | EN 13823 (SBI) | 32 |
| Annex H (normative) Rules for creating performance charts for loose-fill insulation and examples of performance charts | | 33 |
| H.1 | General | 33 |
| H.2 | Performance chart for loft insulation | 33 |
| H.3 | Performance chart for masonry cavity wall insulation and frame constructions insulation | 34 |
| Annex I (normative) Verification of performance chart according to Annex H (normative) | | 36 |
| I.1 | Principle | 36 |
| I.2 | Procedure | 36 |
| Annex J (normative) Specimen preparation method for coverage and density measurement | | 37 |
| J.1 | Principle | 37 |
| J.2 | Procedure for ventilated roof space application | 37 |
| J.3 | Procedure for closed construction | 38 |

| | |
|---|-----------|
| Annex K (normative) Thermal insulating products for lofts - Determination of settlement for blown loose fill insulation | 39 |
| K.1 Principle | 39 |
| K.2 Apparatus | 39 |
| K.3 Test specimens | 39 |
| K.4 Test procedure | 39 |
| K.5 Calculations and expression of results | 40 |
| K.6 Test report | 40 |
| Annex L (informative) Masonry cavity walls - Method for determining suitable spacings for blowing holes | 42 |
| L.1 Test house | 42 |
| L.2 Test method | 42 |
| L.3 Observations | 42 |
| L.4 Installation procedure | 42 |
| Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU Construction Products Directive | 45 |
| ZA.1 Scope and relevant characteristics | 45 |
| ZA.2 Procedures for attestation of conformity of in-situ formed loose-fill mineral wool (MW) products | 46 |
| ZA.2.1 Systems of attestation of conformity | 46 |
| ZA.2.2 EC certificate and declaration of conformity | 49 |
| ZA.3 CE Marking and labelling | 51 |
| Bibliography | 54 |