ISO 15099:2003-11 (E)

Thermal performance of windows, doors and shading devices - Detailed calculations

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Symbols 2
3.1 General 2
3.2 Symbols and units 2
3.3 Subscripts 4

4 Determination of total window and door system properties 5
4.1 Thermal transmittance 5
4.2 Total solar energy transmittance 9
4.3 Visible transmittance 10

5 Vision area properties 10
5.1 Glazing layer optics 10
5.2 Glazing system optics 11
5.3 Vision area heat transfer 13

6 Frame effects 20
6.1 Area and lineal thermal transmittance 20
6.2 Governing equations for calculating thermal transmittance 20
6.3 Geometric representation and meshing 20
6.4 Solid materials 23
6.5 Effective conductivity -- Glazing cavities 23
6.6 Effective conductivity -- Unventilated frame cavities 23
6.7 Ventilated air cavities and grooves 30

7 Shading devices 31
7.1 Definitions 31
7.2 Optical properties 32
7.3 Slat type of shading 34
7.4 Ventilation 39
7.5 Total solar energy transmittance and thermal transmittance 50

8 Boundary conditions 50
8.1 General 50
8.2 Reference boundary conditions 50
8.3 Convective heat transfer 51
8.4 Longwave radiation heat transfer 55
8.5 Combined convective and radiative heat transfer 58
8.6 Prescribed density of heat flow rate 59

Annex A (informative) Solution technique for the multi-layer solar optical model 60

Annex B (normative) Thermophysical fill gas property values 62

Annex C (informative) Examples of calculated values for optical properties of slat type of shading devices 64

Bibliography 69