

DIN EN 15434:2006-08 (E)

Glass in building - Product standard for structural and/or ultra-violet resistant sealant (for use with structural sealant glazing and/or insulating glass units with exposed seals)

| Contents | | Page |
|-----------------|---|-------------|
| Foreword | | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 7 |
| 4 | Sealant | 8 |
| 4.1 | General | 8 |
| 4.2 | The compulsory part of the product description | 8 |
| 5 | Requirements | 9 |
| 5.1 | General | 9 |
| 5.1.1 | Identification - performances | 9 |
| 5.1.2 | Application | 9 |
| 5.2 | Identification tests | 9 |
| 5.2.1 | General | 9 |
| 5.2.2 | Thermogravimetric analysis | 10 |
| 5.2.3 | Specific gravity | 10 |
| 5.2.4 | Shore A hardness | 10 |
| 5.2.5 | Change in volume or shrinkage | 10 |
| 5.2.6 | Infrared spectrometer analysis | 11 |
| 5.3 | Intrinsic properties | 11 |
| 5.3.1 | General | 11 |
| 5.3.2 | Standard substrates and test pieces | 11 |
| 5.3.3 | Tensile | 12 |
| 5.3.4 | Shear at 23 °C | 13 |
| 5.3.5 | Elastic recovery | 13 |
| 5.3.6 | Tear strength | 14 |
| 5.3.7 | Mechanical cyclic load | 15 |
| 5.3.8 | Displacement under permanent shear load (creep test) | 16 |
| 5.3.9 | Elastic modulus of the sealant | 19 |
| 5.4 | Environmental influences | 19 |
| 5.4.1 | General | 19 |
| 5.4.2 | Determination of cohesion/adhesion properties after exposure to artificial light through glass and to water | 19 |
| 5.4.3 | Salt spray | 21 |
| 5.4.4 | SO ₂ atmosphere | 21 |
| 5.4.5 | Façade cleaning products | 22 |
| 5.4.6 | High temperature | 22 |
| 5.5 | Water vapour transmission and gas transmission | 22 |
| 5.6 | Reaction to fire | 22 |
| 5.7 | Dangerous substances | 23 |
| 5.8 | Thin layer outer seal of insulating glass unit category differentiation" | 23 |
| 6 | Sealing and bonding | 23 |
| 7 | Compatibility with adjacent material | 23 |

| | | |
|--|---|----|
| 8 | Evaluation of conformity | 28 |
| 8.1 | General or scope | 28 |
| 8.2 | Requirements | 28 |
| 8.2.1 | Product description | 28 |
| 8.2.2 | Conformity with the definition of sealant | 28 |
| 8.2.3 | Determination of the characteristic's performances | 28 |
| 8.2.4 | Durability | 29 |
| 8.2.5 | Dangerous substances | 30 |
| 8.3 | Evaluation of conformity | 30 |
| 8.3.1 | General | 30 |
| 8.3.2 | Initial type testing of the product (see Clause 5) | 30 |
| 8.3.3 | General | 30 |
| 8.4 | Factory production control and inspection of samples in accordance with a prescribed test plan (8.3.1.1, 1 a) and 1 b)) | 32 |
| 8.4.1 | General | 32 |
| 8.4.2 | Initial inspection of factory and of factory production control (8.3.1.1 1 b)) | 32 |
| 8.4.3 | Continuous surveillance and assessment of the factory production control (see 8.3.1.1 1 c)) | 33 |
| 9 | Marking and/or labelling | 34 |
| 9.1 | General | 34 |
| 9.2 | Labelling | 34 |
| 9.3 | Product marking | 34 |
| 9.4 | Product characteristics | 34 |
| 9.5 | "Characteristics/performance identification paper" | 34 |
| Annex A (normative) Evaluation of tests results | | 36 |
| A.1 | Evaluation of the characteristic values $R_{u,5}$ | 36 |
| A.2 | Evaluation of the rigidity modulus at the origin | 37 |
| A.3 | Secant modulus, tangent modulus and shear modulus | 37 |
| A.4 | Stiffness | 39 |
| Annex B (normative) Shear at 23 °C: Test method | | 43 |
| Annex C (normative) Factory production control | | 45 |
| C.1 | Factory Production Control requirements | 45 |
| C.1.1 | General | 45 |
| C.1.2 | Organisation | 45 |
| C.1.3 | Control system | 45 |
| C.2 | Marking | 46 |
| C.3 | Inspection and testing tables of Sealants production | 46 |
| C.3.1 | Information on Tables C.1 | 46 |
| C.3.2 | Use of proxy testing | 47 |
| Annex D (normative) Thin layer outer seal of insulating glass category differentiation | | 50 |
| D.1 | General | 50 |
| D.2 | Test specimens and test samples | 50 |
| D.2.1 | Test specimen description (see Figure D.1) | 50 |
| D.2.2 | Number of test specimen | 51 |
| D.2.3 | Conditioning | 51 |
| D.3 | Dynamic shear testing | 52 |
| D.4 | Record | 52 |
| D.5 | Specifications and category differentiation | 52 |
| Annex E (normative) Formation of bubbles | | 54 |
| E.1 | Purpose of the test | 54 |
| E.2 | Test specimen description and conditioning | 54 |

| | | |
|------------|--|-----------|
| E.3 | Record and evaluation | 54 |
| | Annex F (informative) Sealing, structural bonding and UV resistance schematic illustrations | 56 |
| | Annex G (normative) Initial testing of bonding of sealant to non- glass substrates | 59 |
| G.1 | Bonding to coated surfaces of coated glass | 59 |
| G.2 | Metals | 59 |
| G.3 | Test specimens | 59 |
| G.4 | Description of the material | 59 |
| G.5 | Mechanical strength and adhesion: initial testing | 59 |
| G.6 | Test report | 60 |
| G.7 | Initial testing of specific projects | 60 |
| | Annex V (informative) Provisions for voluntary involvement of third party(ies) | 61 |
| V.1 | General | 61 |
| V.2 | Voluntary tasks for third parties | 61 |
| V.3 | Marking and labelling | 61 |
| | Bibliography | 62 |