DIN EN 1366-4:2006-08 (E)

Fire resistance tests for service installations - Part 4: Linear joint seals

Contents

Page

Foreword 4

Introduction 5

1 Scope 6

2 Normative references 6

3 Terms and definitions 6

4 Test equipment 7

5 Test conditions 7
5.1 Heating conditions 7
5.2 Pressure conditions 7

6 Test specimen 7
6.1 General 7
6.2 Size 8
6.3 Number of test specimens 8

7 Installation of test specimen 8
7.1 General 8
7.2 Supporting construction 8
7.2.1 General 8
7.2.2 Standard supporting construction 8
7.3 Test construction 9
7.4 Splice locations 9
7.5 Induced movement 10

8 Conditioning 10

9 Application of instrumentation 10
9.1 General 10
9.2 Thermocouples 10
9.2.1 Furnace thermocouples 10
9.2.2 Unexposed face thermocouples 10
9.2.3 Roving thermocouple 11
9.3 Deformation and deflection 11
9.4 Integrity measurement 11

10 Test procedure 11
10.1 General 11
10.2 Installation of test construction 11
10.3 Mechanically induced movement of the test specimen 11
10.4 Measurements and observations 11

11 Performance criteria 12
11.1 Insulation 12
11.2 Integrity 12
11.3 Expression of results 12

12 Test report 12

13 Field of direct application of test results 12
13.1 Orientation 12
13.2 Supporting construction 13
13.3 Seal position 14
13.4 Mechanically induced movement 14

Annex A (normative) Standard condition for linear joint seals with no mechanically induced movement of the joint faces 27

A.1 Standard condition 27
A.2 Test procedure 27

Annex B (normative) Standard condition for linear joint seals with mechanically induced movement of the joint faces 28

B.1 General 28
B.2 Standard condition(s) 28
B.2.1 Standard conditions for lateral movement 28
B.2.2 Standard condition for shear movement 28
B.3 Conditions for other movements 29

Annex C (informative) Guidance on the use of this European Standard 32

C.1 General 32
C.2 Application of the test 32
C.3 Test conditions 32
C.4 Specimen preparation 33
C.5 Notes on general performance criteria 33
C.6 Notes on validity of test results 33
C.7 Notes on Annex B 33