

# DIN EN 1603:2007-06 (E)

Thermal insulating products for building applications - Determination of dimensional stability under constant normal laboratory conditions (23 °C/50 % relative humidity) (includes Amendment A1:2006)

---

| <b>Contents</b> |  | <b>Page</b> |
|-----------------|--|-------------|
| <b>1</b>        | <b>Scope .....</b>                                 | <b>4</b>    |
| <b>2</b>        | <b>Normative references .....</b>                  | <b>4</b>    |
| <b>3</b>        | <b>Definitions .....</b>                           | <b>5</b>    |
| <b>4</b>        | <b>Principle .....</b>                             | <b>5</b>    |
| <b>5</b>        | <b>Apparatus .....</b>                             | <b>5</b>    |
| <b>6</b>        | <b>Test specimens .....</b>                        | <b>6</b>    |
| <b>6.1</b>      | <b>Dimensions of test specimens .....</b>          | <b>6</b>    |
| <b>6.2</b>      | <b>Number of test specimens .....</b>              | <b>6</b>    |
| <b>6.3</b>      | <b>Preparation of test specimens .....</b>         | <b>8</b>    |
| <b>6.4</b>      | <b>Conditioning of test specimens .....</b>        | <b>8</b>    |
| <b>7</b>        | <b>Procedure .....</b>                             | <b>8</b>    |
| <b>7.1</b>      | <b>Test conditions .....</b>                       | <b>8</b>    |
| <b>7.2</b>      | <b>Test procedure .....</b>                        | <b>8</b>    |
| <b>8</b>        | <b>Calculation and expression of results .....</b> | <b>9</b>    |
| <b>9</b>        | <b>Accuracy of measurement .....</b>               | <b>9</b>    |
| <b>10</b>       | <b>Test report .....</b>                           | <b>10</b>   |