

DIN EN 14318-1:2013-04 (E)

Thermal insulating products for buildings - In-situ formed dispensed rigid polyurethane (PUR) and polyisocyanurate (PIR) foam products - Part 1: Specification for the rigid foam dispensed system before installation

| Contents | | Page |
|--|--|-------------|
| Foreword | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms, definitions, symbols and abbreviations | 6 |
| 3.1 | Terms and definitions | 6 |
| 3.2 | Symbols and abbreviations | 8 |
| 4 | Requirements | 9 |
| 4.1 | General | 9 |
| 4.2 | For all applications | 10 |
| 4.3 | Specific applications | 12 |
| 5 | Test methods | 14 |
| 5.1 | Sampling and test specimen preparation | 14 |
| 5.2 | Conditioning | 14 |
| 5.3 | Testing | 14 |
| 6 | Designation code | 16 |
| 7 | Evaluation of conformity | 16 |
| 7.1 | General | 16 |
| 7.2 | Initial type testing | 17 |
| 7.3 | Factory production control | 17 |
| 8 | Marking, labelling and technical information | 17 |
| 8.1 | Marking and labelling | 17 |
| 8.2 | Technical information | 17 |
| Annex A (normative) Determination of declared aged thermal conductivity and aged thermal resistance | | 19 |
| A.1 | Introduction | 19 |
| A.2 | Input data | 19 |
| A.3 | Declared values | 19 |
| Annex B (normative) Determination of substrate adhesion strength perpendicular to faces | | 21 |
| B.1 | Principle | 21 |
| B.2 | Apparatus | 21 |
| B.3 | Test specimen | 21 |
| B.4 | Procedure | 21 |
| B.5 | Report | 22 |
| Annex C (normative) Determination of the aged values of thermal resistance and thermal conductivity | | 23 |

| | | |
|---|--|----|
| C.1 | General | 23 |
| C.2 | Sampling and test specimen preparation | 23 |
| C.3 | Determination of the initial value of thermal conductivity | 24 |
| C.4 | Determination of the accelerated aged value of thermal conductivity | 25 |
| C.5 | Fixed increment procedure | 27 |
| C.6 | Declaration of the aged values of thermal resistance and aged thermal conductivity | 29 |
| Annex D (normative) Initial type testing (ITT) and Factory production control (FPC) | | 31 |
| Annex E (normative) Determination of the reaction profile and free-rise density | | 33 |
| E.1 | Introduction | 33 |
| E.2 | Principle | 33 |
| E.3 | Apparatus | 33 |
| E.4 | Procedure | 33 |
| E.5 | Free-rise density | 34 |
| Annex F (normative) Sample preparation method for the test specimens for the thermal conductivity test | | 35 |
| Annex G (normative) Sample preparation method for the test specimens other than thermal conductivity | | 36 |
| G.1 | Principle | 36 |
| G.2 | Procedure | 36 |
| Annex H (normative) Testing for reaction to fire of products | | 37 |
| H.1 | Scope | 37 |
| H.2 | Product and installation parameters | 37 |
| H.3 | Mounting and fixing | 38 |
| H.4 | Field of application | 40 |
| Annex I (normative) Testing for reaction to fire of products in standardised assemblies simulating end-use application(s) | | 42 |
| I.1 | Scope | 42 |
| I.2 | Product and installation parameters | 42 |
| I.3 | Mounting and fixing | 43 |
| I.4 | Field of application | 46 |
| Annex J (informative) Example for the determination of the declared aged values of thermal conductivity and thermal resistance for a product | | 48 |
| Case where both thermal conductivity and thermal resistance are declared | | 48 |
| Annex K (normative) Instructions for compiling thermal resistance performance charts | | 50 |
| K.1 | Introduction | 50 |
| K.2 | General | 50 |
| K.3 | Procedure for the manufacturer to create the performance charts | 52 |
| Annex ZA (informative) Clause of this European Standard addressing the provisions of the provisions of the EU Construction Products Directive | | 57 |
| ZA.1 Scope and relevant characteristics | | 57 |
| ZA.2 Procedure for attestation of conformity of in-situ formed dispensed rigid polyurethane (PUR) and rigid polyisocyanurate foam(PIR) products | | 59 |
| ZA.3 CE marking and labelling | | 62 |
| Bibliography | | 64 |