

# ISO 5658-2:2006-09 (E)

## Reaction to fire tests - Spread of flame - Part 2: Lateral spread on building and transport products in vertical configuration

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
Introduction .....		vi
1	Scope .....	1
2	Normative references .....	1
3	Definitions .....	1
4	Principle .....	3
5	Suitability of a product for testing .....	4
5.1	Surface characteristics .....	4
5.2	Thermally unstable products .....	5
6	Test specimens .....	5
6.1	Exposed surface .....	5
6.2	Number and size of specimens .....	5
6.3	Construction of specimens .....	7
6.4	Conditioning .....	7
6.5	Preparation .....	7
7	Test apparatus .....	9
7.1	General .....	9
7.2	The radiant panel support framework .....	10
7.3	Specimen support framework .....	11
7.4	Specimen holder .....	11
7.5	Pilot flame burner .....	12
8	Test environment .....	15
9	Additional equipment and instrumentation .....	15
9.1	Heat-flux meter .....	15
9.2	Total radiation pyrometer .....	16
9.3	Recorder .....	16
9.4	Timing devices .....	16
9.5	Dummy specimen .....	16
9.6	Calibration board .....	16
9.7	Backing boards and spacers .....	17
10	Setting-up and calibration procedure .....	17
10.1	Setting-up .....	17
10.2	Verification .....	20
10.3	Adjustment of the pilot flame .....	20
11	Test procedure .....	20
12	Expression of fire performance of a product .....	22
13	Test report .....	22

<b>Annex A (normative) Safety precautions .....</b>	<b>24</b>
<b>Annex B (informative) Specimen construction .....</b>	<b>25</b>
<b>Annex C (informative) Calibration of the working heat-flux meter .....</b>	<b>26</b>
<b>Annex D (informative) Guidelines for reporting and follow-up of results of fire test procedures .....</b>	<b>27</b>
<b>Annex E (informative) Variability of test results .....</b>	<b>28</b>
<b>Annex F (normative) Test method for flame spread of plastic piping .....</b>	<b>31</b>
<b>Bibliography .....</b>	<b>33</b>