

DIN EN 13947:2007-03 (E)

Thermal performance of curtain walling - Calculation of thermal transmittance

| Contents | Page |
|--|------|
| 1 Scope | 6 |
| 2 Normative references | 6 |
| 3 Terms and definitions, symbols and units | 7 |
| 3.1 Terms and definitions | 7 |
| 3.2 Symbols and units | 7 |
| 3.3 Subscripts | 7 |
| 3.4 Superscripts | 8 |
| 4 Geometrical characteristics | 8 |
| 4.1 Main principles | 8 |
| 4.2 Developed areas and internal depth | 11 |
| 4.3 Boundaries of curtain wall structures | 11 |
| 4.3.1 General | 11 |
| 4.3.2 Boundaries of a representative reference element | 12 |
| 4.3.3 Curtain wall areas | 13 |
| 5 Cut-off planes and partitioning of thermal zones | 14 |
| 5.1 Rules for thermal modelling | 14 |
| 5.2 Cut-off planes of the geometrical model | 14 |
| 6 Calculation of curtain wall transmittance | 14 |
| 6.1 Methodologies | 14 |
| 6.2 Single assessment method | 15 |
| 6.2.1 Thermal transmittance of glazing units and panels (filling elements) | 15 |
| 6.2.2 Determination of the heat flow through filling element / mullion or transom / filling element connection | 16 |
| 6.2.3 Determination of the overall thermal transmittance of a curtain wall (Ucw) | 20 |
| 6.3 Component assessment method | 21 |
| 6.3.1 General | 21 |
| 6.3.2 Definition of areas | 21 |
| 6.3.3 Thermal transmittance of glazing units and panels (filling elements) | 24 |
| 6.3.4 Thermal transmittance of frames, mullions and transoms | 24 |
| 6.3.5 Linear thermal transmittance | 25 |
| 6.4 Thermal transmittance of a curtain wall built of different elements | 27 |
| 7 Input data | 28 |
| 8 Report | 29 |
| 8.1 Section drawings | 29 |
| 8.2 Overview drawing of the whole curtain wall element | 29 |
| 8.3 Values used for calculation | 29 |
| 8.4 Presentation of results | 29 |
| Annex A (informative) Guidance for calculating the thermal transmittance Ucw of curtain walling using the two methods | 30 |
| Annex B (informative) Linear thermal transmittance of junctions | 31 |
| Annex C (normative) A method for calculating the thermal effect of screws using a 2D numerical method and the procedures specified in EN ISO 10077-2 | 39 |

| | | |
|--|---|----|
| C.1 | General | 39 |
| C.2 | Calculation of the equivalent thermal conductivity of the screw s,eq | 40 |
| C.3 | Consideration of screw heads and washers | 40 |
| Annex D (normative) Ventilated and unventilated air spaces | | 41 |
| Unventilated air layer | | 41 |
| Annex E (informative) Component method: Calculation example | | 44 |
| E.1 | Data for examples | 44 |
| E.2 | Frames | 46 |
| E.2.1 | Definition and evaluation of areas | 46 |
| E.2.2 | Evaluation of Uf values | 47 |
| E.3 | Glazing units | 48 |
| E.3.1 | Definition and evaluation of areas | 48 |
| E.3.2 | Evaluation of Ug values | 48 |
| E.3.3 | Definition of Ig and evaluation of g, m,f and t,f | 48 |
| E.4 | Panels | 49 |
| E.4.1 | Definition and evaluation of areas | 49 |
| E.4.2 | Evaluation of Up values | 49 |
| E.4.3 | Definition of Ip and evaluation of the p values | 50 |
| E.4.4 | Calculation of a complete element | 50 |
| Annex F (informative) Single assessment method: Calculation example | | 51 |
| F.1 | General description of examples | 51 |
| F.2 | Centre U-value of the glazing unit | 52 |
| F.3 | Centre U-value of the spandrel panel | 52 |
| F.4 | U-values of thermal joints | 52 |
| F.5 | Overall U-value of the curtain wall | 53 |