

# ISO 8873-1:2006-12 (E)

## Rigid cellular plastics - Spray-applied polyurethane foam for thermal insulation - Part 1: Material specifications

---

<b>Contents</b>		<b>Page</b>
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>2</b>
<b>4</b>	<b>Requirements .....</b>	<b>3</b>
<b>4.1</b>	<b>General requirements .....</b>	<b>3</b>
<b>4.2</b>	<b>Categories .....</b>	<b>3</b>
<b>5</b>	<b>Sampling .....</b>	<b>4</b>
<b>5.1</b>	<b>General .....</b>	<b>4</b>
<b>5.2</b>	<b>Preparation of sample panels .....</b>	<b>4</b>
<b>5.3</b>	<b>Conditioning of sample panels .....</b>	<b>4</b>
<b>5.4</b>	<b>Preparation of specimens .....</b>	<b>4</b>
<b>6</b>	<b>Test methods .....</b>	<b>5</b>
<b>6.1</b>	<b>Air permeance .....</b>	<b>5</b>
<b>6.2</b>	<b>Apparent core density .....</b>	<b>5</b>
<b>6.3</b>	<b>Compressive strength .....</b>	<b>5</b>
<b>6.4</b>	<b>Dimensional stability .....</b>	<b>5</b>
<b>6.5</b>	<b>Surface burning characteristics .....</b>	<b>5</b>
<b>6.6</b>	<b>Open-cell content: Volume .....</b>	<b>5</b>
<b>6.7</b>	<b>Initial thermal resistance .....</b>	<b>5</b>
<b>6.8</b>	<b>Long-term thermal resistance (LTTR) .....</b>	<b>6</b>
<b>6.9</b>	<b>Tensile strength .....</b>	<b>6</b>
<b>6.10</b>	<b>Substrate adhesion .....</b>	<b>7</b>
<b>6.11</b>	<b>Volatile organic emissions .....</b>	<b>7</b>
<b>6.12</b>	<b>Water absorption .....</b>	<b>7</b>
<b>6.13</b>	<b>Water vapour permeability .....</b>	<b>7</b>
<b>7</b>	<b>Reporting requirements .....</b>	<b>7</b>
<b>8</b>	<b>Marking, labelling and packaging .....</b>	<b>8</b>
<b>8.1</b>	<b>Packaging .....</b>	<b>8</b>
<b>8.2</b>	<b>Marking and/or labelling .....</b>	<b>8</b>
<b>9</b>	<b>Manufacturer's documentation .....</b>	<b>8</b>