

# DIN EN 15319:2007-10 (E)

## General principles of design of fibrous (gypsum) plaster works

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
Introduction .....		4
<b>1</b>	<b>Scope .....</b>	<b>5</b>
<b>2</b>	<b>Normative references .....</b>	<b>6</b>
<b>3</b>	<b>Terms, definitions, symbols and abbreviations .....</b>	<b>7</b>
<b>3.1</b>	<b>General definitions .....</b>	<b>7</b>
<b>3.2</b>	<b>Technical definitions .....</b>	<b>8</b>
<b>3.3</b>	<b>Symbols and abbreviations .....</b>	<b>16</b>
<b>4</b>	<b>Design .....</b>	<b>16</b>
<b>4.1</b>	<b>General .....</b>	<b>16</b>
<b>4.2</b>	<b>Functions .....</b>	<b>20</b>
<b>4.3</b>	<b>Technical requirements .....</b>	<b>23</b>
<b>4.4</b>	<b>Essential requirements .....</b>	<b>34</b>
<b>5</b>	<b>Setting up on site and arrangements .....</b>	<b>36</b>
<b>5.1</b>	<b>Conditions required prior to commencing the installation of fibrous plaster works .....</b>	<b>36</b>
<b>5.2</b>	<b>Materials, equipment, accessories and other devices .....</b>	<b>39</b>
<b>6</b>	<b>Characteristics of the completed works .....</b>	<b>40</b>
<b>6.1</b>	<b>Surface appearance of the works .....</b>	<b>40</b>
<b>6.2</b>	<b>Flatness of work surfaces .....</b>	<b>41</b>
<b>6.3</b>	<b>Verticality of flat work surfaces .....</b>	<b>42</b>
<b>7</b>	<b>Maintenance and repair .....</b>	<b>42</b>
<b>Annex A (informative) Separations at abutments and within the area of the works .....</b>		<b>43</b>
<b>A.1</b>	<b>Examples of situations likely to require separation at edges of work .....</b>	<b>43</b>
<b>A.2</b>	<b>Examples of situations likely to require sub-division .....</b>	<b>44</b>
<b>Annex B (informative) Design values of thermal conductivity of gypsum plaster .....</b>		<b>45</b>
<b>Annex C (informative) Painting works .....</b>		<b>46</b>
<b>Bibliography .....</b>		<b>47</b>