DIN V 18599-5:2007-02 (E)

Energy efficiency of buildings - Calculation of the net, final and pri mary energy demand for heating, cooling, ventilation, domestic hot water and lighting - Part 5: Final energy demand of heating systems

Contents

Page

Foreword 7

Introduction 9

1 Scope 10

2 Normative references 11

3 Terms and definitions, symbols and units 13
3.1 Terms and definitions 13
3.2 Symbols, units and subscripts 17

4.2.1 Generator heat output 23
4.2.2 Delivered heat 24
4.2.3 Auxiliary energy 25
4.2.4 Uncontrolled heat gains due to the heating system 25

5 Boundary conditions for the individual subsystems 26
5.1 Part load levels 26
5.1.1 Heat control and emission 26
5.1.2 Heat distribution 26
5.1.3 Storage 26
5.1.4 Heat generation 27
5.2 Temperatures 27
5.3 Boiler rated output 29
5.4 Times 29
5.4.1 Running times 29
5.4.2 Distribution of annual values over individual months 32

6 Determination of energy expenditure 32
6.1 Heat control and emission 32
6.1.1 Efficiencies for free emitters (radiators); room heights 4 m 33
6.1.2 Efficiencies for water based embedded systems (surface heating); room heights 4 m 35
6.1.3 Efficiencies for electric heating; (room heights 4 m) 36
6.1.4 Efficiencies for air heating/residential ventilation; room heights 4 m 36
6.1.5 Efficiencies for air heating (HVAC systems); room heights 4 m 37
6.1.6 Efficiencies for rooms with heights 4 m (large indoor spaces) 37
6.1.7 Efficiencies for rooms with heights > 10 m 39
6.1.8 Auxiliary energy Qh,ce,aux 40
6.2 Heat distribution Qh,d - central hot water heating pipe system 43
6.2.1 Auxiliary energy for central hot water heating pipe system 45
6.3 Storage 50
6.4 Heat generator 52
6.4.1 Solar systems supporting domestic hot water heating and space heating systems (combination systems) 53
6.4.1.1 Satisfaction of energy need by solar combination systems 53
6.4.1.2 Energy contribution of solar combination systems 53

-- Prestandard -- 6.4.1.3 Calculation procedure for combination systems 56

6.4.1.4 Calculation procedure for large combination systems ... 60
6.4.1.5 Auxiliary energy for operation of the solar pump ... 60
6.4.2 Heat pump ... 61
6.4.2.1 Principles of the calculation ... 62
6.4.2.2 Outdoor air as heat source; average climatic data for Germany ... 65
6.4.2.3 Energy need for domestic hot water ... 69
6.4.2.4 Calculation of the fraction of heating energy to be provided by the second generator (back-up heating) ... 69
6.4.2.5 Heat output and coefficient of performance of the heat pump at full load (steady-state operation) ... 73
6.4.2.6 Coefficient of performance in part load operation ... 76
6.4.2.7 Generator thermal losses ... 78
6.4.2.8 Calculation of total energy consumption ... 79
6.4.2.9 Auxiliary energy ... 80
6.4.2.10 Energy consumption of the second generator (back-up heating system) ... 81
6.4.2.11 Total energy consumption ... 82
6.4.2.12 Regenerative energy contribution ... 82
6.4.2.13 Performance factor to account for the generator subsystem ... 82
6.4.3 Conventional boilers ... 83
6.4.3.1 Multiple boiler systems ... 83
6.4.3.2 Fuel-fired systems (boilers) ... 84
6.4.3.3 Hand stocked biomass combustion systems ... 94
6.4.3.4 Decentralized fuel-fired systems ... 99
6.4.4 Electric heaters ... 101
6.4.4.1 Decentralized electric heaters ... 101
6.4.4.2 Central electric heaters ... 101
6.4.5 District heating and local heating ... 101
6.4.6 Decentralized CHP ... 102

Annex A (normative) Energy use to meet the heating need ... 103

A.1 Electrically driven heat pumps ... 103
A.2 Heat pumps with combustion drive ... 104
A.3 Default values for heat pump calculations ... 105
A.3.1 Default power values and coefficients of performance for electrically driven heat pumps 105
A.4 Default power values and coefficients of performance for combustion engine-driven heat pumps ... 106
A.4.1 Air-to-water heat pumps ... 106
A.4.2 Combustion engine-driven air-to-water heat pumps ... 107
A.4.3 Air-to-air heat pumps ... 107
A.4.4 Absorption heat pumps ... 108
A.5 Correction factor for part load operation ... 110
A.5.1 Electrically driven heat pumps ... 110
A.5.2 Absorption heat pumps with modulation burner ... 111
A.6 Calculation procedure for source and sink temperature corrections with a set exergetic efficiency ... 111
A.7 VRF systems: relative heat output performance ... 113

Annex B (informative) Dimensioning of buildings ... 116

B.1 General information ... 116

Bibliography ... 119

-- Prestandard -- Figures Figure 3 -- Subscript system ... 20

Figure 4 -- Designation of pipes in hot water heating pipe systems ... 44

Figure 5 -- Distribution of cumulated bin hours for the outdoor air temperature ... 63

Figure 6 -- Bin hours and energy fractions of the heat pump and the second generator (back-up heating) in alternate operation ... 70

Figure 7 -- Bin hours and energy fractions of the heat pump and the second generator (back-up heating) in parallel operation 71

Figure 8 -- Bin hours and energy fractions of the heat pump and the second generator (back-up heating) in partly parallel operation 72

Figure A.1 -- Energy balance of the generator subsystem (electrically driven heat pump) 103

Figure A.2 -- Energy balance of the generator subsystem (heat pump with combustion drive) 104

Figure A.3 -- Heat output of combustion engine-driven air-to-water heat pumps at various source and sink temperatures 106

Figure A.4 -- Standard coefficients of performance for combustion engine-driven air-to-water heat pumps at various source and sink temperatures 107

Figure A.5 -- Heat output of combustion engine-driven air-to-air heat pumps 107

Figure A.6 -- Standard coefficient of performance of combustion engine-driven air-to-air heat pumps 108

Figure A.7 -- Heat output of water-to-water NH3/H2O absorption heat pumps at various source and sink temperatures 108

Figure A.8 -- Heat output of water-to-water H2O/LiBr absorption heat pumps at various source and sink temperatures 109

Figure A.9 -- VRF systems: COP heating for load ratios between 10 % and 100 % 114

Figure A.10 -- VRF systems: relative heat output performance 114

Figure A.11 -- VRF systems: relative COP heating for load ratios between 10 % and 100 % 115

Figure B.1 -- Building geometry 116

Tables Table 1 -- Symbols and units 17

Table 2 -- Subscripts 19

Table 3 -- Input parameters 21

Table 4 -- Output parameters 23

Table 5 -- Design temperatures 28

Table 6 -- Efficiencies for free emitters (radiators); room heights 4 m 34

Table 7 -- Efficiencies for water based embedded systems (surface heating); room heights 4 m 35

Table 8 -- Efficiencies for electric heating; (room heights 4 m) 36

Table 9 -- Efficiencies for air heating (HVAC systems) for room heights 4 m 37

-- Prestandard -- Table 10 -- Efficiencies for rooms with heights from 4 m to 10 m 38

Table 11 -- Efficiencies for rooms with heights > 10 m 39

Table 12 -- Default values for auxiliary energy for the control system 41

Table 13 -- Default values for the auxiliary energy of fans for air supply in rooms where h 4 m 41

Table 14 -- Default values for the auxiliary energy of fans and for the control system in rooms h > 4 m in height (large indoor spaces) 42

Table 15 -- Default values 44

Table 16 -- Assumptions for heat transfer coefficients Ui in W/(m · K) 45

Table 17 -- Constants CP1,CP2 for calculation of the expenditure factor of heat pumps 49

Table 18 -- Distribution of annual solar contribution over months 56

Table 19 -- Correction factor for inclination and alignment 57

Table 20 -- Correction factor for the solar load ratio (fslr) 58

Table 21 -- Correction factor for the heat loss rate of the storage tank or tanks (fs,loss) 58

Table 22 -- Correction factor for the temperature level of the space heating fh,T 59

Table 23 -- Energy fraction from the combination system for domestic water heating 60

Table 24 -- Hours frequency of outdoor temperature (reference location: Würzburg) 66

Table 25 -- Monthly hours sum in the individual bins, distributed according to the testing points from DIN EN 14511 (all parts) 69

Table 26 -- Mean source temperature for ground and groundwater as a function of the average outdoor temperature 74

Table 27 -- Mean source temperature for ground and groundwater as a function of the average monthly outdoor temperature 74

Table 28 -- Correction factors f to account for deviations in temperature differences in heat pump measurement and operation 75

Table 29 -- Boiler temperatures 87

Table 30 -- Temperature correction factors 87

Table 31 -- Efficiency factors 90

Table 32 -- Radiation loss factors 91

Table 33 -- Stand-by heat factors 92

Table 34 -- Auxiliary energy factors 93

Table 35 -- Default values 99

Table 36 -- Efficiency factor 100

Table 37 -- DDS as a function of the primary temperature and type of dwelling substation 102

Table 38 -- Coefficient BDS as a function of the class of insulation and the type of dwelling substation 102

Table A.1 -- Air-to-water heat pumps with a supply temperature of 35 °C 105

Table A.2 -- Air-to-water heat pumps with a supply temperature of 50 °C 105

Table A.3 -- Brine-to-water heat pumps with supply temperatures of 35 °C and 50 °C 105

Table A.4 -- Water-to-water heat pumps with supply temperatures of 35 °C and 50 °C 106

Table A.5 -- Correction factor for part load operation of electrically driven heat pumps with radiators 110

-- Prestandard -- Table A.6 -- Correction factor for part load operation of electrically driven heat pumps with surface heating systems 110

Table A.7 -- Correction factor for part load operation of absorption heat pumps 111

Table A.8 -- Relative heat output performance 113