

DIN V 18599-5:2007-02 (E)

Energy efficiency of buildings - Calculation of the net, final and primary energy demand for heating, cooling, ventilation, domestic hot water and lighting - Part 5: Final energy demand of heating systems

Contents		Page
Foreword		7
Introduction		9
1	Scope	10
2	Normative references	11
3	Terms and definitions, symbols and units	13
3.1	Terms and definitions	13
3.2	Symbols, units and subscripts	17
4.2.1	Generator heat output	23
4.2.2	Delivered heat	24
4.2.3	Auxiliary energy	25
4.2.4	Uncontrolled heat gains due to the heating system	25
5	Boundary conditions for the individual subsystems	26
5.1	Part load levels	26
5.1.1	Heat control and emission	26
5.1.2	Heat distribution	26
5.1.3	Storage	26
5.1.4	Heat generation	27
5.2	Temperatures	27
5.3	Boiler rated output	29
5.4	Times	29
5.4.1	Running times	29
5.4.2	Distribution of annual values over individual months	32
6	Determination of energy expenditure	32
6.1	Heat control and emission	32
6.1.1	Efficiencies for free emitters (radiators); room heights 4 m	33
6.1.2	Efficiencies for water based embedded systems (surface heating); room heights 4 m	35
6.1.3	Efficiencies for electric heating; (room heights 4 m)	36
6.1.4	Efficiencies for air heating/residential ventilation; room heights 4 m	36
6.1.5	Efficiencies for air heating (HVAC systems); room heights 4 m	37
6.1.6	Efficiencies for rooms with heights 4 m (large indoor spaces)	37
6.1.7	Efficiencies for rooms with heights > 10 m	39
6.1.8	Auxiliary energy $Q_{h,ce,aux}$	40
6.2	Heat distribution $Q_{h,d}$ - central hot water heating pipe system	43
6.2.1	Auxiliary energy for central hot water heating pipe system	45
6.3	Storage	50
6.4	Heat generator	52
6.4.1	Solar systems supporting domestic hot water heating and space heating systems (combination systems)	53
6.4.1.1	Satisfaction of energy need by solar combination systems	53
6.4.1.2	Energy contribution of solar combination systems	53
-- Prestandard --	6.4.1.3 Calculation procedure for combination systems	56

6.4.1.4	Calculation procedure for large combination systems	60
6.4.1.5	Auxiliary energy for operation of the solar pump	60
6.4.2	Heat pump	61
6.4.2.1	Principles of the calculation	62
6.4.2.2	Outdoor air as heat source; average climatic data for Germany	65
6.4.2.3	Energy need for domestic hot water	69
6.4.2.4	Calculation of the fraction of heating energy to be provided by the second generator (back-up heating)	69
6.4.2.5	Heat output and coefficient of performance of the heat pump at full load (steady-state operation)	73
6.4.2.6	Coefficient of performance in part load operation	76
6.4.2.7	Generator thermal losses	78
6.4.2.8	Calculation of total energy consumption	79
6.4.2.9	Auxiliary energy	80
6.4.2.10	Energy consumption of the second generator (back-up heating system)	81
6.4.2.11	Total energy consumption	82
6.4.2.12	Regenerative energy contribution	82
6.4.2.13	Performance factor to account for the generator subsystem	82
6.4.3	Conventional boilers	83
6.4.3.1	Multiple boiler systems	83
6.4.3.2	Fuel-fired systems (boilers)	84
6.4.3.3	Hand stocked biomass combustion systems	94
6.4.3.4	Decentralized fuel-fired systems	99
6.4.4	Electric heaters	101
6.4.4.1	Decentralized electric heaters	101
6.4.4.2	Central electric heaters	101
6.4.5	District heating and local heating	101
6.4.6	Decentralized CHP	102
Annex A (normative) Energy use to meet the heating need		103
A.1	Electrically driven heat pumps	103
A.2	Heat pumps with combustion drive	104
A.3	Default values for heat pump calculations	105
A.3.1	Default power values and coefficients of performance for electrically driven heat pumps	105
A.4	Default power values and coefficients of performance for combustion engine-driven heat pumps	106
A.4.1	Air-to-water heat pumps	106
A.4.2	Combustion engine-driven air-to-water heat pumps	107
A.4.3	Air-to-air heat pumps	107
A.4.4	Absorption heat pumps	108
A.5	Correction factor for part load operation	110
A.5.1	Electrically driven heat pumps	110
A.5.2	Absorption heat pumps with modulation burner	111
A.6	Calculation procedure for source and sink temperature corrections with a set exergetic efficiency	111
A.7	VRF systems: relative heat output performance	113
Annex B (informative) Dimensioning of buildings		116
B.1	General information	116
Bibliography		119
-- Prestandard -- Figures Figure 3 -- Subscript system		20
Figure 4 -- Designation of pipes in hot water heating pipe systems		44
Figure 5 -- Distribution of cumulated bin hours for the outdoor air temperature		63
Figure 6 -- Bin hours and energy fractions of the heat pump and the second generator (back-up heating) in alternate operation		70

Figure 7 -- Bin hours and energy fractions of the heat pump and the second generator (back-up heating) in parallel operation	71
Figure 8 -- Bin hours and energy fractions of the heat pump and the second generator (back-up heating) in partly parallel operation	72
Figure A.1 -- Energy balance of the generator subsystem (electrically driven heat pump)	103
Figure A.2 -- Energy balance of the generator subsystem (heat pump with combustion drive)	104
Figure A.3 -- Heat output of combustion engine-driven air-to-water heat pumps at various source and sink temperatures	106
Figure A.4 -- Standard coefficients of performance for combustion engine-driven air-to-water heat pumps at various source and sink temperatures	107
Figure A.5 -- Heat output of combustion engine-driven air-to-air heat pumps	107
Figure A.6 -- Standard coefficient of performance of combustion engine-driven air-to-air heat pumps	108
Figure A.7 -- Heat output of water-to-water NH ₃ /H ₂ O absorption heat pumps at various source and sink temperatures	108
Figure A.8 -- Heat output of water-to-water H ₂ O/LiBr absorption heat pumps at various source and sink temperatures	109
Figure A.9 -- VRF systems: COP heating for load ratios between 10 % and 100 %	114
Figure A.10 -- VRF systems: relative heat output performance	114
Figure A.11 -- VRF systems: relative COP heating for load ratios between 10 % and 100 %	115
Figure B.1 -- Building geometry	116
Tables Table 1 -- Symbols and units	17
Table 2 -- Subscripts	19
Table 3 -- Input parameters	21
Table 4 -- Output parameters	23
Table 5 -- Design temperatures	28
Table 6 -- Efficiencies for free emitters (radiators); room heights 4 m	34
Table 7 -- Efficiencies for water based embedded systems (surface heating); room heights 4 m	35
Table 8 -- Efficiencies for electric heating; (room heights 4 m)	36
Table 9 -- Efficiencies for air heating (HVAC systems) for room heights 4 m	37
-- Prestandard -- Table 10 -- Efficiencies for rooms with heights from 4 m to 10 m	38
Table 11 -- Efficiencies for rooms with heights > 10 m	39
Table 12 -- Default values for auxiliary energy for the control system	41
Table 13 -- Default values for the auxiliary energy of fans for air supply in rooms where h 4 m	41

Table 14 -- Default values for the auxiliary energy of fans and for the control system in rooms $h > 4$ m in height (large indoor spaces)	42
Table 15 -- Default values	44
Table 16 -- Assumptions for heat transfer coefficients U_i in $W/(m \cdot K)$	45
Table 17 -- Constants CP1,CP2 for calculation of the expenditure factor of heat pumps	49
Table 18 -- Distribution of annual solar contribution over months	56
Table 19 -- Correction factor for inclination and alignment	57
Table 20 -- Correction factor for the solar load ratio (fslr)	58
Table 21 -- Correction factor for the heat loss rate of the storage tank or tanks (fs,loss)	58
Table 22 -- Correction factor for the temperature level of the space heating $f_{h,T}$	59
Table 23 -- Energy fraction from the combination system for domestic water heating	60
Table 24 -- Hours frequency of outdoor temperature (reference location: Würzburg)	66
Table 25 -- Monthly hours sum in the individual bins, distributed according to the testing points from DIN EN 14511 (all parts)	69
Table 26 -- Mean source temperature for ground and groundwater as a function of the average outdoor temperature	74
Table 27 -- Mean source temperature for ground and groundwater as a function of the average monthly outdoor temperature	74
Table 28 -- Correction factors f to account for deviations in temperature differences in heat pump measurement and operation	75
Table 29 -- Boiler temperatures	87
Table 30 -- Temperature correction factors	87
Table 31 -- Efficiency factors	90
Table 32 -- Radiation loss factors	91
Table 33 -- Stand-by heat factors	92
Table 34 -- Auxiliary energy factors	93
Table 35 -- Default values	99
Table 36 -- Efficiency factor	100
Table 37 -- DDS as a function of the primary temperature and type of dwelling substation	102
Table 38 -- Coefficient BDS as a function of the class of insulation and the type of dwelling substation	102
Table A.1 -- Air-to-water heat pumps with a supply temperature of 35 °C	105
Table A.2 -- Air-to-water heat pumps with a supply temperature of 50 °C	105
Table A.3 -- Brine-to-water heat pumps with supply temperatures of 35 °C and 50 °C	105

Table A.4 -- Water-to-water heat pumps with supply temperatures of 35 °C and 50 °C 106

Table A.5 -- Correction factor for part load operation of electrically driven heat pumps with radiators 110

-- Prestandard -- Table A.6 -- Correction factor for part load operation of electrically driven heat pumps with surface heating systems 110

Table A.7 -- Correction factor for part load operation of absorption heat pumps 111

Table A.8 -- Relative heat output performance 113