DIN V 18599-4:2007-02 (E)

Energy efficiency of buildings - Calculation of the net, fina l and primary energy demand for heating, cooling, ventilation, domestic hot water and lighting - Part 4: Net and final energy demand for lighting

Contents

Page

Foreword 5

Introduction 7

1 Scope 8

2 Normative references 9

3 Terms and definitions, symbols and units 10
3.1 Terms and definitions 10
3.2 Symbols, units and subscripts 13
3.2.1 Symbols and units 13
3.2.2 Subscripts 13

5 Calculations 15
5.1 Principle of the balance calculations 15
5.2 Subdivision of a building zone 17
5.2.1 Subdivision into evaluation areas 17
5.2.2 Daylight area 18
5.3 Operating times 19
5.4 Artificial lighting 19
5.4.1 Tabular method 19
5.4.2 Simplified utilization factor method 22
5.4.3 Detailed engineering planning 23
5.4.4 Determination of the specific electrical evaluation power in existing buildings 23
5.5 Daylight 24
5.5.1 Annual daylight supply with vertical façades 26
5.5.2 Annual daylight supply through rooflights 37
5.5.3 Daylight-responsive control systems 44
5.5.4 Monthly evaluation method 45
5.6 Occupancy (presence) 46

Annex A (normative) Reduction factor kA to take into account the relative proportion of the area needed for the visual task 48

A.1 General 48
A.2 Detailed calculation of CTL,Vers,Sa,j 49
A.3 Examples of the electrical evaluation power of various illumination solutions 56
A.3.1 General 56
A.3.2 Personal offices (single occupant) 57
A.3.3 Office for two occupants 60
A.3.4 Workgroup offices 63
A.3.5 Call centres (landscaped offices) 66
A.3.6 Corridors 70
A.3.7 Production hall 72
A.4 Example: Determination of the daylight supply factor CTL,Vers,j for a space with rooflights 74
A.4.1 General 74
A.4.2 Determination of the electrical evaluation power 74

A.4.3 Determination of the daylight supply factor CTL,Vers 75
A.4.4 Determination of the annual and monthly energy use for lighting 76

Bibliography 79

-- Prestandard -- Figures Figure 3 -- Flowchart showing calculation of the energy need for lighting . 17

Figure 4 -- Determination of height h'R (schematic diagram) 21

Figure 5 -- Three-stage approach for determining the daylight supply factor CTL,Vers,j 25

Figure 6 -- Effect of the angle of elevation of a linear obstruction V,lV (schematic diagram) 27

Figure 7 -- Effect of the horizontal obstruction angle due to an overhang V,hA (schematic diagram) 27

Figure 8 -- Effect of the vertical obstruction angle V,vA due to a side fin (schematic diagram) 28

Figure 9 -- Geometrical parameters used to define the well index wi (notation) 29

Figure 10 -- Example of a set of functions to determine the daylight supply factor CTL,Vers,SNA,j as a function of DRb and eff,SNA,j according to equation (28) for mE = 500 lx and a south-facing façade 36

Figure 11 -- Notation used to describe the geometry of the upstands of spaces with dome lights and continuous rooflights 40

Figure 12 -- Notation used to describe the geometry of rooflights in sawtooth roofs (sheds) 40

Figure A.1 -- Task area AS and immediate surrounding area AU (schematic diagram) 49

Figure A.2 -- Effective light transmittances eff,u,SA into the lower quarter-space and eff,o,SA into the upper quarter-space (schematic diagram) 53

Figure A.3 -- Factor C'TL,Vers,SA for areas with activated solar radiation protection and/or glare protection as a function of the total light transmittance eff,SA and the distribution key factor vSA for mE = 500 lx 55

Figure A.4 -- Daylight supply factor CTL,Vers,SA for areas with activated solar radiation protection and/or glare protection as a function of the factor C'TL,Vers,SA and the daylight factor DRb of the building carcass roof opening 56

Figure A.5 -- Personal office - illumination solution 1 57

Figure A.6 -- Personal office - illumination solution 2 58

Figure A.7 -- Personal office - illumination solution 3 59

Figure A.8 -- Office for two occupants -- illumination solution 1 60

Figure A.9 -- Office for two occupants - illumination solution 2 61

Figure A.10 -- Office for two occupants - illumination solution 3 62

Figure A.11 -- Workgroup office - illumination solution 1 63

Figure A.12 -- Workgroup office - illumination solution 2 64

Figure A.13 -- Call centre - illumination solution 1 66

Figure A.14 -- Call centre - illumination solution 2 68

Figure A.15 -- Corridor - illumination solution 1 70

Figure A.16 -- Corridor - illumination solution 2 71

Figure A.17 -- Production hall - illumination solution 1 72

Figure A.18 -- Production hall - illumination solution 2 73

Figure A.19 -- Rooflights 74

-- Prestandard -- Tables Table 1 -- Calculation values of the specific electrical evaluation power pj,lx in relation to the floor area per lx of maintained illuminance at the work plane, for luminaires with tubular fluorescent lamps and electronic ballast (EB) 20

Table 2 -- Correction factor kL to account for different types of lamp, with reference to Table 1 21

Table 3 -- Correction factor kR to account for the effect of the space geometry in relation to the room index k 22

Table 4 -- Utilization factors R as a function of the illumination type and the room index 23

Table 5 -- Factor kBG for determining the power of a system from the power consumption of lamps 24

Table 6 -- Daylight supply classification as a function of the daylight factor DRb,j of the building carcass opening 30

Table 7 -- Relative times trel,TL,SNA,j and trel,TL,SA,j for de-activated and activated solar radiation and/or glare protection systems, as a function of the façade orientation 31

Table 8 -- Typical values of light transmittance D65,SNA of transparent building components 33

Table 9 -- Daylight supply factor CTL,Vers,SNA,j as a function of the effective light transmittance of the façade, daylight supply factor, maintained illuminance and façade orientation 34

Table 10 -- Parameters a1 und a2 to be used in equation (28), as a function of the maintained illuminance mE 35

Table 11 -- Parameter a3 to be used in equation (28) to account for the façade orientation 35

Table 12 -- System solutions (to be applied for the period trel,TL,SA,j) 36

Table 13 -- Typical values of light transmittance D65, U and g of components frequently used in rooflight construction 38

Table 14 -- External daylight factor Da as a function of the façade slope F for a floor reflectance B of 0,2 (without taking obstruction into account) 40

Table 15 -- Dome light utilization factors R, as a function of the room index k and the geometry parameters of the upstand design 41

Table 16 -- Utilization factors R of rooflights in sawtooth roofs (sheds), as a function of the room index and the geometry parameters 42

Table 17 -- Classification of daylight supply as a function of the daylight factor jD 43

Table 18 -- Daylight supply factor CTL,Vers,j of spaces with rooflights as a function of the daylight supply classification and the maintained illuminance for façades with different orientations and slopes 43

Table 19 -- Correction factor CTL,kon,j to account for the effect of daylight-responsive control systems in a zone n, as a function of the maintained illuminance mE and the daylight supply classification 45

Table 20 -- Monthly distribution key factors vMonat,i for vertical façades 46

Table 21 -- Monthly distribution key factors vMonat,i for rooflights 46

Table 22 -- Factor CPrä,kon,j to account for the efficiency of presence detection systems 47

Table A.1 --Typical effective light transmittance eff,SA of various types of solar radiation protection and/or Table A.2 -- Typical values of the distribution key factor VSA,j for various types of façade components 53

Table A.3 -- Monthly energy use for continuous-type rooflights 78

Table A.4 -- Monthly energy use for shed rooflights 78