

# DIN EN 14934:2007-12 (E)

## Thermal insulation and light weight fill products for civil engineering applications - Factory made products of extruded polystyrene foam (XPS) - Specification

---

<b>Contents</b>		<b>Page</b>
Foreword .....		4
1	Scope .....	5
2	Normative references .....	5
3	Terms, definitions, symbols, units and abbreviated terms .....	6
3.1	Terms and definitions .....	6
3.2	Symbols, units and abbreviated terms .....	7
4	Requirements .....	9
4.1	General .....	9
4.2	For all applications .....	9
4.3	For specific applications .....	11
5	Test methods .....	17
5.1	Sampling .....	17
5.2	Conditioning .....	17
5.3	Testing .....	17
6	Designation code .....	20
7	Evaluation of conformity .....	21
8	Marking and labelling .....	22
Annex A (normative)	Determination of the declared values of thermal resistance and thermal conductivity .....	23
A.1	Introduction .....	23
A.2	Input data .....	23
A.3	Declared values .....	23
Annex B (normative)	Factory Production Control .....	25
Annex C (normative)	Determination of the aged values of thermal resistance and thermal conductivity .....	29
C.1	Scope .....	29
C.2	Procedure for XPS foam without diffusion tight laminates .....	29
C.3	Procedure for XPS foam for use with diffusion tight facings on both sides .....	30
C.4	Calculation of aged value .....	31
C.5	Blowing agent .....	32
C.6	Product grouping .....	32
Annex D (normative)	Determination of behaviour under cyclic square wave load .....	33
D.1	Scope .....	33
D.2	Definitions .....	33
D.3	Principle .....	34
D.4	Testing equipment .....	34

D.5	Test specimens .....	35
D.6	Procedure .....	35
D.7	Calculation and expression of results .....	37
D.8	Accuracy of measurement .....	38
D.9	Test report .....	38
Annex E (informative) Additional properties .....		39
E.1	General .....	39
E.2	Compressive modulus of elasticity .....	39
E.3	Determination of volume percentage of open and closed cells .....	39
E.4	Determination of shear strength .....	39
Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 89/106/EEC, EU Construction Products Directive .....		41
ZA.1	Scope and relevant characteristics .....	41
ZA.2	Procedures for the attestation of conformity of extruded polystyrene foam products .....	43
ZA.3	CE Marking and labelling .....	48
Bibliography .....		50
Figures	Figure D.1 -- Required load cycle during the fatigue test .....	35
	Figure D.2 -- Dimensions of the test specimen .....	36
	Figure D.3 -- Test set-up .....	37
	Figure ZA.1 -- Example CE marking information .....	49
Tables	Table 1 -- Tolerances of length, width, squareness and flatness .....	10
	Table 2 -- Classes for thickness tolerances .....	10
	Table 3 -- Levels for compressive stress at 10 % deformation or compressive strength .....	11
	Table 4 -- Levels for deformation under specified compressive load and temperature conditions ....	12
	Table 5 -- Levels for compressive stress at 2 % deformation or compressive strength .....	13
	Table 6 -- Levels for compressive stress at 5 % deformation or compressive strength .....	13
	Table 7 -- Levels for long term water absorption by total immersion .....	16
	Table 8 -- Levels for long term water absorption by diffusion .....	16
	Table 9 -- Levels for Freeze-thaw resistance .....	16
	Table 10 -- Test methods, test specimens and conditions .....	18
	Table A.1 -- Values of k for one sided 90 % tolerance interval with a confidence level of 90 % .....	24
	Table B.1 -- Minimum product testing frequencies .....	25
	Table B.2 -- Minimum product testing frequencies for the reaction to fire characteristics .....	27
	Table E.1 -- Test methods, test specimens, conditions and minimum testing frequencies .....	40
	Table ZA.1 -- Relevant clauses .....	42

<b>Table ZA.2 -- System(s) of attestation of conformity .....</b>	<b>44</b>
<b>Table ZA.2.1 -- Assignment of evaluation of conformity tasks for products under system 1 .....</b>	<b>45</b>
<b>Table ZA.2.2 -- Assignment of evaluation of conformity tasks for products under system 3 and 3 (with 4 for RtF) .....</b>	<b>46</b>