

DIN EN 14934:2007-12 (E)

Thermal insulation and light weight fill products for civil engineering applications - Factory made products of extruded polystyrene foam (XPS) - Specification

Contents		Page
Foreword		4
1	Scope	5
2	Normative references	5
3	Terms, definitions, symbols, units and abbreviated terms	6
3.1	Terms and definitions	6
3.2	Symbols, units and abbreviated terms	7
4	Requirements	9
4.1	General	9
4.2	For all applications	9
4.3	For specific applications	11
5	Test methods	17
5.1	Sampling	17
5.2	Conditioning	17
5.3	Testing	17
6	Designation code	20
7	Evaluation of conformity	21
8	Marking and labelling	22
Annex A (normative)	Determination of the declared values of thermal resistance and thermal conductivity	23
A.1	Introduction	23
A.2	Input data	23
A.3	Declared values	23
Annex B (normative)	Factory Production Control	25
Annex C (normative)	Determination of the aged values of thermal resistance and thermal conductivity	29
C.1	Scope	29
C.2	Procedure for XPS foam without diffusion tight laminates	29
C.3	Procedure for XPS foam for use with diffusion tight facings on both sides	30
C.4	Calculation of aged value	31
C.5	Blowing agent	32
C.6	Product grouping	32
Annex D (normative)	Determination of behaviour under cyclic square wave load	33
D.1	Scope	33
D.2	Definitions	33
D.3	Principle	34
D.4	Testing equipment	34

D.5	Test specimens	35
D.6	Procedure	35
D.7	Calculation and expression of results	37
D.8	Accuracy of measurement	38
D.9	Test report	38
Annex E (informative) Additional properties		39
E.1	General	39
E.2	Compressive modulus of elasticity	39
E.3	Determination of volume percentage of open and closed cells	39
E.4	Determination of shear strength	39
Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 89/106/EEC, EU Construction Products Directive		41
ZA.1	Scope and relevant characteristics	41
ZA.2	Procedures for the attestation of conformity of extruded polystyrene foam products	43
ZA.3	CE Marking and labelling	48
Bibliography		50
Figures	Figure D.1 -- Required load cycle during the fatigue test	35
	Figure D.2 -- Dimensions of the test specimen	36
	Figure D.3 -- Test set-up	37
	Figure ZA.1 -- Example CE marking information	49
Tables	Table 1 -- Tolerances of length, width, squareness and flatness	10
	Table 2 -- Classes for thickness tolerances	10
	Table 3 -- Levels for compressive stress at 10 % deformation or compressive strength	11
	Table 4 -- Levels for deformation under specified compressive load and temperature conditions	12
	Table 5 -- Levels for compressive stress at 2 % deformation or compressive strength	13
	Table 6 -- Levels for compressive stress at 5 % deformation or compressive strength	13
	Table 7 -- Levels for long term water absorption by total immersion	16
	Table 8 -- Levels for long term water absorption by diffusion	16
	Table 9 -- Levels for Freeze-thaw resistance	16
	Table 10 -- Test methods, test specimens and conditions	18
	Table A.1 -- Values of k for one sided 90 % tolerance interval with a confidence level of 90 %	24
	Table B.1 -- Minimum product testing frequencies	25
	Table B.2 -- Minimum product testing frequencies for the reaction to fire characteristics	27
	Table E.1 -- Test methods, test specimens, conditions and minimum testing frequencies	40
	Table ZA.1 -- Relevant clauses	42

Table ZA.2 -- System(s) of attestation of conformity	44
Table ZA.2.1 -- Assignment of evaluation of conformity tasks for products under system 1	45
Table ZA.2.2 -- Assignment of evaluation of conformity tasks for products under system 3 and 3 (with 4 for RtF)	46