

DIN EN 12697-31:2007-06 (E)

Bituminous mixtures - Test methods for hot mix asphalt - Part 31: Specimen preparation by gyratory compactor

| Contents | | Page |
|--|--|-------------|
| Foreword | | 4 |
| 1 | Scope | 7 |
| 2 | Normative references | 7 |
| 3 | Terms, definitions and symbols | 8 |
| 3.1 | Terms and definitions | 8 |
| 3.2 | Symbols | 9 |
| 4 | Principle | 10 |
| 5 | Apparatus | 10 |
| 5.1 | Test device | 10 |
| 5.2 | Metallic moulds | 11 |
| 5.3 | Round metallic inserts | 11 |
| 5.4 | Device for measuring the distance between inserts | 11 |
| 5.5 | Device for counting the number of rotations to within one revolution | 11 |
| 6 | Preparation of specimens | 12 |
| 6.1 | Mass of mixture to be introduced in the mould | 12 |
| 6.2 | Preparation of test pieces | 12 |
| 7 | Test procedure | 13 |
| 7.1 | Preliminary setting | 13 |
| 7.2 | Compaction | 13 |
| 8 | Test report | 14 |
| 9 | Precision | 15 |
| Annex A (normative) Procedure for setting the angle and force for types of gyratory compactor using central reference material | | 16 |
| A.1 | Scope | 16 |
| A.2 | Principle | 16 |
| A.3 | Gyratory-type testing procedure | 16 |
| A.4 | Procedure to test the conformity of a gyratory compactor to a type | 18 |
| A.5 | Summary of the gyratory calibration chain | 19 |
| Annex B (normative) Procedure to evaluate the gyratory compactor internal angle of gyration using a self-contained measurement unit | | 20 |
| B.1 | Scope | 20 |
| B.2 | Principle | 20 |
| B.3 | Equipment | 20 |
| B.4 | Procedure | 21 |
| B.5 | Calculation | 23 |
| B.6 | Compliance | 24 |
| B.7 | Report | 25 |
| B.8 | Precision data | 25 |

| | |
|--|-----------|
| Annex C (normative) Procedure to evaluate the gyratory compactor (GC) internal angle of gyration and related parameters using simulated loading | 26 |
| C.1 Scope | 26 |
| C.2 Principle | 26 |
| C.3 Procedure | 26 |
| C.4 Calculation of results | 27 |
| C.5 Compliance | 28 |
| C.6 Report | 28 |
| C.7 Precision and bias | 28 |
| Bibliography | 30 |