ISO 8873-2:2007-05 (E)

Rigid cellular plastics - Spray-applied polyurethane foam for thermal insulation - Part 2: Application

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms and definitions 2

4 Requirements 3
4.1 Manufacturer 3
4.2 Spray polyurethane foam contractor 3
4.3 Spray polyurethane foam installer 4
4.4 Apprentice installer 6
4.5 Material 6
4.6 Equipment 6
4.7 Installation 6

5 Applications 8
5.1 General 8
5.2 Air barrier system application 8
5.3 Vapour barrier application 8
5.4 Exterior foundation insulation application 8
5.5 Interior foundation insulation application 8
5.6 Cathedral ceilings, flat ceilings and decks over heated spaces 8
5.7 Attic application, exterior (cavity) and interior wall application 8

6 Sampling 8

7 Test methods 9
7.1 Determination of density 9
7.2 Cohesion and adhesion test 10
7.3 Verification of substrate (application surface) preparation 10
7.4 Reporting requirements 10

8 Manufacturer's marking 11

9 Manufacturer's documentation 12

10 Limitations 12

Annex A (normative) Substrate preparation 13

Annex B (normative) Selection of chemical components (system) 16

Annex C (informative) Climatic factors 17

Annex D (normative) Job-site set up 18

Annex E (informative) Trouble shooting and repair 20

Annex F (normative) Handling and safety precautions 22

Annex G (normative) Disposal and detoxification of drums 25

Annex H (informative) Daily work record 27

Annex I (informative) Example of job site label 29

Annex J (informative) Outline of licensed installer training programme 30

Annex K (normative) Minimum equipment for site test kit 36

Bibliography 37