

# ISO 8873-3:2007-05 (E)

## Rigid cellular plastics - Spray-applied polyurethane foam for thermal insulation - Part 3: Test methods

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Standard laboratory procedure for the determination of volatile organic compound emissions from cellular plastic products .....</b>	<b>3</b>
<b>4.1</b>	<b>General .....</b>	<b>3</b>
<b>4.2</b>	<b>Apparatus and equipment .....</b>	<b>3</b>
<b>4.3</b>	<b>Test procedure .....</b>	<b>5</b>
<b>4.4</b>	<b>Estimation of indoor air concentrations .....</b>	<b>7</b>
<b>4.5</b>	<b>Test report .....</b>	<b>9</b>
<b>4.6</b>	<b>Assessment of acceptability of the material .....</b>	<b>9</b>
<b>4.7</b>	<b>Accuracy .....</b>	<b>9</b>
<b>5</b>	<b>Test method for air permeance of spray-applied polyurethane foam .....</b>	<b>10</b>
<b>5.1</b>	<b>General .....</b>	<b>10</b>
<b>5.2</b>	<b>Number of samples .....</b>	<b>10</b>
<b>5.3</b>	<b>Apparatus (see Figure 2) .....</b>	<b>10</b>
<b>5.4</b>	<b>Test procedure for air permeance of spray-applied polyurethane foam .....</b>	<b>12</b>
<b>5.5</b>	<b>Test procedure for control .....</b>	<b>16</b>
<b>5.6</b>	<b>Test report .....</b>	<b>17</b>