

### Contents

|           |  |
|-----------|--|
|           | Foreword   |
|           | Introduction   |
| 1         | Scope  |
| 2         | Normative references   |
| 3         | Terms and definitions  |
| 4         | Requirements   |
| 4.1       | Hazardous elements   |
| 4.2       | Dimensions and angles  |
| 4.3       | Release  |
| 5         | Test methods   |
| 5.1       | Dimensions   |
| 5.1.1     | Apparatus  |
| 5.1.2     | Measurement procedures   |
| 5.1.2.1   | Angle of torque (Figure 1)                                     |
| 5.1.2.2   | Angulation (see Figure 2)                                      |
| 5.1.2.3   | In-out (see Figure 3)  |
| 5.1.2.3.1 | Bracket in-out [see Figure 3 a)]                               |
| 5.1.2.3.2 | Tube in-out [see Figure 3 b)]                                  |
| 5.1.2.4   | Rotational offset (see Figure 4)                               |
| 5.1.2.5   | Slot depth (see Figure 5)                                      |
| 5.1.2.6   | Slot height (see Figure 5)                                     |
| 5.2       | Static immersion corrosion test method                         |
| 5.2.1     | Apparatus  |
| 5.2.2     | Samples  |
| 5.2.3     | Test procedure   |
| 5.3       | Treatment of results   |
| 6         | Packaging and labelling information to be provided to the user |
| 6.1       | General requirements   |
| 6.2       | Packaging  |
| 6.3       | Labelling  |