DIN EN 13850:2013-04 (E)

Postal services - Quality of service - Measurement of the transit time of end-to-end services for sing le piece priority mail and first class mail

Contents

Page

Foreword 6

0 Introduction 7
0.1 General 7
0.2 Regulatory background 7

1 Scope 8

2 Normative references 8

3 Terms and definitions 9

4 Symbols and abbreviations 15

5 Transit time as a Quality-of-Service indicator 16
5.1 General 16
5.2 Transit time calculation 17
5.2.1 Measurement unit 17
5.2.2 Continuity of measurement 17
5.2.3 Calculation of the transit time 17
5.3 Service performance indicators 18

6 Methodology 18
6.1 Representative sample design 18
6.2 Minimum Sample Size (MSS) 19
6.2.1 Domestic measurement systems 19
6.2.2 Cross-border measurement systems 19
6.3 Determination of the design basis 20
6.3.1 General 20
6.3.2 Estimation of real mail flows 20
6.3.3 Design basis 21
6.4 Discriminant Mail Characteristics (DMC) 21
6.4.1 General 21
6.4.2 Determination of the discriminant mail characteristics 21
6.4.3 Geographical stratification 22
6.5 Geographical distribution of the panel 23
6.5.1 General 23
6.5.2 Small panels up to 90 panellists 23
6.5.3 Bigger panels over 90 panellists 24
6.6 Integrity of the measurement 25
6.7 Unbiased sample design 26

7 Report 26
7.1 Measurement results 26
7.2 Estimators 27
7.2.1 Accuracy 27
7.2.2 Panel turnover in relation to accuracy 27
7.3 Weighting of the results 28
7.3.1 Reasons for implementing a weighting system 28
7.3.2 Weighting caps 28
7.3.3 Design changes due to annual mail characteristic and postal flow changes 29

7.4 Content and timing 29

8 Quality control and auditing 30

9 The annexes 31

Annex A (normative) Accuracy calculation 32

A.1 Scope 32
A.1.1 General 32
A.1.2 Two stage sampling approach 32
A.1.3 Covariance / Stratification / Accuracy calculation 32
A.1.4 The design factor 32
A.2 Symbols 33
A.3 Variance calculation for one stratum 33
A.3.1 General calculation method 33
A.3.2 Relation-to-total variation 34
A.3.3 Intra-relation variation 34
A.4 Variance calculation for a stratified sample 35
A.4.1 Variance of a weighted sample design 35
A.4.2 Final weight of the individual item 35
A.4.3 Weighting basis 36
A.4.4 Combination of weighting and covariance 36
A.5 Calculation of the confidence interval 37
A.5.1 General 37
A.5.2 Normal approximation 37
A.5.3 Agresti-Coull approximation 39
A.5.4 Inverse Beta approximation 40

Annex B (normative) Transit Time Calculation Rule 41

B.1 Working week transit time calculation rule / domestic and cross-border mail 41
B.2 Calculation rules 42
B.2.1 Rule 1: Collection Monday-Friday / Delivery Monday-Friday 42
B.2.2 Rule 2: Collection Monday-Friday / Delivery Tuesday-Saturday 43
B.2.3 Rule 3: Collection Monday-Friday / Delivery Monday-Saturday 44
B.2.4 Rule 4: Collection Monday-Saturday / Delivery Monday-Friday 45
B.2.5 Rule 5: Collection Sunday-Friday / Delivery Monday-Friday 46
B.2.6 Rule 6: Collection Monday-Saturday / Delivery Monday-Saturday 47
B.2.7 Rule 7: Collection Sunday-Friday / Delivery Monday-Saturday 48

Annex C (normative) Quality control and auditing 49

C.1 Quality Control 49
C.1.1 Statistical design 49
C.1.2 Test item production 49
C.1.3 Provision of test items to the sender panellists 49
C.1.4 Sending test items 50
C.1.5 Receiving test items 50
C.1.6 Data collection 50
C.1.7 Data analysis and reporting 50
C.1.8 Archiving 51
C.1.9 Quality control and Information Technology (IT) 51
C.2 Auditing - general remarks 51
C.3 Audit of the design basis 52
C.3.1 General 52
C.3.2 Methodological audit 52
C.3.3 Results 52
C.4 Audit of the Quality-of-Service measurement system 53
C.4.1 Panel audit 53
C.4.2 Stability of the parameters 53
C.4.3 Instructions given to the panellists 53

C.4.4 General Audit of the system 53

Annex D (normative) Relaxation related to flows with small real mail volumes 54

D.1 General 54
D.1.1 Scope 54
D.1.2 Measurement period 54
D.1.3 Minimum Sample Size (MSS) 54
D.2 Domestic mail flows 55
D.3 Cross-border mail flows 56

Annex E (informative) Purpose of postal Quality of Service standards 58

E.1 General 58
E.2 Benefits of QoS standards 58
E.3 Use of the survey results for quality improvement 59
E.3.1 Detailed analysis 59
E.3.2 Other / broader concepts 59

F.2 Responsibilities 60
F.2.1 General 60
F.2.2 Regulatory authority 61
F.2.3 Postal operator 61
F.2.4 Independent Performance monitoring organisation 62
F.2.5 Auditor 62
F.3 Design of the measurement system 63
F.3.1 Design parameters 63
F.3.2 Field of study 64
F.3.3 Geographical coverage 65
F.3.4 Design requirements due to national peculiarities 66
F.4 Small mail volumes 66
F.4.1 General 66
F.4.2 Domestic 66
F.4.3 Cross border 66
F.5 Measurement organisation 67
F.5.1 Role of the contractor 67
F.5.2 Independence 67
F.5.3 Tender process 67

Annex G (informative) Design basis 68

G.1 Discriminant characteristics 68
G.1.1 Representative sample design 68
G.1.2 Studies for the evaluation of possible candidates 69
G.1.3 Connection between Design Basis and Sample Design 71
G.2 Design basis 72
G.2.1 Real mail studies for domestic mail 72
G.2.2 Real mail studies for cross border mail 75
G.2.3 Alternative design bases 75
G.3 Frequency of update 76

H.1 Stages of the survey 77
H.1.1 Preparation 77
H.1.2 Set-up 77
H.1.3 Pilot (testing phase) 77
H.1.4 Faster implementation 78
H.1.5 Measurement period 78
H.2 Panellists 79
H.2.1 Representativeness 79
H.2.2 Risk of panellist identification 79
H.2.3 Induction and delivery 80
H.2.4 Panel turnover 82

H.3 Validation and transit time calculation 82
H.3.1 Data validation 82
H.3.2 Service standard 84
H.3.3 Transit-time calculation rule 85
H.3.4 Loss 86
H.3.5 Force majeure 86
H.4 Weighting 88
H.4.1 Weighting and stratification 88
H.4.2 Weighting caps 93
H.5 Reporting of results 95
H.5.1 Reporting 95
H.5.2 Archiving 97
H.6 Audit 98
H.6.1 General 98
H.6.2 Position of the auditor 98
H.6.3 Audit report 98
H.6.4 Selection of the auditor 99
H.6.5 Frequency of audit 99
H.7 Implementation timetables 99

Annex I (informative) Application of the accuracy calculation 103

I.1 Limitations of the accuracy calculation methods provided 103
I.1.1 Participants with high mail loads 103
I.1.2 Disproportional models beyond the capping system 103
I.2 Recommendations for the application of the rules 104
I.2.1 Unstratified end-to-end sample 104
I.2.2 Stratified simple random sample 104
I.2.3 Approximation of the Binomial distribution 105
I.2.4 Accuracy 105
I.2.5 Accuracy application 105
I.3 The sample size 107
I.4 General Example for a national yearly result 107
I.4.1 Introduction 107
I.4.2 Design factor for an unstratified end-to-end sample 109
I.4.3 Design factor for a stratified random sample 110
I.4.4 Accuracy calculation 111
I.5 Simplified scenarios 113
I.5.1 General 113
I.5.2 Transit time results up to 96 % 113
I.5.3 Fully proportional sample 113
I.5.4 Single induction / delivery point 114
I.5.5 Induction / delivery point with only one letter 114

J.1 Methodology 115
J.1.1 Accuracy and Minimum Sample Size (MSS) 115
J.1.2 MSS for flows with small real mail volumes 115
J.2 Transit-time calculation rule 116
J.3 Accuracy calculation method 116
J.3.1 Improved applicability 116
J.3.2 Reduced bias in calculation 116