DIN 3021-1:2023-06 (E)

Hose clamps - Spring band clamp - Part 1: Dimensions, marking, materials, types

Contents

Page

Foreword 4

1 Scope 5

2 Normative references 5

3 Terms and definitions 5

4 Types, dimensions, designations 5

5 Clamping forces 13
5.1 3-channel clamping forces for type A and type B 13
5.2 4-channel clamping forces for type A and type B 15

6 Preselection of nominal diameter 19

7 Materials 19

8 Design 20
8.1 Workpiece edges 20
8.2 Surface protection 20

9 Technical delivery conditions 20

10 Marking 20

11 Clamp assembly 20

Annex A (informative) Explanatory notes and design details 21

Annex B (informative) Tabular layout of product properties 22

Bibliography 23

Figures

Figure 1 — Type A (standard spring band clamp) 6

Figure 2 — Type B (space-saving spring band clamp) 6

Figure 3 — 3-channel clamping forces for type A and type B 13

Figure 4 — 4-channel clamping forces for type A and type B 15

Figure 5 — Assembled hose-spigot joint 19

Tables

Table 1 — Dimensions for type A, *c* = 12 mm **7**

Table 2 — Dimensions for type A, *c* = 15 mm **9**

Table 3 — Dimensions for type B, *c* = 12 mm **11**

Table 4 — 3 channel clamping forces for type A and type B with a clamp width of *c* = 12 mm **13**

Table 5 — 4-channel clamping forces for type A and type B with a clamp width of *c* = 12 mm **16**

Table 6 — 4-channel clamping forces for type A with a clamp width of *c* = 15 mm **17**

Table 7 — Material analysis, chemical composition **20**