DIN EN ISO 7731:2008-12 (E)

Ergonomics - Danger signals for public and work areas - Auditory danger signals (ISO 7731:2003)

Contents

Page

Foreword 3

Introduction 4

1 Scope 5

2 Normative references 5

3 Terms, definitions and symbols 5

4 Safety requirements 7
4.1 General 7
4.2 Recognition 7
4.2.1 Introduction 7
4.2.2 Audibility 7
4.2.3 Distinctiveness 7
4.2.4 Unambiguity 7
4.2.5 Moving sources 7
4.3 Review of the signal 8
4.4 Recommended maximum level of the danger signal 8

5 Test methods 8
5.1 Measurement equipment 8
5.2 Objective acoustic measurements 8
5.2.1 General 8
5.2.2 Weighted measurements 8
5.2.3 Measurements made in the frequency domain 8
5.2.4 Measurement of the auditory signal with ambient noise present 9
5.3 Subjective test method 9

6 Design criteria for auditory danger signals 9
6.1 General 9
6.2 Sound-pressure level 9
6.3 Spectral characteristics 10
6.4 Temporal characteristics 10
6.4.1 Temporal distribution of the danger signal 10
6.4.2 Temporal distribution of the frequencies 10
6.4.3 Duration of the danger signals 11
6.5 Information required from suppliers 11

Annex A (normative) Definitions of symbols 12

Annex B (normative) Calculation of effective masked threshold 13

Annex C (normative) Listening test 14

Annex D (informative) Examples of danger signals 15

Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 98/37/EC 21

Annex ZB (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2006/42/EC 22

Bibliography 23