

ISO 1004-2:2013-06 (E)

Information processing - Magnetic ink character recognition - Part 2: Print specifications for CMC7

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms, definitions, symbols and abbreviations	1
3.1	Terms and definitions	1
3.2	Symbols and abbreviations	2
4	Character configuration	3
4.1	Code description	3
4.2	Configuration	3
5	Means of automatic sensing	4
6	Reference edges of documents	4
7	Print location	4
7.1	Horizontal location	4
7.2	Vertical location	4
8	Clear band	4
9	Character spacing and alignment	5
9.1	Horizontal character spacing	5
9.2	Vertical misalignment	5
10	Character definition and tolerances	5
10.1	Definitions	5
10.2	Stroke edge zones and mean edges	6
10.3	Skew angle	6
10.4	Stroke width L	6
10.5	Stroke interval P	6
11	Extraneous ink (spots)	7
11.1	Extraneous ink front	7
11.2	Extraneous ink back	7
12	Voids	7
13	Segment end zones	7
14	Uniformity of ink	7
15	Debossment	8
16	Signal level	8
16.1	Description of the signal	8
16.2	Definitions relating to signal level	8
16.3	Allowable signal level range	8

16.4	Nominal signal level	9
16.5	Residual signal level	9
17	Paper	9
18	MICR ink permanence	9
19	Drawings of the printed characters of Font CMC 7	10
	Annex A (informative) Use of CMC7 Symbols	32