ISO 1004-2:2013-06 (E)

Information processing - Magnetic ink character recognition - Part 2: Print specifications for CMC7

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Terms, definitions, symbols and abbreviations 1
3.1 Terms and definitions 1
3.2 Symbols and abbreviations 2

4 Character configuration 3
4.1 Code description 3
4.2 Configuration 3

5 Means of automatic sensing 4

6 Reference edges of documents 4

7 Print location 4
7.1 Horizontal location 4
7.2 Vertical location 4

8 Clear band 4

9 Character spacing and alignment 5
9.1 Horizontal character spacing 5
9.2 Vertical misalignment 5

10 Character definition and tolerances 5
10.1 Definitions 5
10.2 Stroke edge zones and mean edges 6
10.3 Skew angle 6
10.4 Stroke width L 6
10.5 Stroke interval P 6

11 Extraneous ink (spots) 7
11.1 Extraneous ink front 7
11.2 Extraneous ink back 7

12 Voids 7

13 Segment end zones 7

14 Uniformity of ink 7

15 Debossment 8

16 Signal level 8
16.1 Description of the signal 8
16.2 Definitions relating to signal level 8
16.3 Allowable signal level range 8

16.4 Nominal signal level 9
16.5 Residual signal level 9

17 Paper 9

18 MICR ink permanence 9

19 Drawings of the printed characters of Font CMC 7 10

Annex A (informative) Use of CMC7 Symbols 32