

# ISO 1004-2:2013-06 (E)

## Information processing - Magnetic ink character recognition - Part 2: Print specifications for CMC7

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms, definitions, symbols and abbreviations .....</b>	<b>1</b>
<b>3.1</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>3.2</b>	<b>Symbols and abbreviations .....</b>	<b>2</b>
<b>4</b>	<b>Character configuration .....</b>	<b>3</b>
<b>4.1</b>	<b>Code description .....</b>	<b>3</b>
<b>4.2</b>	<b>Configuration .....</b>	<b>3</b>
<b>5</b>	<b>Means of automatic sensing .....</b>	<b>4</b>
<b>6</b>	<b>Reference edges of documents .....</b>	<b>4</b>
<b>7</b>	<b>Print location .....</b>	<b>4</b>
<b>7.1</b>	<b>Horizontal location .....</b>	<b>4</b>
<b>7.2</b>	<b>Vertical location .....</b>	<b>4</b>
<b>8</b>	<b>Clear band .....</b>	<b>4</b>
<b>9</b>	<b>Character spacing and alignment .....</b>	<b>5</b>
<b>9.1</b>	<b>Horizontal character spacing .....</b>	<b>5</b>
<b>9.2</b>	<b>Vertical misalignment .....</b>	<b>5</b>
<b>10</b>	<b>Character definition and tolerances .....</b>	<b>5</b>
<b>10.1</b>	<b>Definitions .....</b>	<b>5</b>
<b>10.2</b>	<b>Stroke edge zones and mean edges .....</b>	<b>6</b>
<b>10.3</b>	<b>Skew angle .....</b>	<b>6</b>
<b>10.4</b>	<b>Stroke width L .....</b>	<b>6</b>
<b>10.5</b>	<b>Stroke interval P .....</b>	<b>6</b>
<b>11</b>	<b>Extraneous ink (spots) .....</b>	<b>7</b>
<b>11.1</b>	<b>Extraneous ink front .....</b>	<b>7</b>
<b>11.2</b>	<b>Extraneous ink back .....</b>	<b>7</b>
<b>12</b>	<b>VOIDS .....</b>	<b>7</b>
<b>13</b>	<b>Segment end zones .....</b>	<b>7</b>
<b>14</b>	<b>Uniformity of ink .....</b>	<b>7</b>
<b>15</b>	<b>Debossment .....</b>	<b>8</b>
<b>16</b>	<b>Signal level .....</b>	<b>8</b>
<b>16.1</b>	<b>Description of the signal .....</b>	<b>8</b>
<b>16.2</b>	<b>Definitions relating to signal level .....</b>	<b>8</b>
<b>16.3</b>	<b>Allowable signal level range .....</b>	<b>8</b>

<b>16.4</b>	<b>Nominal signal level .....</b>	<b>9</b>
<b>16.5</b>	<b>Residual signal level .....</b>	<b>9</b>
<b>17</b>	<b>Paper .....</b>	<b>9</b>
<b>18</b>	<b>MICR ink permanence .....</b>	<b>9</b>
<b>19</b>	<b>Drawings of the printed characters of Font CMC 7 .....</b>	<b>10</b>
	<b>Annex A (informative) Use of CMC7 Symbols .....</b>	<b>32</b>