ISO 3531-2:2022-04 (E)

Financial services - Financial in formation eXchange session layer - Part 2: FIX session layer

Contents

Page

Foreword vi

Introduction vii

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 FIX session 4
4.1 General 4
4.2 Sequence numbers 5
4.3 Identifying the FIX session 6
4.3.1 General 6
4.3.2 The FIX session profile 6
4.3.3 Identification of FIX session peers 6
4.3.4 Validation of SendingTime(52) 7
4.3.5 Additional fields available for peer identification 7
4.4 Establishing a FIX connection 7
4.4.1 Transport layer requirements 7
4.4.2 Using the TestMessageIndicator(464) to explicitly identify testing 8
4.4.3 Application layer encryption 8
4.4.4 Heartbeat interval 8
4.4.5 Heartbeat interval determination 8
4.4.6 Maximum message size 9
4.4.7 Specifying application version 9
4.4.8 Specifying supported message types 10
4.4.9 Identification of application system and FIX session processor 10
4.4.10 Responding to a request to establish a FIX session 10
4.4.11 Initial synchronization of messages in a FIX connection 13
4.4.12 Synchronization after successful logon 13
4.5 Extended features for FIX session and FIX connection initiation 17
4.5.1 Using NextExpectedMsgSeqNum(789) to synchronize a FIX session 17
4.5.2 Using ResetSeqNumFlag(141) to reset FIX session for 24 h connectivity 19
4.5.3 Using ResetSeqNumFlag(141) to reset FIX session during FIX connection establishment 19 4.5.4 Using initiator state to restore acceptor session state 19
4.6 Message exchange during a FIX connection 20
4.6.1 FIX connection keep alive (heartbeat) 21
4.6.2 Garbled message processing 21
4.6.3 Missing sequence number 21
4.6.4 Rejecting invalid messages 21
4.6.5 Test Request Processing 22
4.7 FIX connection termination 23
4.7.1 Normal logout processing 24
4.7.2 Logout without acknowledgement from peer 25
4.7.3 Logout with retransmission of missed messages 26
4.7.4 When to terminate a FIX connection by terminating the transport layer connection instead of sending a Logout(35 = 5) 27
4.8 Extended features for FIX connection Termination 27

4.8.1 Using NextExpectedMsgSeqNum(789) when terminating FIX connection due to invalid MsgSeqNum(34) ... 27
4.9 Message recovery ... 28
4.9.1 Ordered message processing ... 28
4.9.2 Request retransmission of messages ... 28
4.9.3 Responding to a ResendRequest(35 = 2) message ... 31

ISO 3531-2:2022(E) 4.9.4 Possible duplicates ... 32
4.9.5 Gap fill process ... 32
4.9.6 Sequence reset ... 34
4.9.7 Processing inbound possible duplicate messages (PossDup(43) set to "Y") ... 35
4.9.8 Processing gaps when receiving FIX session layer messages ... 35
4.10 Resending an unacknowledged application message ... 36
4.10.1 The difference between application layer resend and session layer retransmission ... 37
4.11 FIX session state matrix ... 38
4.11.1 FIX logon process state transition diagram ... 40
4.11.2 FIX logout process state transition diagram ... 41

5 FIX session profiles ... 42
5.1 FIX.4.2 session profile ... 42
5.1.1 Profile identification ... 42
5.1.2 Application version identification ... 42
5.2 FIX4 session profile ... 43
5.2.1 Profile identification ... 43
5.2.2 Application version identification ... 43
5.3 FIXT session profile ... 43
5.3.1 Profile identification ... 43
5.3.2 Multiple application version support over a single FIXT session ... 43
5.3.3 Session default application version identification ... 43
5.3.4 Message type default application version ... 44
5.3.5 Explicit application version per message ... 44
5.3.6 Use of extension packs ... 44
5.3.7 Use of a custom application version ... 45
5.4 Lightweight FIXT (LFIXT session profile) ... 45
5.4.1 Profile identification ... 46
5.4.2 Application version identification ... 46
5.4.3 LFIXT transport layer requirements ... 46
5.4.4 LFIXT compatible mode ... 46
5.4.5 LFIXT succinct mode ... 47
5.4.6 LFIXT and FIXT operating mode interoperability ... 47
5.4.7 Validation of message sequence numbers ... 48
5.4.8 Application layer recovery ... 48
5.4.9 LFIXT initiator connects to LFIXT acceptor ... 48
5.4.10 FIXT initiator connects to LFIXT acceptor (compatible mode) ... 50
5.4.11 Receipt of ResendRequest(35 = 2) message from a FIXT peer ... 53
5.4.12 Processing invalid messages ... 55

6 FIX message routing ... 55
6.1 Message routing details - one firm-to-one firm (point-to-point) ... 55
6.2 Message routing details - third party message routing ... 55

7 Transmitting alternatively encoded messages over a FIX session ... 56
7.1 Use of Attachment group ... 57

8 Components ... 57
8.1 AttachmentGrp ... 57
8.2 AttachmentKeywordGrp ... 58
8.3 HopGrp ... 58
8.4 MsgTypeGrp ... 59
8.5 StandardHeader ... 59
8.6 StandardTrailer ... 61

9 Messages 61
9.1 Heartbeat message 61
9.2 TestRequest message 62
9.3 ResendRequest message 62

ISO 3531-2:2022(E) 9.4 Reject message 62
9.5 SequenceReset message 63
9.6 Logout message 63
9.7 Logon message 64
9.8 XMLnonFIX message 66

10Fields 66

11Code sets 72

11.1 ApplLevelRecoveryIndicatorCodeSet 72
11.2 ApplVerIDCodeSet 73
11.3 AttachmentEncodingTypeCodeSet 73
11.4 EncryptMethodCodeSet 74
11.5 GapFillFlagCodeSet 74
11.6 MsgDirectionCodeSet 74
11.7 MsgTypeCodeSet 75
11.8 PossDupFlagCodeSet 75
11.9 PossResendCodeSet 75
11.10 ResetSeqNumFlagCodeSet 76
11.11 SessionRejectReasonCodeSet 76
11.12 SessionStatusCodeSet 77
11.13 TestMessageIndicatorCodeSet 77

Bibliography 78