

DIN 6932:2011-10 (E)

Design rules for stamped steel parts

| Contents | | Page |
|--|---|-------------|
| Foreword | | 3 |
| 1 | Scope | 4 |
| 2 | Normative references | 4 |
| 3 | General rules | 4 |
| 4 | Design rules | 4 |
| 4.1 | General | 4 |
| 4.2 | Design rules for cut parts | 4 |
| 4.2.1 | Basic principles | 4 |
| 4.2.2 | Shape of pierced holes | 5 |
| 4.2.3 | Hole diameter | 5 |
| 4.2.4 | Notching | 6 |
| 4.2.5 | Piercing and notching on one side | 6 |
| 4.2.6 | Curvatures | 6 |
| 4.2.7 | Curvatures on strip lengths | 6 |
| 4.2.8 | Distances | 7 |
| 4.2.9 | Oblique cutting | 7 |
| 4.2.10 | Positioning guard | 8 |
| 4.3 | Design rules for bent parts | 8 |
| 4.3.1 | Basic principles | 8 |
| 4.3.2 | Bending radii | 8 |
| 4.3.3 | Internal radius/External radius | 8 |
| 4.3.4 | Preparation for bending | 9 |
| 4.3.5 | Minimum leg length | 10 |
| 4.3.6 | Minimum distance from the bending axis | 11 |
| 4.3.7 | Relief holes | 11 |
| 4.4 | Design rules for deep-drawn parts | 11 |
| 4.4.1 | General | 11 |
| 4.4.2 | Earing | 11 |
| 4.4.3 | Radii of curvature | 12 |
| 4.4.4 | h/d ratio | 12 |
| 4.4.5 | Buckling/Wrinkling | 13 |
| 4.4.6 | Bottom flatness | 13 |
| 4.4.7 | Material elongation/Material thickening | 14 |
| 4.4.8 | Box-shaped deep-drawn parts | 14 |
| 4.4.9 | Plunging | 15 |
| 5 | Dimensioning | 15 |
| Annex A (informative) Explanatory notes | | 17 |
| Bibliography | | 18 |