

# DIN EN 13906-3:2014-06 (E)

## Cylindrical helical springs made from round wire and bar - Calculation and design - Part 3: Torsion springs

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
1	Scope .....	4
2	Normative references .....	4
3	Terms and definitions, symbols, units and abbreviated terms .....	4
3.1	Terms and definitions .....	4
3.2	Symbols, units and abbreviated terms .....	5
4	Theoretical torsion spring diagram .....	7
5	Design Principles .....	10
5.1	General .....	10
5.2	Design of the ends .....	10
5.3	Mounting of the ends .....	11
5.4	Design of the spring body .....	11
6	Types of loading .....	12
6.1	General .....	12
6.2	Static and quasi-static loading .....	12
6.3	Dynamic loading .....	12
7	Stress correction factor q .....	13
8	Material property values for the calculations of springs .....	14
9	Design formulate .....	15
9.1	Design assumptions .....	15
9.2	Formulae .....	15
9.2.1	General .....	15
9.2.2	Spring torque .....	15
9.2.3	Angular spring rate .....	15
9.2.4	Developed length of active coils .....	16
9.2.5	Nominal diameter of wire or bar .....	16
9.2.6	Inside coil diameter of the spring .....	16
9.2.7	Outside coil diameter of the spring .....	16
9.2.8	Body length of the spring (excluding ends) .....	16
9.2.9	Number of active coils .....	16
9.2.10	Torsional angle .....	16
9.2.11	Spring work .....	17
9.2.12	Uncorrected bending stress .....	17
9.2.13	Corrected bending stress .....	17
10	Permissible bending stress .....	20
10.1	Permissible bending stress under static or quasi-static loading .....	20
10.2	Permissible stress range under dynamic loading .....	20
10.2.1	Fatigue strength values .....	20
10.2.2	Permissible stress range .....	20
10.2.3	Lines of equal stress ratio .....	21
Bibliography .....		22