

DIN EN 13906-3:2014-06 (E)

Cylindrical helical springs made from round wire and bar - Calculation and design - Part 3: Torsion springs

Contents	Page
Foreword	3
1 Scope	4
2 Normative references	4
3 Terms and definitions, symbols, units and abbreviated terms	4
3.1 Terms and definitions	4
3.2 Symbols, units and abbreviated terms	5
4 Theoretical torsion spring diagram	7
5 Design Principles	10
5.1 General	10
5.2 Design of the ends	10
5.3 Mounting of the ends	11
5.4 Design of the spring body	11
6 Types of loading	12
6.1 General	12
6.2 Static and quasi-static loading	12
6.3 Dynamic loading	12
7 Stress correction factor q	13
8 Material property values for the calculations of springs	14
9 Design formulate	15
9.1 Design assumptions	15
9.2 Formulae	15
9.2.1 General	15
9.2.2 Spring torque	15
9.2.3 Angular spring rate	15
9.2.4 Developed length of active coils	16
9.2.5 Nominal diameter of wire or bar	16
9.2.6 Inside coil diameter of the spring	16
9.2.7 Outside coil diameter of the spring	16
9.2.8 Body length of the spring (excluding ends)	16
9.2.9 Number of active coils	16
9.2.10 Torsional angle	16
9.2.11 Spring work	17
9.2.12 Uncorrected bending stress	17
9.2.13 Corrected bending stress	17
10 Permissible bending stress	20
10.1 Permissible bending stress under static or quasi-static loading	20
10.2 Permissible stress range under dynamic loading	20
10.2.1 Fatigue strength values	20
10.2.2 Permissible stress range	20
10.2.3 Lines of equal stress ratio	21
Bibliography	22