

ISO 22705-1:2021 (E)

Springs — Measurement and test parameters — Part 1: Cold formed cylindrical helical compression springs

Contents

| | |
|-------|--|
| | Foreword |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms, definitions, symbols and abbreviated terms |
| 3.1 | Terms and definitions |
| 3.2 | Symbols and abbreviated terms |
| 4 | Environmental conditions |
| 5 | Qualifications of the person(s) performing the work |
| 6 | Geometries of guiding and supporting devices |
| 7 | Measuring and testing equipment |
| 8 | Measurement and test parameter for technical cold formed cylindrical compression springs |
| 8.1 | Free length (L ₀) |
| 8.1.1 | General |
| 8.1.2 | Type of characteristic |
| 8.1.3 | Measuring and/or testing equipment |
| 8.1.4 | Conditions of measurement and testing |
| 8.1.5 | Method of measurement and testing |
| 8.1.6 | Test location on the product |
| 8.2 | Outside diameter (D _e) |
| 8.2.1 | General |
| 8.2.2 | Type of characteristic |
| 8.2.3 | Measurement and/or testing equipment |
| 8.2.4 | Conditions of measurement and testing |
| 8.2.5 | Method of measurement and testing |
| 8.2.6 | Test location on the product |
| 8.3 | Inside diameter (D _i) |
| 8.3.1 | General |
| 8.3.2 | Type of characteristic |
| 8.3.3 | Measuring and/or testing equipment |
| 8.3.4 | Conditions of measurement and testing |
| 8.3.5 | Method of measurement and testing |
| 8.3.6 | Test location on the product |
| 8.4 | Total number of coils (n _t), number of active coils (n) and coil direction |
| 8.4.1 | General |
| 8.4.2 | Type of characteristic |
| 8.4.3 | Measuring and/or testing equipment |
| 8.4.4 | Conditions of measurement and testing |
| 8.4.5 | Method of measurement and testing |
| 8.4.6 | Test location on the product |
| 8.5 | Applied end coils |
| 8.5.1 | General |
| 8.5.2 | Type of characteristic |
| 8.5.3 | Measuring and/or testing equipment |
| 8.5.4 | Conditions of measurement and testing |
| 8.5.5 | Method of measurement and testing |

- 8.5.6 Test location on the product
- 8.6 Solid length (Lc)/solid force (Fc)
 - 8.6.1 General
 - 8.6.2 Type of characteristics
 - 8.6.3 Measuring and/or testing equipment
 - 8.6.4 Conditions of measurement and testing
 - 8.6.5 Method of measurement and testing
 - 8.6.6 Test location on the product
- 8.7 Spring load (F)
 - 8.7.1 General
 - 8.7.2 Type of characteristic
 - 8.7.3 Measuring and/or testing equipment
 - 8.7.4 Conditions of measurement and testing
 - 8.7.5 Method of measurement and testing
 - 8.7.6 Test location on the product
- 8.8 Spring pitch (p)/distance between the coils
 - 8.8.1 General
 - 8.8.2 Type of characteristic
 - 8.8.3 Measuring and/or testing equipment
 - 8.8.4 Conditions of measurement and testing
 - 8.8.5 Method of measurement and testing
 - 8.8.6 Test location on the product
- 8.9 Ground surface/angle
 - 8.9.1 General
 - 8.9.2 Type of characteristic
 - 8.9.3 Measuring and/or testing equipment
 - 8.9.4 Conditions of measurement and testing
 - 8.9.5 Method of measurement and testing
 - 8.9.6 Test location on the product
- 8.10 Perpendicularity (e1)
 - 8.10.1 General
 - 8.10.2 Type of characteristic
 - 8.10.3 Measuring and/or testing equipment
 - 8.10.4 Conditions of measurement and testing
 - 8.10.5 Method of measurement and testing
 - 8.10.6 Test location on the product
- 8.11 Parallelism (e2)
 - 8.11.1 General
 - 8.11.2 Type of characteristic
 - 8.11.3 Measuring and/or testing equipment
 - 8.11.4 Conditions of measurement and testing
 - 8.11.5 Method of measurement and testing
 - 8.11.6 Test location on the product
- 8.12 Shear-off burr
 - 8.12.1 General
 - 8.12.2 Type of characteristic
 - 8.12.3 Measuring and/or testing equipment
 - 8.12.4 Conditions of measurement and testing
 - 8.12.5 Method of measurement and testing
 - 8.12.6 Test location on the product

Annex A (informative) Calculation of spring rate (R)

- A.1 General
- A.2 Type of characteristic