

ISO 22705-2:2023-02 (E)

Springs - Measurement and test parameters - Part 2: Cold formed cylindrical helical extension springs

| Contents | | Page |
|-----------------|---|-------------|
| Foreword | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms, definitions, symbols and abbreviated terms | 1 |
| 3.1 | Terms and definitions | 1 |
| 3.2 | Symbols and abbreviated terms | 2 |
| 4 | Environmental conditions | 3 |
| 5 | Qualifications of the person(s) performing the work | 3 |
| 6 | Geometries of guiding and supporting devices | 3 |
| 7 | Measuring and testing equipment | 3 |
| 8 | Measurement and test parameter for technical cold formed cylindrical extension springs .. | 4 |
| 8.1 | Free length (L0) | 4 |
| 8.1.1 | General | 4 |
| 8.1.2 | Type of characteristic | 4 |
| 8.1.3 | Measuring and/or testing equipment | 4 |
| 8.1.4 | Conditions of measurement and testing | 4 |
| 8.1.5 | Method of measurement and testing | 4 |
| 8.1.6 | Test location on the product | 7 |
| 8.2 | Body length (LB) | 7 |
| 8.2.1 | General | 7 |
| 8.2.2 | Type of characteristic | 7 |
| 8.2.3 | Measuring and/or testing equipment | 8 |
| 8.2.4 | Conditions of measurement and testing | 8 |
| 8.2.5 | Method of measurement and testing | 8 |
| 8.2.6 | Test location on the product | 10 |
| 8.3 | Spring hook length (LH) | 10 |
| 8.3.1 | General | 10 |
| 8.3.2 | Type of characteristic | 10 |
| 8.3.3 | Measuring and/or testing equipment | 11 |
| 8.3.4 | Conditions of measurement and testing | 11 |
| 8.3.5 | Method of measurement and testing | 11 |
| 8.3.6 | Test location on the product | 13 |
| 8.4 | Hook opening (m) | 13 |
| 8.4.1 | General | 13 |
| 8.4.2 | Type of characteristic | 13 |
| 8.4.3 | Measuring and/or testing equipment | 14 |
| 8.4.4 | Conditions of measurement and testing | 14 |
| 8.4.5 | Method of measurement and testing | 14 |
| 8.4.6 | Test location on the product | 15 |
| 8.5 | Outside diameter (De) | 15 |
| 8.5.1 | General | 15 |
| 8.5.2 | Type of characteristic | 15 |
| 8.5.3 | Measurement and/or testing equipment | 16 |

| | | |
|---|---|----|
| 8.5.4 | Conditions of measurement and testing | 16 |
| 8.5.5 | Method of measurement and testing | 16 |
| 8.5.6 | Test location on the product | 20 |
| 8.6 | Inside diameter (Di) | 20 |
| 8.6.1 | General | 20 |
| 8.6.2 | Type of characteristic | 20 |
| 8.6.3 | Measuring and/or testing equipment | 20 |
| 8.6.4 | Conditions of measurement and testing | 20 |
| 8.6.5 | Method of measurement and testing | 21 |
| 8.6.6 | Test location on the product | 23 |
| 8.7 | Total number of coils (nt), number of active coils (n) and coil direction | 23 |
| 8.7.1 | General | 23 |
| 8.7.2 | Type of characteristic | 23 |
| 8.7.3 | Measuring and/or testing equipment | 25 |
| 8.7.4 | Conditions of measurement and testing | 25 |
| 8.7.5 | Method of measurement and testing | 25 |
| 8.7.6 | Test location on the product | 26 |
| 8.8 | Bending radius (r) | 26 |
| 8.8.1 | General | 26 |
| 8.8.2 | Type of characteristic | 26 |
| 8.8.3 | Measuring and/or testing equipment | 27 |
| 8.8.4 | Conditions of measurement and testing | 27 |
| 8.8.5 | Method of measurement and testing | 27 |
| 8.8.6 | Test location on the product | 27 |
| 8.9 | Spring load (F) | 28 |
| 8.9.1 | General | 28 |
| 8.9.2 | Type of characteristic | 28 |
| 8.9.3 | Measuring and/or testing equipment | 28 |
| 8.9.4 | Conditions of measurement and testing | 28 |
| 8.9.5 | Method of measurement and testing | 28 |
| 8.9.6 | Test location on the product | 29 |
| 8.10 | Spring pitch (p) / distance between the coils (u) | 29 |
| 8.10.1 | General | 29 |
| 8.10.2 | Type of characteristic | 29 |
| 8.10.3 | Measuring and/or testing equipment | 30 |
| 8.10.4 | Conditions of measurement and testing | 30 |
| 8.10.5 | Method of measurement and testing | 30 |
| 8.10.6 | Test location on the product | 30 |
| 8.11 | Loop/ Hook position | 31 |
| 8.11.1 | General | 31 |
| 8.11.2 | Type of characteristic | 31 |
| 8.11.3 | Measuring and/or testing equipment | 31 |
| 8.11.4 | Conditions of measurement and testing | 32 |
| 8.11.5 | Method of measurement and testing | 32 |
| 8.11.6 | Test location on the product | 32 |
| 8.12 | Shear-off burr | 32 |
| 8.12.1 | General | 32 |
| 8.12.2 | Type of characteristic | 32 |
| 8.12.3 | Measuring and/or testing equipment | 33 |
| 8.12.4 | Conditions of measurement and testing | 33 |
| 8.12.5 | Method of measurement and testing | 33 |
| 8.12.6 | Test location on the product | 34 |
| Annex A (Informative) Calculation of spring rate R | | 35 |
| Annex B (Informative) Calculation of initial tension force (Fi) | | 36 |
| Annex C (Informative) Types of hooks | | 38 |