

# ISO 15253:2021 (E)

## Ophthalmic optics and instruments — Optical and electro-optical devices for enhancing low vision

---

### Contents

|         |   |
|---------|---|
|         | Foreword  |
|         | Introduction  |
| 1       | Scope   |
| 2       | Normative references  |
| 3       | Terms and definitions   |
| 4       | Classification  |
| 4.1     | Optical devices   |
| 4.1.1   | Distance vision   |
| 4.1.2   | Near and intermediate vision  |
| 4.1.3   | Retinal illumination reduction or contrast enhancement                              |
| 4.2     | Electro-optical devices   |
| 5       | Requirements  |
| 5.1     | General   |
| 5.1.1   | Risk assessment and management  |
| 5.1.2   | Materials   |
| 5.1.3   | Dimensions and weight   |
| 5.1.4   | Flammability/Ignitability   |
| 5.1.5   | Resistance to perspiration  |
| 5.1.6   | Robustness  |
| 5.1.7   | Resistance to drop  |
| 5.2     | Optical devices   |
| 5.2.1   | Spatial resolution  |
| 5.2.1.1 | Devices designed for near/intermediate use  |
| 5.2.1.2 | Devices designed for distance vision  |
| 5.2.2   | Equivalent power (applies to optical devices designed for near or intermediate use) |
| 5.2.3   | Magnification   |
| 5.2.3.1 | Nominal magnification or trade magnification (applies to all magnifiers)            |
| 5.2.3.2 | Transverse magnification (applies to stand magnifiers)                              |
| 5.2.3.3 | Angular magnification (applies to telescopes designed for distance use)             |
| 5.2.3.4 | Uniformity of magnification   |
| 5.2.4   | Exit image distance (applies to stand magnifiers)                                   |
| 5.2.5   | Entrance pupil diameter (applies to telescopes)                                     |
| 5.2.6   | Transmittance   |
| 5.2.7   | Image relocation  |
| 5.3     | Electro-optical devices   |
| 5.3.1   | Display size  |
| 5.3.2   | Ambient temperatures  |
| 5.3.3   | Image characteristics   |
| 5.3.3.1 | System resolution   |
| 5.3.3.2 | Display magnification   |
| 5.3.3.3 | Display size  |
| 5.3.3.4 | Electro-optical device field of view  |
| 5.3.3.5 | Display luminance   |
| 5.3.3.6 | Contrast ratio  |
| 5.3.4   | Object (XY) table   |
| 5.3.5   | Electro-optical device working distance   |
| 5.3.6   | Text to speech system   |

- 5.3.7 Electrical requirements
  - 5.3.7.1 General
  - 5.3.7.2 Electromagnetic compatibility
- 6 Test methods
  - 6.1 General
  - 6.2 Optical devices
    - 6.2.1 Spatial resolution test
      - 6.2.1.1 Test principle
      - 6.2.1.2 Test set-up
        - 6.2.1.2.1 General
        - 6.2.1.2.2 Magnifiers and telemicroscopes/near-vision telescopes
        - 6.2.1.2.3 Telescopes
      - 6.2.1.3 Test procedure
        - 6.2.1.3.1 Magnifiers and telemicroscopes/near-vision telescopes
        - 6.2.1.3.2 Telescopes
      - 6.2.1.4 Test evaluation
    - 6.2.2 Equivalent power – Magnifiers
    - 6.2.3 Angular magnification – Telescopes
    - 6.2.4 Transverse magnification – Stand magnifiers
    - 6.2.5 Lateral variation of magnification test
    - 6.2.6 Exit image distance – Stand magnifiers
  - 6.3 Electro-optical devices
    - 6.3.1 Display magnification test
      - 6.3.1.1 Equipment
      - 6.3.1.2 Procedure
    - 6.3.2 Uniformity of magnification
- 7 Information to be provided by the manufacturer
  - 7.1 Marking
  - 7.2 Instructions for use
- Annex A (informative) Determination of lateral variation of magnification
  - A.1 Principle
  - A.2 Apparatus
    - A.2.1 Hand and stand magnifiers.
    - A.2.2 Distance and afocal telescopes.
  - A.3 Procedure
    - A.3.1 Magnifier viewing position
    - A.3.2 Near-vision telescope viewing position
    - A.3.3 Afocal and distance telescope viewing position
  - A.4 Assessment
    - A.4.1 Magnifiers
    - A.4.2 Near-vision telescopes
    - A.4.3 Afocal and distance telescopes

Page count: 26