

IEC 60086-3:2021-04 (E)

Primary batteries - Part 3: Watch batteries

Contents

Page

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references	7
3 Terms and definitions	7
4 Physical requirements	8
4.1 Battery dimensions, symbols and size codes	8
4.2 Terminals.....	11
4.3 Projection of the negative terminal (h_5).....	11
4.4 Shape of battery	11
4.5 Mechanical resistance to pressure	12
4.6 Deformation	12
4.7 Leakage.....	12
4.8 Marking.....	12
4.8.1 General	12
4.8.2 Disposal	13
5 Electrical requirements	13
5.1 Electrochemical system, nominal voltage, end-point voltage and open-circuit voltage.....	13
5.2 Closed circuit voltage U_{CC} (CCV), internal resistance and impedance	13
5.3 Capacity	13
5.4 Capacity retention.....	13
6 Sampling and quality assurance	14
7 Test methods.....	14
7.1 Shape and dimensions.....	14
7.1.1 Shape requirement	14
7.2 Electrical characteristics	14
7.2.1 Environmental conditions.....	14
7.2.2 Equivalent circuit – Effective internal resistance – DC method.....	14
7.2.3 Equipment	15
7.2.4 Measurement of open-circuit voltage U_{OC} (OCV) and closed circuit voltage U_{CC} (CCV).....	16
7.2.5 Calculation of the internal resistance R_i	17
7.2.6 Measurement of the capacity	17
7.2.7 Calculation of the internal resistance R_i during discharge in case of method A (optional)	19
7.3 Test methods for determining the resistance to leakage.....	19
7.3.1 Preconditioning and initial visual examination.....	19
7.3.2 High temperature and humidity test	20
7.3.3 Test by temperature cycles.....	20

8	Visual examination and acceptance conditions	20
8.1	Preconditioning	20
8.2	Magnification	21
8.3	Leakage levels and classification	21
8.4	Acceptance conditions	22
	Annex A (normative) Designation	23
	Bibliography	24
	Figure 1 – Dimensional drawing	8
	Figure 2 – Shape of battery	11
	Figure 3 – Shape requirement	14
	Figure 4 – Schematic voltage transient	15
	Figure 5 – Curve: $U = f(t)$	16
	Figure 6 – Circuitry principle	16
	Figure 7 – Circuitry principle for method A	18
	Figure 8 – Circuitry principle for method B	19
	Figure 9 – Test by temperature cycles	20
	Table 1 – Zinc systems L and S dimensions and size codes	9
	Table 2 – Lithium systems B and C dimensions and size codes	10
	Table 3 – Values of I_1	11
	Table 4 – Applied force F by battery dimensions	12
	Table 5 – Standardised electrochemical systems	13
	Table 6 – Test method for U_{CC} (CCV) measurement	17
	Table 7 – Test method A for U_{CC} (CCV) measurement	18
	Table 8 – Storage conditions for the recommended test	20
	Table 9 – Storage conditions for optional test	20
	Table 10 – Leakage levels and classification	21