

ISO 17411:2022-12 (E)

Optics and photonics - Optical materials and components - Test method for homogeneity of optical glasses by laser interferometry

| Contents | | Page |
|-----------------------|--|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Principle | 2 |
| 5 | Measuring apparatus | 2 |
| 5.1 | General | 2 |
| 5.2 | Laser interferometer | 3 |
| 5.3 | Interferogram analysis device | 3 |
| 5.4 | Thermostatic chamber | 3 |
| 5.5 | Vibration isolation device | 3 |
| 5.6 | Biaxial adjustment platform | 3 |
| 6 | Preparation of test part | 4 |
| 6.1 | General | 4 |
| 6.2 | Transmission method | 4 |
| 6.3 | PHom method | 4 |
| 6.4 | Oil-on plate method | 4 |
| 6.5 | FT-PSI and SCI method | 4 |
| 7 | Operation | 4 |
| 8 | Measurement | 5 |
| 8.1 | General | 5 |
| 8.2 | Transmission method | 5 |
| 8.3 | PHom method | 5 |
| 8.4 | Oil-on plate method | 6 |
| 8.5 | FT-PSI method and SCI method | 6 |
| 9 | Calculation | 6 |
| 10 | Test report | 7 |
| 10.1 | Requirements | 7 |
| 10.2 | Optional | 7 |
| Annex A (informative) | Laser interferometer | 8 |
| Annex B (informative) | Temperature stability for homogeneity measurements | 11 |
| Annex C (normative) | Measurement using oil-on plate method | 14 |
| Annex D (informative) | Flatness of the test part | 19 |
| Annex E (informative) | Method for obtaining WPV | 20 |

| | |
|--|-----------|
| Annex F (informative) Measurement using PHom (Polished test part Homogeneity) method | 22 |
| Annex G (normative) Method that can measure the linear change among the refractive index variations | 24 |
| Bibliography | 27 |