

ISO 16436-1:2026-08 (E)

Implants for surgery - Wear of total shoulder-joint prostheses - Part 1: Methodology for simulator wear testing of anatomic total shoulder-joint prostheses

Contents	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle	6
4.1 Reference position	6
4.2 Physiological motion simulated	8
4.3 Component alignment in the knee simulator	8
5 Test specimens, soak control specimen, sample size and lubricant	9
5.1 Test specimens	9
5.1.1 General	9
5.1.2 Assembly of components and interlocks	9
5.1.3 Permitted component adaptations	10
5.2 Soak control specimen	10
5.3 Sample size	10
5.4 Lubricant (fluid test medium)	10
6 Apparatus	11
7 Procedure	14
8 Test report	16
9 Disposal of test specimens	17
Annex A (normative) Details of axial force target waveform for the test cycle described in Figure 7 a)	18
Annex B (normative) Details of shear force target waveform for the test cycle described in Figure 7 b)	21
Annex C (normative) Details of rotation around x target waveform for the test cycle described in Figure 7 c)	24
Annex D (normative) Details of rotation around z target waveform for the test cycle described in Figure 7 d)	27
Annex E (informative) Principles of the definition of the tolerance envelopes around each target waveform	30
Bibliography	31