DIN EN ISO 10328:2007-04 (E)

Prosthetics - Structural testing of lower-limb prostheses - Requirements and test methods (ISO 10328:2006)

Contents

Page

Foreword 8

Introduction 9

1 Scope 10

2 Normative references 11

3 Terms and definitions 11

4 Designations and symbols of test forces and moments 12

5 Strength and related performance requirements and conditions of use 12

6 Coordinate systems and test configurations 14
6.1 General 14
6.2 Axes of coordinate systems 14
6.3 Reference planes 14
6.3.1 General 14
6.3.2 Top reference plane, T 14
6.3.3 Knee reference plane, K 14
6.3.4 Ankle reference plane, A 14
6.3.5 Bottom reference plane, B 15
6.4 Reference points 17
6.5 Test force 17
6.6 Load line 17
6.7 Longitudinal axis of the foot and effective joint centres and centrelines 17
6.7.1 General 17
6.7.2 Longitudinal axis of the foot 17
6.7.3 Effective ankle-joint centre 17
6.7.4 Effective ankle-joint centreline 19
6.7.5 Effective knee-joint centreline 19
6.7.6 Effective knee-joint centre 20
6.8 Reference distances 20
6.8.1 Offsets 20
6.8.2 Combined offsets 20
6.8.3 Effective lever arms LA and LK 20
6.8.4 Distance LBT 20

7 Test loading conditions and test loading levels 20
7.1 Test loading conditions 20
7.1.1 General 20
7.1.2 Test loading conditions of principal structural tests 21
7.1.3 Test loading conditions of separate structural tests 21
7.2 Test loading levels 21

8 Values of test loads, dimensions and cycles 22

9 Compliance 30
9.1 General 30
9.2 Selection of tests required to claim compliance with this International Standard 30

9.3 Arrangements for tests on samples of prosthetic structures including ankle-foot devices or foot units, required to claim compliance with this International Standard 30
9.3.1 General 30
9.3.2 Particular arrangements concerning the ankle-foot device or foot unit 30
9.3.3 Particular arrangements and requirements concerning the part required to connect the ankle-foot device or foot unit to the remainder of the prosthetic structure 30
9.4 Number of tests and test samples required to claim compliance with this International Standard 31
9.5 Multiple use of test samples 31
9.5.1 General 31
9.5.2 Restriction 32
9.6 Testing at particular test loading levels not specified in this International Standard 32

10 Test samples 34
10.1 Selection of test samples 34
10.1.1 General 34
10.1.2 Selection of ankle-foot devices and foot units of appropriate size of foot 34
10.2 Types of test samples 35
10.2.1 Complete structure 35
10.2.2 Partial structure 37
10.2.3 Any other structure 37
10.3 Preparation of test samples 37
10.4 Identification of test samples 38
10.5 Alignment of test samples 39
10.5.1 Test samples for principal tests and separate tests on knee locks 39
10.5.2 Test samples for separate tests on ankle-foot devices and foot units 39
10.5.3 Test samples for separate static ultimate strength tests in maximum knee flexion for knee joints and associated parts 40
10.5.4 Test samples for separate tests on knee locks 40
10.6 Worst-case alignment position of test samples 41

11 Responsibility for test preparation 41

12 Test submission document 42
12.1 General requirements 42
12.2 Information required for test samples 43
12.2.1 All test samples 43
12.2.2 Test samples for tests on ankle-foot devices and foot units 43
12.2.3 Test samples for static ultimate strength tests in maximum knee flexion for knee joints and associated parts 43
12.3 Information required for tests 44
12.3.1 General 44
12.3.2 For all tests 44
12.3.3 For static tests in torsion and on ankle-foot devices and foot units 44
12.3.4 For static ultimate strength tests 44
12.3.5 For cyclic tests 44
12.3.6 For tests in torsion 44
12.3.7 For tests on ankle-foot devices and foot units 45

13 Equipment 45
13.1 General 45
13.2 Equipment for the principal tests specified in 16.2 and 16.3 45
13.2.1 End attachments 45
13.2.2 Jig (optional) 47
13.2.3 Test equipment 47
13.3 Equipment for the separate static test in torsion specified in 17.1 49
13.3.1 Test equipment 49
13.4 Equipment for the separate tests on ankle-foot devices and foot units specified in 17.2 ... 49
13.4.1 Test equipment 49
13.5 Equipment for the separate static ultimate strength test in maximum knee flexion for knee joints and associated parts specified in 17.3 53
13.5.1 Extension pieces 53

13.5.2 Test equipment to perform static compression loading - (Compression testing machine or other equipment) 53
13.6 Equipment for the separate tests on knee locks specified in 17.4 53
13.6.1 End attachments 53
13.6.2 Jig (optional) 53
13.6.3 Test equipment 53

14 Accuracy 54
14.1 General 54
14.2 Accuracy of equipment 54
14.3 Accuracy of procedure 54

15 Test principles 55
15.1 General 55
15.2 Static test procedure 55
15.3 Cyclic test procedure 55

16 Test procedures - Principal structural tests 55
16.1 Test loading requirements 55
16.1.1 Preparation for test loading 55
16.1.2 Application of test loading 55
16.2 Principal static test procedure 57
16.2.1 Principal static proof test 57
16.2.2 Principal static ultimate strength test 62
16.3 Principal cyclic test procedure 66
16.3.1 General requirements 66
16.3.2 Test method 66
16.3.3 Performance requirements 70
16.3.4 Compliance conditions 70

17 Test procedures - Separate structural tests 74
17.1 Separate static test in torsion 74
17.1.1 General 74
17.1.2 Purpose of test 74
17.1.3 Test method 74
17.1.4 Performance requirements 76
17.1.5 Compliance conditions 76
17.2 Separate tests on ankle-foot devices and foot units 78
17.2.1 General 78
17.2.2 Purpose of tests 78
17.2.3 Separate static proof test for ankle-foot devices and foot units 78
17.2.4 Separate static ultimate strength test for ankle-foot devices and foot units 82
17.2.5 Separate cyclic test for ankle-foot devices and foot units 87
17.3 Separate static ultimate strength test in maximum knee flexion for knee joints and associated parts 92
17.3.1 General 92
17.3.2 Purpose of test 92
17.3.3 Applicability of the test to specific test samples 92
17.3.4 Test method 93
17.3.5 Performance requirement 93
17.3.6 Compliance conditions 94
17.4 Separate tests on knee locks 95
17.4.1 General 95
17.4.2 Purpose of tests 95
17.4.3 Separate static proof test for knee locks 95
17.4.4 Separate static ultimate strength test for knee locks 99
17.4.5 Separate cyclic test for knee locks 101

18 Test laboratory/facility log 110
18.1 General requirements 110
18.2 Specific requirements 110

19 Test report ... 110
19.1 General requirements ... 110
19.2 Specific requirements ... 111
19.3 Options ... 111

20 Classification and designation ... 111
20.1 General ... 111
20.2 Examples of classification and designation ... 111

21 Labelling ... 112
21.1 General ... 112
21.2 Use of mark "*)" and warning symbol ... 113
21.3 Examples of label layout ... 113
21.4 Label placement ... 113

Annex A (informative) Description of internal loads and their effects ... 115

Annex B (informative) Reference data for the specification of test loading conditions and test loading levels of principal cyclic tests ... 119

Annex C (informative) Guidance on the application of an alternative static ultimate strength test ... 123

Annex D (informative) Guidance on the application of an additional test loading level P6 ... 124

Annex E (informative) Summary of the records to be entered in the test laboratory/facility log ... 127

Annex F (informative) Background information on the loading profiles generated by test equipment according to 13.4.1.2 for separate cyclic tests for ankle-foot devices and foot units according to 17.2.5.1 ... 142

Annex G (informative) Reference to the essential principles of safety and performance of medical devices according to ISO/TR 16142 ... 144

Bibliography ... 145

Annex ZA (informative) Clauses of this European Standard addressing essential requirements or other provisions of EU Directives ... 146

Figure 1 -- Coordinate systems for right and left-sided application ... 15

Figure 2 -- Coordinate systems according to Figure 1 with reference planes ... 15

Figure 3 -- Specific configuration with uB = 0, showing coordinate systems with reference planes (see Figures 1 and 2), reference lines, reference points and test force, F, for right and left- sided application ... 16

Figure 4 -- Determination of longitudinal axis of foot (see 6.7.2), effective ankle-joint centre (see 6.7.3) and effective ankle-joint centreline (see 6.7.4) for test loading conditions I and II and of combined bottom offset SB (see 6.8.2) for test loading condition II [see 7.1.2 b)] ... 18

Figure 5 -- Position of effective knee-joint centreline for prosthetic knee units of different types ... 19

Figure 6 -- Application of a specific test configuration with uB = 0 to a left-sided sample specified in 10.2.1 ... 36

Figure 7 -- Position of foot in test equipment (see 10.5.2, 13.4 and 17.2) ... 39

Figure 8 -- Test configuration for the separate static ultimate strength test in maximum knee flexion on knee joints and associated parts (see 10.5.3.1, 13.5 and 17.3.4) ... 40

Figure 9 -- Load cycle parameters for the principal cyclic test ... 48

Figure 10 -- Load cycle parameters for the separate cyclic test for ankle-foot devices and foot units 52

Figure 11 -- Illustration of test loading principle applied to a knee unit with attachments, aligned to simulate a left-sided test sample (see 16.1.1) 56

Figure 12 -- Method of calculating offsets at any height u = ux (see 16.1.1) 57

Figure 13 -- Flowchart for the principal static proof test, specified in 16.2.1.1 61

Figure 14 -- Flowchart for the principal static ultimate strength test, specified in 16.2.2.1 65

Figure 15 -- Flowchart for the principal cyclic test, specified in 16.3.2 Continued on Figures 16 and 17 71

Figure 16 -- Flowchart for the principal cyclic test, specified in 16.3.2 Continued from Figure 15 and continued on Figure 17 72

Figure 17 -- Flowchart for the principal cyclic test, specified in 16.3.2 Continued from Figure 16 73

Figure 18 -- Flowchart for the separate static test in torsion, specified in 17.1.3 77

Figure 19 -- Flowchart for the separate static proof test for ankle-foot devices and foot units, specified in 17.2.3.1 81

Figure 20 -- Flowchart for the separate static ultimate strength test for ankle-foot devices and foot units, specified in 17.2.4.1 86

Figure 21 -- Flowchart for the separate cyclic test for ankle-foot devices and foot units, specified in 17.2.5.1 Continued on Figure 22 90

Figure 22 -- Flowchart for the separate cyclic test for ankle-foot devices and foot units, specified in 17.2.5.1 Continued from Figure 21 91

Figure 23 -- Flowchart for the separate static ultimate strength test in maximum knee flexion for knee joints and associated parts, specified in 17.3.4 94

Figure 24 -- Flowchart for the separate static proof test for knee locks, specified in 17.4.3.1 98

Figure 25 -- Flowchart for the separate static ultimate strength test for knee locks, specified in 17.4.4.1 101

Figure 26 -- Flowchart for the separate cyclic test for knee locks, specified in 17.4.5.1 Continued on Figures 27 and 28 107

Figure 27 -- Flowchart for the separate cyclic test for knee locks, specified in 17.4.5.1 Continued from Figure 26 and continued on Figure 28 108

Figure 28 -- Flowchart for the separate cyclic test for knee locks, specified in 17.4.5.1 Continued from Figure 27 109

Figure 29 -- General concept for the label layout 112

Figure 30 -- Models for the label layout 114

Annex A (informative) Description of internal loads and their effects 115

Figure A.1 -- Test loading condition I [see 7.1.2 a)] 117

Figure A.2 -- Test loading condition II [see 7.1.2 b)] 118

Table 1 -- Designations and symbols of test forces and moments 12

Table 2 -- Categories of strength addressed in this International Standard, together with the related performance requirements and test methods for their verification 13

Table 3 -- Test loads and relevant references 23

Table 4 -- Test forces of the proof test of end attachments for test loading levels P5, P4 and P3 (see 13.2.1.2) 24

Table 5 -- Total length and segmental lengths of different types of test samples for principal tests and separate tests on knee locks, for all test loading conditions and test loading levels (see also 10.2, 10.3, 16.2, 16.3, 17.4 and Figure 2) 24

Table 6 -- Values of offsets for all principal tests (see 16.2 and 16.3) 25

Table 7 -- Values of combined offsets related to the values of offsets listed in Table 6 (see 10.1.2 and 13.2.1.2.3) 25

Table 8 -- Test forces of all principal tests and prescribed number of cycles of the cyclic test, for test loading levels P5, P4 and P3 (see 16.2 and 16.3) 26

Table 9 -- Twisting moments of the separate static test in torsion (see 17.1) 27

Table 10 -- Angles of directions of loading of all separate tests on ankle-foot devices and foot units, for test loading levels P5, P4 and P3 (see 17.2 and Figure 7) 27

Table 11 -- Test forces of all separate tests on ankle-foot devices and foot units and prescribed number of cycles of the cyclic test, for test loading levels P5, P4 and P3 (see 17.2) 28

Table 12 -- Loading parameters of the separate static ultimate strength test in maximum knee flexion for knee joints and associated parts (see 17.3 and Figure 8) 28

Table 13 -- Offsets of all separate tests on knee locks, for test loading levels P5, P4 and P3 (see 17.4) 29

Table 14 -- Test forces of all separate tests on knee locks and prescribed number of cycles of the cyclic test, for test loading levels P5, P4 and P3 (see 17.4) 29

Table 15 -- Tests required to claim compliance with this International Standard for prosthetic structures representing complete assemblies, partial assemblies or individual components 32

Table 16 -- Number of tests and test samples required to claim compliance with this International Standard 33

Table 17 -- Option for end attachments of specific design 46

Table A.1 -- Positive internal forces and moments with descriptions of their effects 116

Table B.1 -- Values of ankle and knee moments related to test force F = Fcr for different test loading conditions and test loading levels of principal cyclic tests 120

Table B.2 -- Calculated values of axial force and twisting moment related to test force F = Fcr for different test loading conditions and test loading levels of principal cyclic tests 120

Table B.3 -- Values of ankle and knee moments related to test force F = Fcmax for different test loading conditions and test loading levels of principal cyclic tests 121

Table B.4 -- Calculated values of axial force and twisting moment related to test force F = Fcmax for different test loading conditions and test loading levels of principal cyclic tests 121

Table D.1 -- Test forces of the proof test of end attachments for test loading level P6 (see 13.2.1.2) 125

Table D.2 -- Test forces of all principal tests and prescribed number of cycles of the cyclic test, for test loading level P6 (see 16.2 and 16.3) 125

Table D.3 -- Test forces of all separate tests on ankle-foot devices and foot units and prescribed number of cycles of the cyclic test, for test loading level P6 (see 17.2) 126

Table G.1 -- Correspondence between this International Standard and the essential principles of ISO/TR 16142 144

Table ZA.1 -- Correspondence between this European Standard and EU Directives 146