

DIN EN ISO 10328:2007-04 (E)

Prosthetics - Structural testing of lower-limb prostheses - Requirements and test methods (ISO 10328:2006)

Contents		Page
Foreword		8
Introduction		9
1	Scope	10
2	Normative references	11
3	Terms and definitions	11
4	Designations and symbols of test forces and moments	12
5	Strength and related performance requirements and conditions of use	12
6	Coordinate systems and test configurations	14
6.1	General	14
6.2	Axes of coordinate systems	14
6.3	Reference planes	14
6.3.1	General	14
6.3.2	Top reference plane, T	14
6.3.3	Knee reference plane, K	14
6.3.4	Ankle reference plane, A	14
6.3.5	Bottom reference plane, B	15
6.4	Reference points	17
6.5	Test force	17
6.6	Load line	17
6.7	Longitudinal axis of the foot and effective joint centres and centrelines	17
6.7.1	General	17
6.7.2	Longitudinal axis of the foot	17
6.7.3	Effective ankle-joint centre	17
6.7.4	Effective ankle-joint centreline	19
6.7.5	Effective knee-joint centreline	19
6.7.6	Effective knee-joint centre	20
6.8	Reference distances	20
6.8.1	Offsets	20
6.8.2	Combined offsets	20
6.8.3	Effective lever arms LA and LK	20
6.8.4	Distance LBT	20
7	Test loading conditions and test loading levels	20
7.1	Test loading conditions	20
7.1.1	General	20
7.1.2	Test loading conditions of principal structural tests	21
7.1.3	Test loading conditions of separate structural tests	21
7.2	Test loading levels	21
8	Values of test loads, dimensions and cycles	22
9	Compliance	30
9.1	General	30
9.2	Selection of tests required to claim compliance with this International Standard	30

9.3	Arrangements for tests on samples of prosthetic structures including ankle-foot devices or foot units, required to claim compliance with this International Standard	30
9.3.1	General	30
9.3.2	Particular arrangements concerning the ankle-foot device or foot unit	30
9.3.3	Particular arrangements and requirements concerning the part required to connect the ankle-foot device or foot unit to the remainder of the prosthetic structure	30
9.4	Number of tests and test samples required to claim compliance with this International Standard	31
9.5	Multiple use of test samples	31
9.5.1	General	31
9.5.2	Restriction	32
9.6	Testing at particular test loading levels not specified in this International Standard	32
10	Test samples	34
10.1	Selection of test samples	34
10.1.1	General	34
10.1.2	Selection of ankle-foot devices and foot units of appropriate size of foot	34
10.2	Types of test samples	35
10.2.1	Complete structure	35
10.2.2	Partial structure	37
10.2.3	Any other structure	37
10.3	Preparation of test samples	37
10.4	Identification of test samples	38
10.5	Alignment of test samples	39
10.5.1	Test samples for principal tests and separate tests on knee locks	39
10.5.2	Test samples for separate tests on ankle-foot devices and foot units	39
10.5.3	Test samples for separate static ultimate strength tests in maximum knee flexion for knee joints and associated parts	40
10.5.4	Test samples for separate tests on knee locks	40
10.6	Worst-case alignment position of test samples	41
11	Responsibility for test preparation	41
12	Test submission document	42
12.1	General requirements	42
12.2	Information required for test samples	43
12.2.1	All test samples	43
12.2.2	Test samples for tests on ankle-foot devices and foot units	43
12.2.3	Test samples for static ultimate strength tests in maximum knee flexion for knee joints and associated parts	43
12.3	Information required for tests	44
12.3.1	General	44
12.3.2	For all tests	44
12.3.3	For static tests in torsion and on ankle-foot devices and foot units	44
12.3.4	For static ultimate strength tests	44
12.3.5	For cyclic tests	44
12.3.6	For tests in torsion	44
12.3.7	For tests on ankle-foot devices and foot units	45
13	Equipment	45
13.1	General	45
13.2	Equipment for the principal tests specified in 16.2 and 16.3	45
13.2.1	End attachments	45
13.2.2	Jig (optional)	47
13.2.3	Test equipment	47
13.3	Equipment for the separate static test in torsion specified in 17.1	49
13.3.1	Test equipment	49
13.4	Equipment for the separate tests on ankle-foot devices and foot units specified in 17.2 ...	49
13.4.1	Test equipment	49
13.5	Equipment for the separate static ultimate strength test in maximum knee flexion for knee joints and associated parts specified in 17.3	53
13.5.1	Extension pieces	53

13.5.2	Test equipment to perform static compression loading - (Compression testing machine or other equipment)	53
13.6	Equipment for the separate tests on knee locks specified in 17.4	53
13.6.1	End attachments	53
13.6.2	Jig (optional)	53
13.6.3	Test equipment	53
14	Accuracy	54
14.1	General	54
14.2	Accuracy of equipment	54
14.3	Accuracy of procedure	54
15	Test principles	55
15.1	General	55
15.2	Static test procedure	55
15.3	Cyclic test procedure	55
16	Test procedures - Principal structural tests	55
16.1	Test loading requirements	55
16.1.1	Preparation for test loading	55
16.1.2	Application of test loading	55
16.2	Principal static test procedure	57
16.2.1	Principal static proof test	57
16.2.2	Principal static ultimate strength test	62
16.3	Principal cyclic test procedure	66
16.3.1	General requirements	66
16.3.2	Test method	66
16.3.3	Performance requirements	70
16.3.4	Compliance conditions	70
17	Test procedures - Separate structural tests	74
17.1	Separate static test in torsion	74
17.1.1	General	74
17.1.2	Purpose of test	74
17.1.3	Test method	74
17.1.4	Performance requirements	76
17.1.5	Compliance conditions	76
17.2	Separate tests on ankle-foot devices and foot units	78
17.2.1	General	78
17.2.2	Purpose of tests	78
17.2.3	Separate static proof test for ankle-foot devices and foot units	78
17.2.4	Separate static ultimate strength test for ankle-foot devices and foot units	82
17.2.5	Separate cyclic test for ankle-foot devices and foot units	87
17.3	Separate static ultimate strength test in maximum knee flexion for knee joints and associated parts	92
17.3.1	General	92
17.3.2	Purpose of test	92
17.3.3	Applicability of the test to specific test samples	92
17.3.4	Test method	93
17.3.5	Performance requirement	93
17.3.6	Compliance conditions	94
17.4	Separate tests on knee locks	95
17.4.1	General	95
17.4.2	Purpose of tests	95
17.4.3	Separate static proof test for knee locks	95
17.4.4	Separate static ultimate strength test for knee locks	99
17.4.5	Separate cyclic test for knee locks	101
18	Test laboratory/facility log	110
18.1	General requirements	110
18.2	Specific requirements	110

19	Test report	110
19.1	General requirements	110
19.2	Specific requirements	111
19.3	Options	111
20	Classification and designation	111
20.1	General	111
20.2	Examples of classification and designation	111
21	Labelling	112
21.1	General	112
21.2	Use of mark "*" and warning symbol	113
21.3	Examples of label layout	113
21.4	Label placement	113
Annex A (informative) Description of internal loads and their effects		115
Annex B (informative) Reference data for the specification of test loading conditions and test loading levels of principal cyclic tests		119
Annex C (informative) Guidance on the application of an alternative static ultimate strength test ..		123
Annex D (informative) Guidance on the application of an additional test loading level P6		124
Annex E (informative) Summary of the records to be entered in the test laboratory/facility log		127
Annex F (informative) Background information on the loading profiles generated by test equipment according to 13.4.1.2 for separate cyclic tests for ankle-foot devices and foot units according to 17.2.5.1		142
Annex G (informative) Reference to the essential principles of safety and performance of medical devices according to ISO/TR 16142		144
Bibliography		145
Annex ZA (informative) Clauses of this European Standard addressing essential requirements or other provisions of EU Directives		146
Figure 1 -- Coordinate systems for right and left-sided application		15
Figure 2 -- Coordinate systems according to Figure 1 with reference planes		15
Figure 3 -- Specific configuration with $u_B = 0$, showing coordinate systems with reference planes (see Figures 1 and 2), reference lines, reference points and test force, F, for right and left-sided application		16
Figure 4 -- Determination of longitudinal axis of foot (see 6.7.2), effective ankle-joint centre (see 6.7.3) and effective ankle-joint centreline (see 6.7.4) for test loading conditions I and II and of combined bottom offset SB (see 6.8.2) for test loading condition II [see 7.1.2 b)] ...		18
Figure 5 -- Position of effective knee-joint centreline for prosthetic knee units of different types		19
Figure 6 -- Application of a specific test configuration with $u_B = 0$ to a left-sided sample specified in 10.2.1		36
Figure 7 -- Position of foot in test equipment (see 10.5.2, 13.4 and 17.2)		39
Figure 8 -- Test configuration for the separate static ultimate strength test in maximum knee flexion on knee joints and associated parts (see 10.5.3.1, 13.5 and 17.3.4)		40
Figure 9 -- Load cycle parameters for the principal cyclic test		48

Figure 10 -- Load cycle parameters for the separate cyclic test for ankle-foot devices and foot units	52
Figure 11 -- Illustration of test loading principle applied to a knee unit with attachments, aligned to simulate a left-sided test sample (see 16.1.1)	56
Figure 12 -- Method of calculating offsets at any height $u = u_x$ (see 16.1.1)	57
Figure 13 -- Flowchart for the principal static proof test, specified in 16.2.1.1	61
Figure 14 -- Flowchart for the principal static ultimate strength test, specified in 16.2.2.1	65
Figure 15 -- Flowchart for the principal cyclic test, specified in 16.3.2 Continued on Figures 16 and 17	71
Figure 16 -- Flowchart for the principal cyclic test, specified in 16.3.2 Continued from Figure 15 and continued on Figure 17	72
Figure 17 -- Flowchart for the principal cyclic test, specified in 16.3.2 Continued from Figure 16	73
Figure 18 -- Flowchart for the separate static test in torsion, specified in 17.1.3	77
Figure 19 -- Flowchart for the separate static proof test for ankle-foot devices and foot units, specified in 17.2.3.1	81
Figure 20 -- Flowchart for the separate static ultimate strength test for ankle-foot devices and foot units, specified in 17.2.4.1	86
Figure 21 -- Flowchart for the separate cyclic test for ankle-foot devices and foot units, specified in 17.2.5.1 Continued on Figure 22	90
Figure 22 -- Flowchart for the separate cyclic test for ankle-foot devices and foot units, specified in 17.2.5.1 Continued from Figure 21	91
Figure 23 -- Flowchart for the separate static ultimate strength test in maximum knee flexion for knee joints and associated parts, specified in 17.3.4	94
Figure 24 -- Flowchart for the separate static proof test for knee locks, specified in 17.4.3.1	98
Figure 25 -- Flowchart for the separate static ultimate strength test for knee locks, specified in 17.4.4.1	101
Figure 26 -- Flowchart for the separate cyclic test for knee locks, specified in 17.4.5.1 Continued on Figures 27 and 28	107
Figure 27 -- Flowchart for the separate cyclic test for knee locks, specified in 17.4.5.1 Continued from Figure 26 and continued on Figure 28	108
Figure 28 -- Flowchart for the separate cyclic test for knee locks, specified in 17.4.5.1 Continued from Figure 27	109
Figure 29 -- General concept for the label layout	112
Figure 30 -- Models for the label layout	114
Annex A (informative) Description of internal loads and their effects	115
Figure A.1 -- Test loading condition I [see 7.1.2 a)]	117
Figure A.2 -- Test loading condition II [see 7.1.2 b)]	118
Table 1 -- Designations and symbols of test forces and moments	12

Table 2 -- Categories of strength addressed in this International Standard, together with the related performance requirements and test methods for their verification	13
Table 3 -- Test loads and relevant references	23
Table 4 -- Test forces of the proof test of end attachments for test loading levels P5, P4 and P3 (see 13.2.1.2)	24
Table 5 -- Total length and segmental lengths of different types of test samples for principal tests and separate tests on knee locks, for all test loading conditions and test loading levels (see also 10.2, 10.3, 16.2, 16.3, 17.4 and Figure 2)	24
Table 6 -- Values of offsets for all principal tests (see 16.2 and 16.3)	25
Table 7 -- Values of combined offsets related to the values of offsets listed in Table 6 (see 10.1.2 and 13.2.1.2.3)	25
Table 8 -- Test forces of all principal tests and prescribed number of cycles of the cyclic test, for test loading levels P5, P4 and P3 (see 16.2 and 16.3)	26
Table 9 -- Twisting moments of the separate static test in torsion (see 17.1)	27
Table 10 -- Angles of directions of loading of all separate tests on ankle-foot devices and foot units, for test loading levels P5, P4 and P3 (see 17.2 and Figure 7)	27
Table 11 -- Test forces of all separate tests on ankle-foot devices and foot units and prescribed number of cycles of the cyclic test, for test loading levels P5, P4 and P3 (see 17.2)	28
Table 12 -- Loading parameters of the separate static ultimate strength test in maximum knee flexion for knee joints and associated parts (see 17.3 and Figure 8)	28
Table 13 -- Offsets of all separate tests on knee locks, for test loading levels P5, P4 and P3 (see 17.4)	29
Table 14 -- Test forces of all separate tests on knee locks and prescribed number of cycles of the cyclic test, for test loading levels P5, P4 and P3 (see 17.4)	29
Table 15 -- Tests required to claim compliance with this International Standard for prosthetic structures representing complete assemblies, partial assemblies or individual components	32
Table 16 -- Number of tests and test samples required to claim compliance with this International Standard	33
Table 17 -- Option for end attachments of specific design	46
Table A.1 -- Positive internal forces and moments with descriptions of their effects	116
Table B.1 -- Values of ankle and knee moments related to test force $F = F_{cr}$ for different test loading conditions and test loading levels of principal cyclic tests	120
Table B.2 -- Calculated values of axial force and twisting moment related to test force $F = F_{cr}$ for different test loading conditions and test loading levels of principal cyclic tests	120
Table B.3 -- Values of ankle and knee moments related to test force $F = F_{cmax}$ for different test loading conditions and test loading levels of principal cyclic tests	121
Table B.4 -- Calculated values of axial force and twisting moment related to test force $F = F_{cmax}$ for different test loading conditions and test loading levels of principal cyclic tests	121
Table D.1 -- Test forces of the proof test of end attachments for test loading level P6 (see 13.2.1.2)	125

Table D.2 -- Test forces of all principal tests and prescribed number of cycles of the cyclic test, for test loading level P6 (see 16.2 and 16.3) 125

Table D.3 -- Test forces of all separate tests on ankle-foot devices and foot units and prescribed number of cycles of the cyclic test, for test loading level P6 (see 17.2) 126

Table G.1 -- Correspondence between this International Standard and the essential principles of ISO/TR 16142 144

Table ZA.1 -- Correspondence between this European Standard and EU Directives 146