

ISO 10328:2006-10 (E)

Prosthetics - Structural testing of lower-limb prostheses - Requirements and test methods

Contents		Page
Foreword		ix
Introduction		x
1	Scope	1
2	Normative references	2
3	Terms and definitions	2
4	Designations and symbols of test forces and moments	3
5	Strength and related performance requirements and conditions of use	3
6	Coordinate systems and test configurations	5
6.1	General	5
6.2	Axes of coordinate systems	5
6.3	Reference planes	5
6.3.1	General	5
6.3.2	Top reference plane, T	5
6.3.3	Knee reference plane, K	5
6.3.4	Ankle reference plane, A	5
6.3.5	Bottom reference plane, B	6
6.4	Reference points	8
6.5	Test force	8
6.6	Load line	8
6.7	Longitudinal axis of the foot and effective joint centres and centrelines	8
6.7.1	General	8
6.7.2	Longitudinal axis of the foot	8
6.7.3	Effective ankle-joint centre	8
6.7.4	Effective ankle-joint centreline	10
6.7.5	Effective knee-joint centreline	10
6.7.6	Effective knee-joint centre	11
6.8	Reference distances	11
6.8.1	Offsets	11
6.8.2	Combined offsets	11
6.8.3	Effective lever arms LA and LK	11
6.8.4	Distance LBT	11
7	Test loading conditions and test loading levels	11
7.1	Test loading conditions	11
7.1.1	General	11
7.1.2	Test loading conditions of principal structural tests	12
7.1.3	Test loading conditions of separate structural tests	12
7.2	Test loading levels	12
8	Values of test loads, dimensions and cycles	13
9	Compliance	21
9.1	General	21
9.2	Selection of tests required to claim compliance with this International Standard	21

9.3	Arrangements for tests on samples of prosthetic structures including ankle-foot devices or foot units, required to claim compliance with this International Standard	21
9.3.1	General	21
9.3.2	Particular arrangements concerning the ankle-foot device or foot unit	21
9.3.3	Particular arrangements and requirements concerning the part required to connect the ankle-foot device or foot unit to the remainder of the prosthetic structure	21
9.4	Number of tests and test samples required to claim compliance with this International Standard	22
9.5	Multiple use of test samples	22
9.5.1	General	22
9.5.2	Restriction	23
9.6	Testing at particular test loading levels not specified in this International Standard	23
10	Test samples	25
10.1	Selection of test samples	25
10.1.1	General	25
10.1.2	Selection of ankle-foot devices and foot units of appropriate size of foot	25
10.2	Types of test samples	26
10.2.1	Complete structure	26
10.2.2	Partial structure	28
10.2.3	Any other structure	28
10.3	Preparation of test samples	28
10.4	Identification of test samples	29
10.5	Alignment of test samples	30
10.5.1	Test samples for principal tests and separate tests on knee locks	30
10.5.2	Test samples for separate tests on ankle-foot devices and foot units	30
10.5.3	Test samples for separate static ultimate strength tests in maximum knee flexion for knee joints and associated parts	31
10.5.4	Test samples for separate tests on knee locks	31
10.6	Worst-case alignment position of test samples	32
11	Responsibility for test preparation	32
12	Test submission document	33
12.1	General requirements	33
12.2	Information required for test samples	34
12.2.1	All test samples	34
12.2.2	Test samples for tests on ankle-foot devices and foot units	34
12.2.3	Test samples for static ultimate strength tests in maximum knee flexion for knee joints and associated parts	34
12.3	Information required for tests	35
12.3.1	General	35
12.3.2	For all tests	35
12.3.3	For static tests in torsion and on ankle-foot devices and foot units	35
12.3.4	For static ultimate strength tests	35
12.3.5	For cyclic tests	35
12.3.6	For tests in torsion	35
12.3.7	For tests on ankle-foot devices and foot units	36
13	Equipment	36
13.1	General	36
13.2	Equipment for the principal tests specified in 16.2 and 16.3	36
13.2.1	End attachments	36
13.2.2	Jig (optional)	38
13.2.3	Test equipment	38
13.3	Equipment for the separate static test in torsion specified in 17.1	40
13.3.1	Test equipment	40
13.4	Equipment for the separate tests on ankle-foot devices and foot units specified in 17.2 ...	40
13.4.1	Test equipment	40
13.5	Equipment for the separate static ultimate strength test in maximum knee flexion for knee joints and associated parts specified in 17.3	44
13.5.1	Extension pieces	44

13.5.2	Test equipment to perform static compression loading - (Compression testing machine or other equipment)	44
13.6	Equipment for the separate tests on knee locks specified in 17.4	44
13.6.1	End attachments	44
13.6.2	Jig (optional)	44
13.6.3	Test equipment	44
14	Accuracy	45
14.1	General	45
14.2	Accuracy of equipment	45
14.3	Accuracy of procedure	45
15	Test principles	46
15.1	General	46
15.2	Static test procedure	46
15.3	Cyclic test procedure	46
16	Test procedures - Principal structural tests	46
16.1	Test loading requirements	46
16.1.1	Preparation for test loading	46
16.1.2	Application of test loading	46
16.2	Principal static test procedure	48
16.2.1	Principal static proof test	48
16.2.2	Principal static ultimate strength test	53
16.3	Principal cyclic test procedure	57
16.3.1	General requirements	57
16.3.2	Test method	57
16.3.3	Performance requirements	61
16.3.4	Compliance conditions	61
17	Test procedures - Separate structural tests	65
17.1	Separate static test in torsion	65
17.1.1	General	65
17.1.2	Purpose of test	65
17.1.3	Test method	65
17.1.4	Performance requirements	67
17.1.5	Compliance conditions	67
17.2	Separate tests on ankle-foot devices and foot units	69
17.2.1	General	69
17.2.2	Purpose of tests	69
17.2.3	Separate static proof test for ankle-foot devices and foot units	69
17.2.4	Separate static ultimate strength test for ankle-foot devices and foot units	73
17.2.5	Separate cyclic test for ankle-foot devices and foot units	78
17.3	Separate static ultimate strength test in maximum knee flexion for knee joints and associated parts	83
17.3.1	General	83
17.3.2	Purpose of test	83
17.3.3	Applicability of the test to specific test samples	83
17.3.4	Test method	84
17.3.5	Performance requirement	84
17.3.6	Compliance conditions	85
17.4	Separate tests on knee locks	86
17.4.1	General	86
17.4.2	Purpose of tests	86
17.4.3	Separate static proof test for knee locks	86
17.4.4	Separate static ultimate strength test for knee locks	90
17.4.5	Separate cyclic test for knee locks	92
18	Test laboratory/facility log	101
18.1	General requirements	101
18.2	Specific requirements	101

19	Test report	101
19.1	General requirements	101
19.2	Specific requirements	102
19.3	Options	102
20	Classification and designation	102
20.1	General	102
20.2	Examples of classification and designation	102
21	Labelling	103
21.1	General	103
21.2	Use of mark "*" and warning symbol	104
21.3	Examples of label layout	104
21.4	Label placement	104
Annex A (informative) Description of internal loads and their effects		106
Annex B (informative) Reference data for the specification of test loading conditions and test loading levels of principal cyclic tests		110
Annex C (informative) Guidance on the application of an alternative static ultimate strength test ..		114
Annex D (informative) Guidance on the application of an additional test loading level P6		115
Annex E (informative) Summary of the records to be entered in the test laboratory/facility log		118
Annex F (informative) Background information on the loading profiles generated by test equipment according to 13.4.1.2 for separate cyclic tests for ankle-foot devices and foot units according to 17.2.5.1		133
Annex G (informative) Reference to the essential principles of safety and performance of medical devices according to ISO/TR 16142		135
Bibliography		136
Figure 1 -- Coordinate systems for right and left-sided application		6
Figure 2 -- Coordinate systems according to Figure 1 with reference planes		6
Figure 3 -- Specific configuration with $u_B = 0$, showing coordinate systems with reference planes (see Figures 1 and 2), reference lines, reference points and test force, F, for right and left-sided application		7
Figure 4 -- Determination of longitudinal axis of foot (see 6.7.2), effective ankle-joint centre (see 6.7.3) and effective ankle-joint centreline (see 6.7.4) for test loading conditions I and II and of combined bottom offset SB (see 6.8.2) for test loading condition II [see 7.1.2 b)]		9
Figure 5 -- Position of effective knee-joint centreline for prosthetic knee units of different types		10
Figure 6 -- Application of a specific test configuration with $u_B = 0$ to a left-sided sample specified in 10.2.1		27
Figure 7 -- Position of foot in test equipment (see 10.5.2, 13.4 and 17.2)		30
Figure 8 -- Test configuration for the separate static ultimate strength test in maximum knee flexion on knee joints and associated parts (see 10.5.3.1, 13.5 and 17.3.4)		31
Figure 9 -- Load cycle parameters for the principal cyclic test		39
Figure 10 -- Load cycle parameters for the separate cyclic test for ankle-foot devices and foot units		43

Figure 11 -- Illustration of test loading principle applied to a knee unit with attachments, aligned to simulate a left-sided test sample (see 16.1.1)	47
Figure 12 -- Method of calculating offsets at any height $u = u_x$ (see 16.1.1)	48
Figure 13 -- Flowchart for the principal static proof test, specified in 16.2.1.1	52
Figure 14 -- Flowchart for the principal static ultimate strength test, specified in 16.2.2.1	56
Figure 15 -- Flowchart for the principal cyclic test, specified in 16.3.2 Continued on Figures 16 and 17	62
Figure 16 -- Flowchart for the principal cyclic test, specified in 16.3.2 Continued from Figure 15 and continued on Figure 17	63
Figure 17 -- Flowchart for the principal cyclic test, specified in 16.3.2 Continued from Figure 16	64
Figure 18 -- Flowchart for the separate static test in torsion, specified in 17.1.3	68
Figure 19 -- Flowchart for the separate static proof test for ankle-foot devices and foot units, specified in 17.2.3.1	72
Figure 20 -- Flowchart for the separate static ultimate strength test for ankle-foot devices and foot units, specified in 17.2.4.1	77
Figure 21 -- Flowchart for the separate cyclic test for ankle-foot devices and foot units, specified in 17.2.5.1 Continued on Figure 22	81
Figure 22 -- Flowchart for the separate cyclic test for ankle-foot devices and foot units, specified in 17.2.5.1 Continued from Figure 21	82
Figure 23 -- Flowchart for the separate static ultimate strength test in maximum knee flexion for knee joints and associated parts, specified in 17.3.4	85
Figure 24 -- Flowchart for the separate static proof test for knee locks, specified in 17.4.3.1	89
Figure 25 -- Flowchart for the separate static ultimate strength test for knee locks, specified in 17.4.4.1	92
Figure 26 -- Flowchart for the separate cyclic test for knee locks, specified in 17.4.5.1 Continued on Figures 27 and 28	98
Figure 27 -- Flowchart for the separate cyclic test for knee locks, specified in 17.4.5.1 Continued from Figure 26 and continued on Figure 28	99
Figure 28 -- Flowchart for the separate cyclic test for knee locks, specified in 17.4.5.1 Continued from Figure 27	100
Figure 29 -- General concept for the label layout	103
Figure 30 -- Models for the label layout	105
Figure A.1 -- Test loading condition I [see 7.1.2 a)]	108
Figure A.2 -- Test loading condition II [see 7.1.2 b)]	109
Table 1 -- Designations and symbols of test forces and moments	3
Table 2 -- Categories of strength addressed in this International Standard, together with the related performance requirements and test methods for their verification	4
Table 3 -- Test loads and relevant references	14

Table 4 -- Test forces of the proof test of end attachments for test loading levels P5, P4 and P3 (see 13.2.1.2)	15
Table 5 -- Total length and segmental lengths of different types of test samples for principal tests and separate tests on knee locks, for all test loading conditions and test loading levels (see also 10.2, 10.3, 16.2, 16.3, 17.4 and Figure 2)	15
Table 6 -- Values of offsets for all principal tests (see 16.2 and 16.3)	16
Table 7 -- Values of combined offsets related to the values of offsets listed in Table 6 (see 10.1.2 and 13.2.1.2.3)	16
Table 8 -- Test forces of all principal tests and prescribed number of cycles of the cyclic test, for test loading levels P5, P4 and P3 (see 16.2 and 16.3)	17
Table 9 -- Twisting moments of the separate static test in torsion (see 17.1)	18
Table 10 -- Angles of directions of loading of all separate tests on ankle-foot devices and foot units, for test loading levels P5, P4 and P3 (see 17.2 and Figure 7)	18
Table 11 -- Test forces of all separate tests on ankle-foot devices and foot units and prescribed number of cycles of the cyclic test, for test loading levels P5, P4 and P3 (see 17.2)	19
Table 12 -- Loading parameters of the separate static ultimate strength test in maximum knee flexion for knee joints and associated parts (see 17.3 and Figure 8)	19
Table 13 -- Offsets of all separate tests on knee locks, for test loading levels P5, P4 and P3 (see 17.4)	20
Table 14 -- Test forces of all separate tests on knee locks and prescribed number of cycles of the cyclic test, for test loading levels P5, P4 and P3 (see 17.4)	20
Table 15 -- Tests required to claim compliance with this International Standard for prosthetic structures representing complete assemblies, partial assemblies or individual components	23
Table 16 -- Number of tests and test samples required to claim compliance with this International Standard	24
Table 17 -- Option for end attachments of specific design	37
Table A.1 -- Positive internal forces and moments with descriptions of their effects	107
Table B.1 -- Values of ankle and knee moments related to test force $F = F_{cr}$ for different test loading conditions and test loading levels of principal cyclic tests	111
Table B.2 -- Calculated values of axial force and twisting moment related to test force $F = F_{cr}$ for different test loading conditions and test loading levels of principal cyclic tests	111
Table B.3 -- Values of ankle and knee moments related to test force $F = F_{cmax}$ for different test loading conditions and test loading levels of principal cyclic tests	112
Table B.4 -- Calculated values of axial force and twisting moment related to test force $F = F_{cmax}$ for different test loading conditions and test loading levels of principal cyclic tests	112
Table D.1 -- Test forces of the proof test of end attachments for test loading level P6 (see 13.2.1.2)	116
Table D.2 -- Test forces of all principal tests and prescribed number of cycles of the cyclic test, for test loading level P6 (see 16.2 and 16.3)	116

Table D.3 -- Test forces of all separate tests on ankle-foot devices and foot units and prescribed number of cycles of the cyclic test, for test loading level P6 (see 17.2) 117

Table G.1 -- Correspondence between this International Standard and the essential principles of ISO/TR 16142 135