

# ISO 26142:2010-06 (E)

## Hydrogen detection apparatus - Stationary applications

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
Introduction .....		vi
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>General requirements .....</b>	<b>4</b>
<b>4.1</b>	<b>Construction .....</b>	<b>4</b>
<b>4.1.1</b>	<b>General .....</b>	<b>4</b>
<b>4.1.2</b>	<b>Enclosure .....</b>	<b>4</b>
<b>4.1.3</b>	<b>Measuring range .....</b>	<b>4</b>
<b>4.1.4</b>	<b>Alarm system .....</b>	<b>4</b>
<b>4.1.5</b>	<b>Indicators .....</b>	<b>5</b>
<b>4.1.6</b>	<b>Adjustments .....</b>	<b>5</b>
<b>4.1.7</b>	<b>Software-controlled hydrogen detection apparatus .....</b>	<b>6</b>
<b>4.1.8</b>	<b>Reliability .....</b>	<b>7</b>
<b>4.2</b>	<b>Labelling and marking .....</b>	<b>8</b>
<b>4.3</b>	<b>Instruction manual .....</b>	<b>8</b>
<b>4.4</b>	<b>Vibration .....</b>	<b>9</b>
<b>5</b>	<b>Performance requirements .....</b>	<b>9</b>
<b>6</b>	<b>Tests .....</b>	<b>9</b>
<b>6.1</b>	<b>General requirements for tests .....</b>	<b>9</b>
<b>6.1.1</b>	<b>Number of samples .....</b>	<b>9</b>
<b>6.1.2</b>	<b>Sequence of tests .....</b>	<b>9</b>
<b>6.1.3</b>	<b>Preparation of the hydrogen detection apparatus before testing .....</b>	<b>10</b>
<b>6.2</b>	<b>Test equipment .....</b>	<b>10</b>
<b>6.3</b>	<b>Normal test conditions .....</b>	<b>10</b>
<b>6.3.1</b>	<b>Temperature .....</b>	<b>10</b>
<b>6.3.2</b>	<b>Pressure .....</b>	<b>10</b>
<b>6.3.3</b>	<b>Humidity .....</b>	<b>10</b>
<b>6.3.4</b>	<b>Voltage .....</b>	<b>10</b>
<b>6.3.5</b>	<b>Orientation .....</b>	<b>10</b>
<b>6.4</b>	<b>Test methods .....</b>	<b>11</b>
<b>6.4.1</b>	<b>General .....</b>	<b>11</b>
<b>6.4.2</b>	<b>Standard response test .....</b>	<b>11</b>
<b>6.4.3</b>	<b>Measuring range and calibration .....</b>	<b>11</b>
<b>6.4.4</b>	<b>Stability .....</b>	<b>12</b>
<b>6.4.5</b>	<b>Alarm set point(s) .....</b>	<b>13</b>
<b>6.4.6</b>	<b>Temperature .....</b>	<b>13</b>
<b>6.4.7</b>	<b>Pressure .....</b>	<b>14</b>
<b>6.4.8</b>	<b>Humidity .....</b>	<b>14</b>
<b>6.4.9</b>	<b>Vibration .....</b>	<b>14</b>
<b>6.4.10</b>	<b>Orientation .....</b>	<b>15</b>
<b>6.4.11</b>	<b>Flow rate for aspirated apparatus .....</b>	<b>16</b>
<b>6.4.12</b>	<b>Air velocity .....</b>	<b>16</b>
<b>6.4.13</b>	<b>Time of response and time of recovery .....</b>	<b>17</b>

6.4.14	Selectivity .....	17
6.4.15	Poisoning .....	17
6.4.16	Operation above the measuring range .....	18
6.4.17	Power supply variations .....	18
6.4.18	Power supply interruptions, voltage transients and step changes of voltage .....	19
6.4.19	Warm-up time after restart .....	19
6.4.20	Electromagnetic immunity .....	19
6.4.21	Field calibration kit .....	20
Annex A (informative) Chamber test method .....		21
Annex B (informative) Flow-through test method .....		24
Bibliography .....		27