

DIN EN 15420:2011-03 (E)

Gas-fired central heating boilers - Type C boilers of nominal heat input exceeding 70 kW, but not exceeding 1 000 kW

| Contents | | Page |
|-----------------|--|-------------|
| Foreword | | 7 |
| 1 | Scope | 8 |
| 2 | Normative references | 8 |
| 3 | Terms and definitions | 10 |
| 3.1 | Combustible gases | 10 |
| 3.2 | Constituent parts of the boiler | 12 |
| 3.2.1 | Gas supply | 12 |
| 3.2.2 | Air supply and combustion products evacuation | 13 |
| 3.2.3 | Adjusting, control and safety devices | 15 |
| 3.3 | Operation of the boiler | 17 |
| 3.3.1 | Gas rates | 17 |
| 3.3.2 | Outputs | 18 |
| 3.3.3 | Efficiency | 18 |
| 3.3.4 | Gas combustion | 19 |
| 3.3.5 | Times | 19 |
| 3.3.6 | spark restoration | 20 |
| 3.3.7 | recycling | 20 |
| 3.3.8 | controlled shutdown | 20 |
| 3.3.9 | safety shutdown | 20 |
| 3.3.10 | Locking out | 20 |
| 3.4 | Auxiliary energy | 21 |
| 3.4.1 | electric auxiliary energy | 21 |
| 3.5 | Country of destination | 21 |
| 3.5.1 | direct country of destination | 21 |
| 3.5.2 | indirect country of destination | 21 |
| 4 | Classification of boilers | 21 |
| 4.1 | Gases and categories | 21 |
| 4.2 | Mode of air supply and evacuation of the combustion products | 22 |
| 4.2.1 | Type C Boilers | 22 |
| 4.2.2 | Type of installation of the boiler | 22 |
| 4.2.3 | Presence and position of a fan | 23 |
| 4.3 | Classification according to operating conditions) | 23 |
| 4.3.1 | Standard boiler | 23 |
| 4.3.2 | Low-temperature boiler | 23 |
| 4.3.3 | Gas condensing boiler) | 24 |
| 4.4 | Modular boiler | 24 |
| 5 | Constructional requirements | 24 |
| 5.1 | General | 24 |
| 5.2 | Conversion to different gases | 24 |
| 5.3 | Materials and method of construction | 24 |
| 5.3.1 | General | 24 |
| 5.3.2 | Materials and thicknesses of walls or tubes under water pressure | 25 |
| 5.3.3 | Thermal insulation | 33 |
| 5.4 | Combustion products evacuation duct | 34 |
| 5.4.1 | Stability under mechanical loading | 34 |
| 5.4.2 | Stability under exposure to heat | 34 |

| | | |
|--------|---|----|
| 5.4.3 | Corrosion resistance | 34 |
| 5.4.4 | Resistance to condensate and moisture under normal operating conditions | 34 |
| 5.5 | Design | 34 |
| 5.5.1 | General | 34 |
| 5.5.2 | Modular boilers | 35 |
| 5.6 | Use and servicing | 35 |
| 5.7 | Connections to the gas and water pipes | 35 |
| 5.7.1 | General | 35 |
| 5.7.2 | Connections to the gas pipe | 35 |
| 5.7.3 | Connections to the central heating circuit | 36 |
| 5.8 | Soundness | 36 |
| 5.8.1 | Soundness of the gas circuit | 36 |
| 5.8.2 | Soundness of the combustion circuit | 36 |
| 5.9 | Supply of combustion air and the evacuation of the combustion products | 37 |
| 5.9.1 | General | 37 |
| 5.9.2 | Air supply and combustion products evacuation duct) | 37 |
| 5.9.3 | Terminal | 37 |
| 5.9.4 | Terminal guard | 37 |
| 5.9.5 | Fitting piece | 38 |
| 5.9.6 | Control dampers in the air or combustion products circuit | 38 |
| 5.9.7 | Special requirements for certain components of boilers with a fan | 38 |
| 5.9.8 | Condensate discharge | 39 |
| 5.10 | Checking the state of operation | 40 |
| 5.11 | Drainage | 40 |
| 5.12 | Electrical equipment | 40 |
| 5.13 | Operational safety in the event of failure of the auxiliary energy | 40 |
| 5.14 | Adjusting, control and safety devices | 40 |
| 5.14.1 | General | 40 |
| 5.14.2 | Adjusters and range rating devices | 41 |
| 5.14.3 | Gas circuit | 41 |
| 5.14.4 | Gas pressure regulator | 43 |
| 5.14.5 | Ignition devices | 43 |
| 5.14.6 | Flame supervision systems | 44 |
| 5.14.7 | Thermostats and water temperature limiting devices | 45 |
| 5.15 | Burners | 46 |
| 5.16 | Pressure test points | 46 |
| 5.17 | Chemical composition of the condensate | 46 |
| 6 | Operational requirements | 46 |
| 6.1 | General | 46 |
| 6.2 | Soundness | 46 |
| 6.2.1 | Soundness of the gas circuit | 46 |
| 6.2.2 | Soundness of the combustion circuit | 47 |
| 6.2.3 | Soundness of the water circuit | 48 |
| 6.3 | Nominal, maximum and minimum heat inputs, and nominal output | 48 |
| 6.3.1 | Nominal heat input or maximum and minimum heat inputs | 48 |
| 6.3.2 | Adjustment of the heat input by the downstream pressure | 48 |
| 6.3.3 | Ignition rate | 48 |
| 6.3.4 | Nominal output | 48 |
| 6.3.5 | Gas pressure regulator | 48 |
| 6.4 | Safety of operation | 49 |
| 6.4.1 | Limiting temperatures | 49 |
| 6.4.2 | Ignition - Cross-lighting - Flame stability | 50 |
| 6.4.3 | Pre-purge | 51 |
| 6.4.4 | Functioning of a permanent ignition burner when the fan stops during the standby time . | 52 |
| 6.5 | Adjusting, control and safety devices | 52 |
| 6.5.1 | General | 52 |
| 6.5.2 | Ignition devices | 52 |
| 6.5.3 | Flame supervision devices | 53 |
| 6.5.4 | Ignition burner and ignition rates | 55 |
| 6.5.5 | Air proving | 55 |
| 6.5.6 | Gas pressure switches | 56 |

| | | |
|-------|---|-----|
| 6.5.7 | Control thermostat and safety temperature limiter | 57 |
| 6.5.8 | Condensate discharge blockage | 58 |
| 6.6 | Combustion | 58 |
| 6.6.1 | Carbon monoxide | 58 |
| 6.6.2 | Limit conditions | 58 |
| 6.6.3 | Special conditions | 58 |
| 6.6.4 | Sooting | 58 |
| 6.6.5 | Other pollutants | 58 |
| 6.7 | Useful efficiencies | 59 |
| 6.7.1 | Useful efficiency at the nominal heat input | 59 |
| 6.7.2 | Useful efficiency at part load | 59 |
| 6.8 | Criteria for condensation in the flue | 60 |
| 6.9 | Resistance of the materials to pressure | 60 |
| 6.9.1 | General | 60 |
| 6.9.2 | Boilers of sheet steel or non-ferrous metals | 60 |
| 6.9.3 | Boilers of cast iron and cast materials | 60 |
| 6.10 | Hydraulic resistance | 61 |
| 6.11 | Condensation in the boiler | 61 |
| 6.12 | Combustion air and flue dampers | 61 |
| 7 | Test methods | 61 |
| 7.1 | General | 61 |
| 7.1.1 | Characteristics of the reference and limit gases | 61 |
| 7.1.2 | General test conditions | 67 |
| 7.2 | Soundness | 70 |
| 7.2.1 | Soundness of the gas circuit | 70 |
| 7.2.2 | Soundness of the combustion circuit | 71 |
| 7.2.3 | Soundness of the water circuit | 72 |
| 7.3 | Nominal, maximum and minimum heat inputs, and nominal output | 72 |
| 7.3.1 | Nominal heat input or maximum and minimum heat inputs | 72 |
| 7.3.2 | Adjustment of the heat input by the downstream pressure | 73 |
| 7.3.3 | Ignition rate | 74 |
| 7.3.4 | Nominal output | 74 |
| 7.3.5 | Gas pressure regulator | 74 |
| 7.4 | Safety of operation | 74 |
| 7.4.1 | Limiting temperatures | 74 |
| 7.4.2 | Ignition - Cross-lighting - Flame stability | 76 |
| 7.4.3 | Pre-purge | 79 |
| 7.4.4 | Functioning of a permanent ignition burner when the fan stops during standby time | 80 |
| 7.5 | Adjusting, control and safety devices | 80 |
| 7.5.1 | General | 80 |
| 7.5.2 | Ignition devices | 80 |
| 7.5.3 | Flame supervision devices | 81 |
| 7.5.4 | Ignition burner and ignition rates | 83 |
| 7.5.5 | Air proving | 83 |
| 7.5.6 | Gas pressure switches | 85 |
| 7.5.7 | Control thermostat and safety temperature limiter | 85 |
| 7.5.8 | Condensate discharge blockage | 87 |
| 7.6 | Combustion | 87 |
| 7.6.1 | Carbon monoxide | 87 |
| 7.6.2 | Limit conditions | 88 |
| 7.6.3 | Special conditions | 89 |
| 7.6.4 | Other pollutants | 91 |
| 7.7 | Useful efficiencies | 95 |
| 7.7.1 | Useful efficiency at the nominal heat input | 95 |
| 7.7.2 | Useful efficiency at part load | 96 |
| 7.8 | Criteria for condensation in the flue | 101 |
| 7.8.1 | Determination of flue losses | 101 |
| 7.8.2 | Minimum temperature of the combustion products | 102 |
| 7.9 | Resistance of materials to pressure | 102 |
| 7.9.1 | General | 102 |
| 7.9.2 | Boilers of sheet steel or non-ferrous metals | 102 |

| | | |
|---|--|-----|
| 7.9.3 | Boilers of cast iron and cast materials | 103 |
| 7.10 | Hydraulic resistance | 103 |
| 7.11 | Condensation in the boiler | 103 |
| 7.12 | Combustion air and flue dampers | 103 |
| 8 | Marking and instructions | 104 |
| 8.1 | Marking of the boiler | 104 |
| 8.1.1 | General | 104 |
| 8.1.2 | Data plate | 104 |
| 8.1.3 | Supplementary marking | 106 |
| 8.1.4 | Packaging | 108 |
| 8.1.5 | Warnings on the boiler and on the packaging | 108 |
| 8.1.6 | Other information | 108 |
| 8.2 | Instructions | 108 |
| 8.2.1 | Technical instructions for the installer | 108 |
| 8.2.2 | For installation of the combustion circuit | 109 |
| 8.2.3 | Use and maintenance instructions for the user | 110 |
| 8.2.4 | Conversion instructions | 111 |
| 8.3 | Presentation | 111 |
| Annex A (informative) National situations | | 127 |
| A.1 | Categories marketed in the various countries | 127 |
| A.2 | Special categories marketed nationally or locally | 129 |
| A.3 | Gas groups distributed locally | 129 |
| A.4 | Boiler supply pressures | 130 |
| A.5 | Gas connections in common use in the various countries | 132 |
| Annex B (informative) Special national conditions | | 133 |
| Annex C (informative) A-deviations | | 134 |
| Annex D (informative) Classification of type C boilers | | 135 |
| Annex E (informative) Practical method of calibrating the test rig to enable the heat loss D_p to be determined | | 142 |
| Annex F (informative) Main symbols and abbreviations used | | 143 |
| Annex G (informative) Compilation of test conditions | | 144 |
| Annex H (informative) Valving | | 147 |
| H.1 | General | 147 |
| H.2 | Boilers with permanent ignition burner or alternating ignition burner or leakage control device or with pre-purge | 147 |
| H.2.1 | Heat inputs up to 150 kW | 147 |
| H.2.2 | Heat inputs up to 300 kW | 148 |
| H.3 | Boilers without permanent ignition burner or alternating ignition burner, without leakage control device and without pre-purge | 149 |
| H.3.1 | Heat inputs up to 150 kW | 149 |
| H.3.2 | Heat inputs up to 300 kW | 150 |
| H.4 | Heat inputs exceeding 300 kW but not exceeding 1 000 kW | 151 |
| H.4.1 | Boilers with permanent ignition burner or alternating ignition burner or leakage control device or with pre-purge | 151 |
| H.4.2 | Boilers without permanent ignition burner or alternating ignition burner, without a leakage control device and without pre-purge | 152 |
| Annex I (informative) Determination of the heat losses from the test rig of the indirect method and the contributions of the circulating pump of the test rig | | 153 |
| Annex J (informative) Means of determining the ignition time at full rate | | 154 |

| | |
|--|------------|
| Annex K (informative) Example of the calculation of the NO_x weighting factors for a boiler with several rates | 155 |
| K.1 Apportioning of Q_{pi} = 20 % | 155 |
| K.2 Apportioning of Q_{pi} = 40 % | 155 |
| K.3 Apportioning of Q_{pi} = 60 % | 155 |
| K.4 Apportioning of Q_{pi} = 70 % | 156 |
| K.5 Total apportioning | 156 |
| Annex L (informative) Calculation of conversions of NO_x | 157 |
| Annex M (normative) Test apparatus for type C2 boilers (see 7.4.2.3.3) | 158 |
| Annex N (informative) Requirements and test methods for separate air supply and combustion products evacuation ducts of type C6 boilers) | 159 |
| N.1 Requirements | 159 |
| N.1.1 Pressure losses | 159 |
| N.1.2 Pressure loss under the influence of wind | 159 |
| N.1.3 Suction under the influence of wind | 159 |
| N.1.4 Recirculation of the combustion products | 159 |
| N.2 Test methods | 160 |
| N.2.1 Pressure loss in still air | 160 |
| N.2.2 Pressure loss under the influence of wind | 160 |
| N.2.3 Suction under the influence of wind | 160 |
| N.2.4 Recirculation of the combustion products | 161 |
| N.2.5 Wind test conditions | 161 |
| Annex O (informative) Use of test gases | 164 |
| O.1 Boilers within a range | 164 |
| O.2 Guidance on the use of test gases | 164 |
| Annex ZA (informative) Clauses of this European Standard addressing essential requirements or provisions of EU Directives | 165 |
| Bibliography | 168 |