DIN EN 12007-2:2012-10 (E)

Gas infrastructure - Pipelines for maximum operating pressure up to a nd including 16 bar - Part 2: Specific functional requirements for polyethylene (MOP up to and including 10 bar)

Contents

Page

Foreword 4

1 Scope 5

2 Normative references 5

3 Terms, definitions, symbols and abbreviations 6

4 Design 7
4.1 General 7
4.2 Materials and components 7
4.3 Maximum operating pressure 7
4.3.1 General 7
4.3.2 Verification of the overall service (design) coefficient 8
4.3.3 Verification of the RCP criterion 8
4.4 Assembly techniques 10
4.5 Material properties for flow stopping by squeeze-off 10
4.6 Pipework inside buildings 10

5 Construction 10
5.1 Storage, handling and transportation 10
5.2 Jointing 11
5.2.1 General 11
5.2.2 Fusion jointing 11
5.2.3 Mechanical joints 12
5.3 Laying 12
5.4 Connection to existing systems 13
5.4.1 Static electricity 13
5.4.2 Squeeze-off 13

6 Quality control 14
6.1 Inspection prior to installation 14
6.2 Inspection during laying 14
6.2.1 Laying 14
6.2.2 Joint integrity 14

7 Pressure testing 14

Annex A (informative) Storage, handling and transportation 16

A.1 General 16
A.2 Storage 16
A.2.1 Storage conditions 16
A.2.2 Bundles 16
A.2.3 Stacking loose straight pipes 17
A.2.4 Drums and coils 17
A.2.5 Storing 17
A.2.6 First in - first out 18
A.3 Handling 18

A.3.1 General 18
A.3.2 Handling in cold weather 18
A.3.3 Straight pipes 18
A.3.4 Coils 18
A.3.5 Drums 18
A.3.6 Uncoiling 19
A.4 Transportation 19
A.4.1 Straight pipes 19
A.4.2 Coiled pipe 19
A.4.3 Drums 19

Annex B (informative) Fusion joint integrity 20

B.1 General 20
B.2 Visual inspection criteria 20
B.2.1 General 20
B.2.2 Butt fusion guidelines for the visual examination of butt fusion joints 20
B.2.3 Electrofusion 23
B.2.4 Ancillary tooling 26

Bibliography 28