DIN EN 12405-3:2016-04 (E)

Gas meters - Conversion devices - Part 3: Flow computer

Contents

Page

European foreword 5

Introduction 6

1 Scope 8

2 Normative references 8

3 Terms, definitions and symbols 10
3.1 Terms and definitions 10
3.2 Symbols and subscripts 16
3.3 Abbreviations 18
3.4 Environmental classification for flow computers 18
3.4.1 Climatic conditions 18
3.4.2 Mechanical conditions 18
3.4.3 Electrical and Electromagnetic conditions 18

4 Principle of measurement 18
4.1 General 18
4.2 Correction functions 19
4.2.1 General 19
4.2.2 Correction of the volume at measurement conditions 20
4.2.3 Temperature and pressure correction of USM body dimension 23
4.2.4 Temperature and pressure measurement correction for conversion 23

5 Rated operating conditions 23
5.1 Specified field of measurement 23
5.1.1 General 23
5.1.2 Specified measurement range for gas pressure 23
5.1.3 Specified measurement range for gas temperature 24
5.1.4 Gas characteristics 24
5.1.5 Base conditions 24
5.2 Environmental conditions 24
5.2.1 Ambient temperature range 24
5.2.2 Humidity range 24
5.3 Power supply 24

6 Construction requirements 25
6.1 General 25
6.2 Sealing 25
6.3 Time measuring functions 27
6.3.1 Clock 27
6.3.2 Time interval 27
6.4 Casings 28
6.5 Indications 28
6.5.1 General 28
6.5.2 Electronic indicating device 30
6.6 Inputs for volume conversion 30
6.7 Alarms in flow computer 31
6.7.1 Detection of defective operation situations 31
6.7.2 Handling of volumes during maintenance 31
6.7.3 Memorization of metrological data 31

6.7.4 Handling of alarms 31
6.8 Specific monitoring functions performed by flow computer 31
6.8.1 General 31
6.8.2 Turbine Meter health check (Mechanical meter) 33
6.8.3 USM health check (meter integrity check) 34
6.8.4 Gas analysis devices health check 35
6.8.5 p-T transducer health check 36
6.8.6 Self check of the Z algorithm 36
6.8.7 Volume comparison 36
6.8.8 Gas quality comparison 38
6.9 Cut-off function 38
6.10 Long-term data storage 38
6.10.1 General 38
6.10.2 Categories of data to be stored 39
6.10.3 Triggers and methods for storage 39
6.10.4 Clock-time stamps 40
6.10.5 Security (physical, electronic and software) 40
6.10.6 Error handling 41
6.10.7 Long term data storage - Security audit 41

7 Installation requirements 42
7.1 General 42
7.2 Calculator 43
7.3 Temperature transducer 43
7.4 Pressure transducer 43

8 Performance 44
8.1 Reference conditions 44
8.2 Rated operating conditions 44
8.3 Maximum permissible errors 44
8.3.1 General 44
8.3.2 Global approach: error of main indication 45
8.3.3 Modular approach: specific errors for a FC 45
8.4 Conditions of matching the constituent elements of a FC 45
8.5 Influence factors 46
8.6 Disturbances 46
8.7 Durability 46
8.8 Repeatability 46
8.9 Reliability 46
8.10 Adjustment and calibration of the transducers 47

9 Tests of conformity 47
9.1 Verification of the construction requirements 47
9.2 Verification of the performance requirements 48
9.2.1 Test conditions 48
9.2.2 Samples of FC required for testing 49

10 Marking 50

11 Installation and operating instructions 51

Annex A (normative) Type test 52

A.1 General conditions 52
A.2 Accuracy tests under reference conditions 54
A.3 Effect of ambient temperature 55
A.4 Effect of damp heat, steady-state test 55
A.5 Effect of damp heat, cyclic test 56
A.6 Electrical power variation 56
A.7 Short time power reductions 57
A.8 Electrical bursts 58
A.9 Electromagnetic susceptibility 58

A.10 Electrostatic discharges 59
A.11 Overload of pressure (only for pressure transducers) 59
A.12 Effect of vibrations 60
A.13 Effect of shocks 60
A.14 Overload of pressure (mechanical) (only for pressure transducer) 61
A.15 Durability 61
A.16 Alarms operation 62
A.17 Repeatability 63
A.18 Short time DC power variations 63
A.19 Surges on supply lines and/or signal lines 64
A.20 Power frequency magnetic field 64

Annex B (normative) Pressure transducers 65

B.1 Scope 65
B.2 Rated operating conditions 65
B.3 Construction requirements 65
B.4 Performances 66
B.5 Tests of conformity 67
B.6 Marking 67

Annex C (normative) Temperature transducers 68

C.1 Scope 68
C.2 Rated operating conditions 68
C.3 Construction requirements 68
C.4 Performances 69
C.5 Tests of conformity 70
C.6 Marking 70

Annex D (normative) Requirements and testing of meter error correction 71

D.1 General 71
D.2 Verification of the volumetric flow rate determination 71
D.3 Verification of the gas density calculation procedure 71
D.4 Verification of the gas viscosity calculation procedures 72
D.5 Verification of the error transposition from e(Qi) to e(Rei) 72
D.6 Verification of the error function (Q) or (Re) interpolation or approximation 73
D.7 Verification of correction factor F(Q) or F(Re), corrected flow rate and corrected volume determination 73
D.8 Verification of the activation and deactivation of error correction calculations on limits of its application 73

Annex E (informative) Range of application of meter error correction with functions: e(Q) or e (Re) .74

E.1 General 74
E.2 Range of application 74
E.3 Example for turbine meters working at pop nearly constant 75

Bibliography 77