

ISO 16903:2015-06 (E)

Petroleum and natural gas industries - Characteristics of LNG, influencing the design, and material selection

| Contents | | Page |
|-----------------|--|-------------|
| Foreword | | iv |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Abbreviated terms | 2 |
| 5 | General characteristics of LNG | 2 |
| 5.1 | General | 2 |
| 5.2 | Properties of LNG | 2 |
| 5.2.1 | Composition | 2 |
| 5.2.2 | Density | 2 |
| 5.2.3 | Temperature | 3 |
| 5.2.4 | Viscosity | 3 |
| 5.2.5 | Examples of LNG | 3 |
| 5.3 | Physical properties | 3 |
| 5.3.1 | Physical properties of boil-off gas | 3 |
| 5.3.2 | Flash | 4 |
| 5.3.3 | Spillage of LNG | 4 |
| 5.3.4 | Expansion and dispersion of gas clouds | 4 |
| 5.3.5 | Ignition | 5 |
| 5.3.6 | Pool fires | 5 |
| 5.3.7 | Development and consequences of pressure waves | 5 |
| 5.3.8 | Containment | 5 |
| 5.3.9 | Rollover | 5 |
| 5.3.10 | RPT | 6 |
| 5.3.11 | BLEVE | 6 |
| 6 | Health and safety | 6 |
| 6.1 | General | 6 |
| 6.2 | Exposure to cold | 7 |
| 6.2.1 | Warning notice | 7 |
| 6.2.2 | Handling, cold contact burns | 7 |
| 6.2.3 | Frostbite | 7 |
| 6.2.4 | Effect of cold on the lungs | 7 |
| 6.2.5 | Hypothermia | 7 |
| 6.2.6 | Recommended protective clothing | 7 |
| 6.3 | Exposure to gas | 7 |
| 6.3.1 | Toxicity | 7 |
| 6.3.2 | Asphyxia | 7 |
| 6.4 | Fire precautions and protection | 8 |
| 6.5 | Colour | 8 |
| 6.6 | Odour | 8 |
| 7 | Materials of construction | 8 |
| 7.1 | Materials used in the LNG industry | 8 |
| 7.1.1 | General | 8 |
| 7.1.2 | Materials in direct contact | 8 |

| | | |
|--------------------|--|----|
| 7.1.3 | Materials not in direct contact under normal operation | 9 |
| 7.1.4 | Other information | 9 |
| 7.2 | Thermal stresses | 10 |
| Bibliography | | 11 |